
EPIC

COMPONENTS

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 96 for grommet locations; and page 94 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 211 for support options
- Refer to pages 663-705 for accessories

BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
			D	W	H	A	KW			
RECTANGULAR WORKSURFACE										
36" DEPTH										
SOFTENED RIM										
	25N3684WSSW	Wood	\$ 1210	36 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	117 lbs.	4.0
	25N3684WSSL	Laminate	823	36 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	117 lbs.	4.0
	25N3678WSSW	Wood	\$ 1120	36 ¹ / ₁₆	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	108 lbs.	4.0
	25N3678WSSL	Laminate	761	36 ¹ / ₁₆	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	108 lbs.	4.0
	25N3672WSSW	Wood	\$ 1030	36 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	100 lbs.	4.0
	25N3672WSSL	Laminate	700	36 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	100 lbs.	4.0
	KNIFE RIM									
	25N3884WSSWK1	Wood	\$ 1575	37 ⁷ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	120 lbs.	4.2
	25N3884WSSLK1	Laminate	1278	37 ⁷ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	120 lbs.	4.2
	25N3878WSSWK1	Wood	\$ 1457	37 ⁷ / ₁₆	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	111 lbs.	4.2
	25N3878WSSLK1	Laminate	1178	37 ⁷ / ₁₆	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	111 lbs.	4.2
	25N3872WSSWK1	Wood	\$ 1341	37 ⁷ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	103 lbs.	4.2
25N3872WSSLK1	Laminate	1087	37 ⁷ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	103 lbs.	4.2	
25N3984WSSWK2	Wood	\$ 1575	39 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	120 lbs.	4.4	
25N3984WSSLK2	Laminate	1278	39 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	120 lbs.	4.4	
25N3978WSSWK2	Wood	\$ 1457	39 ¹ / ₁₆	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	117 lbs.	4.4	
25N3978WSSLK2	Laminate	1178	39 ¹ / ₁₆	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	117 lbs.	4.4	
25N3972WSSWK2	Wood	\$ 1341	39 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	108 lbs.	4.4	
25N3972WSSLK2	Laminate	1087	39 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	108 lbs.	4.4	

- Wire Manager available on left side, back, right side, back & left or back & right; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Worksurfaces can be ordered in 1/8" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 29" deep component pedestals
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 211
- For undersurface wire managers, see page 685

TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminite models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminite Top Color
10. Worksurface Sheen (wood models)


SAMPLE MODEL NUMBERS:

25N3684WSSL M V403 G11MBLR X X 83½ 807
 25N3984WSSLK2 E K403 G11MBLR D1B403 X X 807

• See pages 91-95 for all options available in Epic

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET
		D	W	H				
RECTANGULAR WORKSURFACE 30" DEPTH								
SOFTENED RIM								
25N3096WSSW Wood	\$ 1120	30½	95½	1¾	—	—	111 lbs.	4.0
25N3096WSSL Laminate	688	30½	95½	1¾	—	—	111 lbs.	4.0
25N3090WSSW Wood	\$ 1076	30½	89½	1¾	—	—	104 lbs.	3.9
25N3090WSSL Laminate	666	30½	89½	1¾	—	—	104 lbs.	3.9
25N3084WSSW Wood	\$ 1030	30½	83½	1¾	—	—	97 lbs.	3.7
25N3084WSSL Laminate	640	30½	83½	1¾	—	—	97 lbs.	3.7
25N3078WSSW Wood	\$ 938	30½	77½	1¾	—	—	90 lbs.	3.6
25N3078WSSL Laminate	577	30½	77½	1¾	—	—	90 lbs.	3.6
25N3072WSSW Wood	\$ 849	30½	71½	1¾	—	—	83 lbs.	3.5
25N3072WSSL Laminate	519	30½	71½	1¾	—	—	83 lbs.	3.5
25N3066WSSW Wood	\$ 817	30½	66	1¾	—	—	76 lbs.	3.4
25N3066WSSL Laminate	476	30½	66	1¾	—	—	76 lbs.	3.4
25N3060WSSW Wood	\$ 799	30½	60	1¾	—	—	69 lbs.	3.3
25N3060WSSL Laminate	434	30½	60	1¾	—	—	69 lbs.	3.3
25N3054WSSW Wood	\$ 781	30½	54	1¾	—	—	63 lbs.	3.0
25N3054WSSL Laminate	399	30½	54	1¾	—	—	63 lbs.	3.0
25N3048WSSW Wood	\$ 764	30½	48½	1¾	—	—	56 lbs.	2.7
25N3048WSSL Laminate	363	30½	48½	1¾	—	—	56 lbs.	2.7

RECTANGULAR WORKSURFACE 30" DEPTH



- Wire Manager available on left side, back, right side, back & left or back & right; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Worksurfaces can be ordered in ½" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 23" or 29" deep pedestals
- Worksurfaces up to 72" wide can be used for table desking applications
- Specify center grommet only when using C-leg bases; field installed grommets are also available
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 211
- For Epicenter depth worksurfaces see pages 244-246
- For undersurface wire managers, see page 685

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 96 for grommet locations; and page 94 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 211 for support options
- Refer to pages 663-705 for accessories


BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
		D	W	H	A	KW		
RECTANGULAR WORKSURFACE 30" DEPTH (CONTINUED)								
KNIFE RIM								
25N3296WSSWK1 Wood	\$ 1457	31 $\frac{1}{16}$ "	95 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	119 lbs.	4.2
25N3296WSSLK1 Laminate	1067	31 $\frac{1}{16}$ "	95 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	119 lbs.	4.2
25N3290WSSWK1 Wood	\$ 1398	31 $\frac{1}{16}$ "	89 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	111 lbs.	4.1
25N3290WSSLK1 Laminate	1030	31 $\frac{1}{16}$ "	89 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	111 lbs.	4.1
25N3284WSSWK1 Wood	\$ 1341	31 $\frac{1}{16}$ "	83 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	104 lbs.	3.9
25N3284WSSLK1 Laminate	992	31 $\frac{1}{16}$ "	83 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	104 lbs.	3.9
25N3278WSSWK1 Wood	\$ 1221	31 $\frac{1}{16}$ "	77 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	96 lbs.	3.8
25N3278WSSLK1 Laminate	894	31 $\frac{1}{16}$ "	77 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	96 lbs.	3.8
25N3272WSSWK1 Wood	\$ 1102	31 $\frac{1}{16}$ "	71 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	89 lbs.	3.7
25N3272WSSLK1 Laminate	805	31 $\frac{1}{16}$ "	71 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	89 lbs.	3.7
25N3266WSSWK1 Wood	\$ 1061	31 $\frac{1}{16}$ "	66"	1 $\frac{3}{16}$ "	—	—	82 lbs.	3.6
25N3266WSSLK1 Laminate	737	31 $\frac{1}{16}$ "	66"	1 $\frac{3}{16}$ "	—	—	82 lbs.	3.6
25N3260WSSWK1 Wood	\$ 1039	31 $\frac{1}{16}$ "	60"	1 $\frac{3}{16}$ "	—	—	74 lbs.	3.5
25N3260WSSLK1 Laminate	673	31 $\frac{1}{16}$ "	60"	1 $\frac{3}{16}$ "	—	—	74 lbs.	3.5
25N3254WSSWK1 Wood	\$ 1015	31 $\frac{1}{16}$ "	54"	1 $\frac{3}{16}$ "	—	—	67 lbs.	3.2
25N3254WSSLK1 Laminate	618	31 $\frac{1}{16}$ "	54"	1 $\frac{3}{16}$ "	—	—	67 lbs.	3.2
25N3248WSSWK1 Wood	\$ 995	31 $\frac{1}{16}$ "	48 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	59 lbs.	2.8
25N3248WSSLK1 Laminate	563	31 $\frac{1}{16}$ "	48 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	59 lbs.	2.8



- Wire Manager available on left side, back, right side, back & left or back & right; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Worksurfaces can be ordered in $\frac{1}{16}$ " increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 23" or 29" deep pedestals
- Worksurfaces up to 72" wide can be used for table desking applications
- Specify center grommet only when using C-leg bases; field installed grommets are also available
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 211
- For Epicenter depth worksurfaces see pages 244-246
- For undersurface wire managers, see page 685


TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminite models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminite Top Color
10. Worksurface Sheen (wood models)

SAMPLE MODEL NUMBER:

25N3378WSSLK2 M K478 G1A X X X 478

• See pages 91-95 for all options available in Epic

RECTANGULAR WORKSURFACE 30" DEPTH (CONTINUED)	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET	
			D	W	H					
	KNIFE RIM (CONTINUED)									
	25N3396WSSWK2	Wood	\$ 1457	33 ¹ / ₈	95 ¹ / ₈	1 ¹ / ₈	—	—	122 lbs.	4.4
	25N3396WSSLK2	Laminite	1067	33 ¹ / ₈	95 ¹ / ₈	1 ¹ / ₈	—	—	122 lbs.	4.4
	25N3390WSSWK2	Wood	\$ 1398	33 ¹ / ₈	89 ¹ / ₈	1 ¹ / ₈	—	—	114 lbs.	4.3
	25N3390WSSLK2	Laminite	1030	33 ¹ / ₈	89 ¹ / ₈	1 ¹ / ₈	—	—	114 lbs.	4.3
	25N3384WSSWK2	Wood	\$ 1341	33 ¹ / ₈	83 ¹ / ₈	1 ¹ / ₈	—	—	107 lbs.	4.1
	25N3384WSSLK2	Laminite	992	33 ¹ / ₈	83 ¹ / ₈	1 ¹ / ₈	—	—	107 lbs.	4.1
	25N3378WSSWK2	Wood	\$ 1221	33 ¹ / ₈	77 ¹ / ₈	1 ¹ / ₈	—	—	99 lbs.	4.0
	25N3378WSSLK2	Laminite	894	33 ¹ / ₈	77 ¹ / ₈	1 ¹ / ₈	—	—	99 lbs.	4.0
	25N3372WSSWK2	Wood	\$ 1102	33 ¹ / ₈	71 ¹ / ₈	1 ¹ / ₈	—	—	92 lbs.	3.9
	25N3372WSSLK2	Laminite	805	33 ¹ / ₈	71 ¹ / ₈	1 ¹ / ₈	—	—	92 lbs.	3.9
	25N3366WSSWK2	Wood	\$ 1061	33 ¹ / ₈	66	1 ¹ / ₈	—	—	84 lbs.	3.8
	25N3366WSSLK2	Laminite	737	33 ¹ / ₈	66	1 ¹ / ₈	—	—	84 lbs.	3.8
	25N3360WSSWK2	Wood	\$ 1039	33 ¹ / ₈	60	1 ¹ / ₈	—	—	76 lbs.	3.6
	25N3360WSSLK2	Laminite	673	33 ¹ / ₈	60	1 ¹ / ₈	—	—	76 lbs.	3.6
	25N3354WSSWK2	Wood	\$ 1015	33 ¹ / ₈	54	1 ¹ / ₈	—	—	69 lbs.	3.3
	25N3354WSSLK2	Laminite	618	33 ¹ / ₈	54	1 ¹ / ₈	—	—	69 lbs.	3.3
	25N3348WSSWK2	Wood	\$ 995	33 ¹ / ₈	48 ¹ / ₈	1 ¹ / ₈	—	—	61 lbs.	3.0
	25N3348WSSLK2	Laminite	563	33 ¹ / ₈	48 ¹ / ₈	1 ¹ / ₈	—	—	61 lbs.	3.0

- Wire Manager available on left side, back, right side, back & left or back & right; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Worksurfaces can be ordered in 1/8" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 23" or 29" deep pedestals
- Worksurfaces up to 72" wide can be used for table desking applications
- Specify center grommet only when using C-leg bases; field installed grommets are also available
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 211
- For Epicenter depth worksurfaces see pages 244-246
- For undersurface wire managers, see page 685

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 96 for grommet locations; and page 94 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 211 for support options
- Refer to pages 663-705 for accessories

BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

RECTANGULAR WORKSURFACE 24" DEPTH	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
			D	W	H	A	KW		
	SOFTENED RIM								
	25N2496WSSW Wood	\$ 1031	24	95 ¹ / ₁₆	1 ³ / ₁₆	—	—	89 lbs.	3.6
	25N2496WSSL Laminate	607	24	95 ¹ / ₁₆	1 ³ / ₁₆	—	—	89 lbs.	3.6
	25N2490WSSW Wood	\$ 987	24	89 ¹ / ₁₆	1 ³ / ₁₆	—	—	83 lbs.	3.5
	25N2490WSSL Laminate	583	24	89 ¹ / ₁₆	1 ³ / ₁₆	—	—	83 lbs.	3.5
	25N2484WSSW Wood	\$ 939	24	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	78 lbs.	3.2
	25N2484WSSL Laminate	560	24	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	78 lbs.	3.2
	25N2478WSSW Wood	\$ 850	24	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	72 lbs.	3.3
	25N2478WSSL Laminate	497	24	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	72 lbs.	3.3
	25N2472WSSW Wood	\$ 758	24	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	67 lbs.	3.3
	25N2472WSSL Laminate	434	24	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	67 lbs.	3.3
	25N2466WSSW Wood	\$ 729	24	66	1 ³ / ₁₆	—	—	61 lbs.	3.1
	25N2466WSSL Laminate	402	24	66	1 ³ / ₁₆	—	—	61 lbs.	3.1
	25N2460WSSW Wood	\$ 709	24	60	1 ³ / ₁₆	—	—	56 lbs.	2.8
	25N2460WSSL Laminate	381	24	60	1 ³ / ₁₆	—	—	56 lbs.	2.8
	25N2454WSSW Wood	\$ 690	24	54	1 ³ / ₁₆	—	—	50 lbs.	2.5
	25N2454WSSL Laminate	337	24	54	1 ³ / ₁₆	—	—	50 lbs.	2.5
	25N2448WSSW Wood	\$ 675	24	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	44 lbs.	2.3
	25N2448WSSL Laminate	306	24	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	44 lbs.	2.3

- Wire Manager available on left side, back, right side, back & left or back & right; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Worksurfaces can be ordered in ¹/₁₆" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 23" deep pedestals
- Worksurfaces up to 72" wide can be used for table desking applications
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 211
- For worksurfaces with grain direction running front-to-back see pages 164-165
- For Epicenter depth worksurfaces see pages 247-251
- For undersurface wire managers, see page 685


TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminite models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminite Top Color
10. Worksurface Sheen (wood models)

SAMPLE MODEL NUMBER:

25N2496WSSW M V X D1B462 X 95.5 R CL

• See pages 91-95 for all options available in Epic

RECTANGULAR WORKSURFACE 24" DEPTH (CONTINUED)	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS				A	KW	CARTONED WEIGHT	CUBIC FEET
			D	W	H					
	SOFTENED RIM (CONTINUED)									
	25N2442WSSW Wood	\$ 645	24	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	38 lbs.	2.3	
	25N2442WSSL Laminate	275	24	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	38 lbs.	2.3	
	25N2436WSSW Wood	\$ 621	24	36 ¹ / ₁₆	1 ³ / ₁₆	—	—	33 lbs.	1.8	
	25N2436WSSL Laminate	251	24	36 ¹ / ₁₆	1 ³ / ₁₆	—	—	33 lbs.	1.8	
	25N2430WSSW Wood	\$ 604	24	30 ¹ / ₁₆	1 ³ / ₁₆	—	—	28 lbs.	1.5	
	25N2430WSSL Laminate	225	24	30 ¹ / ₁₆	1 ³ / ₁₆	—	—	28 lbs.	1.5	

- Wire Manager available on left side, back, right side, back & left or back & right; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Worksurfaces can be ordered in ¹/₁₆" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 23" deep pedestals
- Worksurfaces up to 72" wide can be used for table desking applications
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 211
- For worksurfaces with grain direction running front-to-back see pages 164-165
- For Epicenter depth worksurfaces see pages 247-251
- For undersurface wire managers, see page 685

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 96 for grommet locations; and page 94 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 211 for support options
- Refer to pages 663-705 for accessories

BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

RECTANGULAR WORKSURFACE 24" DEPTH (CONTINUED)	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
			D	W	H	A	KW		
	25N2696WSSWK1 Wood	\$ 1342	25½	95¾	1¾	—	—	96 lbs.	3.8
	25N2696WSSLK1 Laminate	940	25½	95¾	1¾	—	—	96 lbs.	3.8
	25N2690WSSWK1 Wood	\$ 1281	25½	89¾	1¾	—	—	89 lbs.	3.7
	25N2690WSSLK1 Laminate	905	25½	89¾	1¾	—	—	89 lbs.	3.7
	25N2684WSSWK1 Wood	\$ 1222	25½	83¾	1¾	—	—	81 lbs.	3.6
	25N2684WSSLK1 Laminate	867	25½	83¾	1¾	—	—	81 lbs.	3.6
	25N2678WSSWK1 Wood	\$ 1103	25½	77¾	1¾	—	—	78 lbs.	3.5
	25N2678WSSLK1 Laminate	771	25½	77¾	1¾	—	—	78 lbs.	3.5
	25N2672WSSWK1 Wood	\$ 987	25½	71¾	1¾	—	—	72 lbs.	3.4
	25N2672WSSLK1 Laminate	673	25½	71¾	1¾	—	—	72 lbs.	3.4
	25N2666WSSWK1 Wood	\$ 951	25½	66	1¾	—	—	66 lbs.	3.3
	25N2666WSSLK1 Laminate	626	25½	66	1¾	—	—	66 lbs.	3.3
	25N2660WSSWK1 Wood	\$ 922	25½	60	1¾	—	—	60 lbs.	2.9
	25N2660WSSLK1 Laminate	592	25½	60	1¾	—	—	60 lbs.	2.9
	25N2654WSSWK1 Wood	\$ 896	25½	54	1¾	—	—	54 lbs.	2.6
	25N2654WSSLK1 Laminate	523	25½	54	1¾	—	—	54 lbs.	2.6
	25N2648WSSWK1 Wood	\$ 879	25½	48¾	1¾	—	—	48 lbs.	2.4
	25N2648WSSLK1 Laminate	472	25½	48¾	1¾	—	—	48 lbs.	2.4

- Wire Manager available on left side, back, right side, back & left or back & right; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Worksurfaces can be ordered in ¼" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 23" deep pedestals
- Worksurfaces up to 72" wide can be used for table desking applications
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 211
- For worksurfaces with grain direction running front-to-back see pages 164-165
- For Epicenter depth worksurfaces see pages 247-251
- For undersurface wire managers, see page 685


TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminate Top Color
10. Worksurface Sheen (wood models)

SAMPLE MODEL NUMBER:

25N2696WSSWK1 F K G1LR D1B461 25 94 MC

• See pages 91-95 for all options available in Epic

RECTANGULAR WORKSURFACE 24" DEPTH (CONTINUED)	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET
			D	W	H				
	KNIFE RIM (CONTINUED)								
	25N2642WSSWK1 Wood	\$ 837	25½	42½	1¾	—	—	42 lbs.	2.4
	25N2642WSSLK1 Laminate	426	25½	42½	1¾	—	—	42 lbs.	2.4
	25N2636WSSWK1 Wood	\$ 808	25½	36½	1¾	—	—	36 lbs.	1.9
	25N2636WSSLK1 Laminate	389	25½	36½	1¾	—	—	36 lbs.	1.9
	25N2630WSSWK1 Wood	\$ 785	25½	30½	1¾	—	—	30 lbs.	1.6
	25N2630WSSLK1 Laminate	347	25½	30½	1¾	—	—	30 lbs.	1.6
	25N2796WSSWK2 Wood	\$ 1342	27	95½	1¾	—	—	100 lbs.	4.0
	25N2796WSSLK2 Laminate	940	27	95½	1¾	—	—	100 lbs.	4.0
	25N2790WSSWK2 Wood	\$ 1281	27	89½	1¾	—	—	94 lbs.	3.9
	25N2790WSSLK2 Laminate	905	27	89½	1¾	—	—	94 lbs.	3.9
	25N2784WSSWK2 Wood	\$ 1222	27	83½	1¾	—	—	88 lbs.	3.7
	25N2784WSSLK2 Laminate	867	27	83½	1¾	—	—	88 lbs.	3.7
	25N2778WSSWK2 Wood	\$ 1103	27	77½	1¾	—	—	81 lbs.	3.6
	25N2778WSSLK2 Laminate	771	27	77½	1¾	—	—	81 lbs.	3.6
	25N2772WSSWK2 Wood	\$ 987	27	71½	1¾	—	—	75 lbs.	3.5
	25N2772WSSLK2 Laminate	673	27	71½	1¾	—	—	75 lbs.	3.5
	25N2766WSSWK2 Wood	\$ 951	27	66	1¾	—	—	69 lbs.	3.4
	25N2766WSSLK2 Laminate	626	27	66	1¾	—	—	69 lbs.	3.4

- Wire Manager available on left side, back, right side, back & left or back & right; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Worksurfaces can be ordered in ½" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a work surface with a size modification, specify desired depth and/or width
- For use with 23" deep pedestals
- Worksurfaces up to 72" wide can be used for table desking applications
- To provide additional work surface support when using in table desking applications, see undersurface support rails on page 211
- For work surfaces with grain direction running front-to-back see pages 164-165
- For Epicenter depth work surfaces see pages 247-251
- For undersurface wire managers, see page 685

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 96 for grommet locations; and page 94 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 211 for support options
- Refer to pages 663-705 for accessories

BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

RECTANGULAR WORKSURFACE 24" DEPTH (CONTINUED)	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
			D	W	H	A	KW		
	25N2760WSSWK2 Wood	\$ 922	27	60	1 3/8	—	—	63 lbs.	3.1
	25N2760WSSLK2 Laminate	592	27	60	1 3/8	—	—	63 lbs.	3.1
	25N2754WSSWK2 Wood	\$ 896	27	54	1 3/8	—	—	56 lbs.	2.8
	25N2754WSSLK2 Laminate	523	27	54	1 3/8	—	—	56 lbs.	2.8
	25N2748WSSWK2 Wood	\$ 879	27	48 1/2	1 3/8	—	—	50 lbs.	2.5
	25N2748WSSLK2 Laminate	472	27	48 1/2	1 3/8	—	—	50 lbs.	2.5
	25N2742WSSWK2 Wood	\$ 837	27	42 1/2	1 3/8	—	—	44 lbs.	2.3
	25N2742WSSLK2 Laminate	426	27	42 1/2	1 3/8	—	—	44 lbs.	2.3
	25N2736WSSWK2 Wood	\$ 808	27	36 1/2	1 3/8	—	—	38 lbs.	2.0
	25N2736WSSLK2 Laminate	389	27	36 1/2	1 3/8	—	—	38 lbs.	2.0
	25N2730WSSWK2 Wood	\$ 785	27	30 1/2	1 3/8	—	—	31 lbs.	1.7
	25N2730WSSLK2 Laminate	347	27	30 1/2	1 3/8	—	—	31 lbs.	1.7

- Wire Manager available on left side, back, right side, back & left or back & right; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Worksurfaces can be ordered in 1/8" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 23" deep pedestals
- Worksurfaces up to 72" wide can be used for table desking applications
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 211
- For worksurfaces with grain direction running front-to-back see pages 164-165
- For Epicenter depth worksurfaces see pages 247-251
- For undersurface wire managers, see page 685


TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminite models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminite Top Color
10. Worksurface Sheen (wood models)

SAMPLE MODEL NUMBER:

25N2760WSSWK2 E K G1A X X X N CL

• See pages 91-95 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
			D	W	H	A	KW			
RECTANGULAR WORKSURFACE 24" DEEP FOR STORAGE CREDENZAS 	SOFTENED RIM									
	25N24A96WSSL	Laminate	\$ 607	24	96½	1¾	—	—	89 lbs.	3.6
	25N24A90WSSL	Laminate	583	24	90½	1¾	—	—	83 lbs.	3.5
	25N24A84WSSL	Laminate	560	24	84½	1¾	—	—	78 lbs.	3.2
	25N24A78WSSL	Laminate	497	24	78½	1¾	—	—	72 lbs.	3.3
	25N24A72WSSL	Laminate	434	24	72½	1¾	—	—	67 lbs.	3.3
	25N24A66WSSL	Laminate	402	24	66½	1¾	—	—	61 lbs.	3.1
	25N24A60WSSL	Laminate	381	24	60½	1¾	—	—	56 lbs.	2.8
	KNIFE RIM									
	25N26A96WSSLK1	Laminate	\$ 940	25½	96½	1¾	—	—	96 lbs.	3.8
25N26A90WSSLK1	Laminate	905	25½	90½	1¾	—	—	89 lbs.	3.7	
25N26A84WSSLK1	Laminate	867	25½	84½	1¾	—	—	81 lbs.	3.6	
25N26A78WSSLK1	Laminate	771	25½	78½	1¾	—	—	78 lbs.	3.5	
25N26A72WSSLK1	Laminate	673	25½	72½	1¾	—	—	72 lbs.	3.4	
25N26A66WSSLK1	Laminate	626	25½	66½	1¾	—	—	66 lbs.	3.3	
25N26A60WSSLK1	Laminate	592	25½	60½	1¾	—	—	60 lbs.	2.9	

- For use in storage credenza application
- Wire Manager available on left side, back, right side, back & left or back & right; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- For use with 23" deep pedestals

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 96 for grommet locations; and page 94 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 211 for support options
- Refer to pages 663-705 for accessories

BASE MODEL KEY


- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
		D	W	H	A	KW		
RECTANGULAR WORKSURFACE 24" DEPTH								
SOFTENED RIM								
25N2460WSSVW Wood	\$ 709	24	60	1 ³ / ₁₆	—	—	56 lbs.	2.8
25N2460WSSVL Laminate	381	24	60	1 ³ / ₁₆	—	—	56 lbs.	2.8
25N2454WSSVW Wood	\$ 690	24	54	1 ³ / ₁₆	—	—	50 lbs.	2.5
25N2454WSSVL Laminate	337	24	54	1 ³ / ₁₆	—	—	50 lbs.	2.5
25N2448WSSVW Wood	\$ 675	24	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	44 lbs.	2.3
25N2448WSSVL Laminate	306	24	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	44 lbs.	2.3
25N2442WSSVW Wood	\$ 645	24	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	38 lbs.	2.1
25N2442WSSVL Laminate	275	24	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	38 lbs.	2.1
25N2436WSSVW Wood	\$ 621	24	36 ¹ / ₁₆	1 ³ / ₁₆	—	—	33 lbs.	1.8
25N2436WSSVL Laminate	251	24	36 ¹ / ₁₆	1 ³ / ₁₆	—	—	33 lbs.	1.8
25N2430WSSVW Wood	\$ 604	24	30 ¹ / ₁₆	1 ³ / ₁₆	—	—	28 lbs.	1.5
25N2430WSSVL Laminate	225	24	30 ¹ / ₁₆	1 ³ / ₁₆	—	—	28 lbs.	1.5
KNIFE RIM								
25N2660WSSVWK1 Wood	\$ 922	25 ¹ / ₂	60	1 ³ / ₁₆	—	—	60 lbs.	2.9
25N2660WSSVLK1 Laminate	592	25 ¹ / ₂	60	1 ³ / ₁₆	—	—	60 lbs.	2.9
25N2654WSSVWK1 Wood	\$ 896	25 ¹ / ₂	54	1 ³ / ₁₆	—	—	54 lbs.	2.6
25N2654WSSVLK1 Laminate	523	25 ¹ / ₂	54	1 ³ / ₁₆	—	—	54 lbs.	2.6
25N2648WSSVWK1 Wood	\$ 879	25 ¹ / ₂	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	48 lbs.	2.4
25N2648WSSVLK1 Laminate	472	25 ¹ / ₂	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	48 lbs.	2.4

RECTANGULAR WORKSURFACE 24" DEPTH



Grain direction runs front-to-back

- Wire Manager available on left side, back, right side, back & left or back & right; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Worksurfaces can be ordered in 1/8" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- Grain direction runs front-to-back
- For use with 23" deep pedestals
- Intended to be used when building an L or U configuration utilizing components
- For worksurfaces with grain direction running left-to-right, refer to pages 158-162
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 211
- For Epicenter depth worksurfaces see pages 247-251
- For undersurface wire managers, see page 685


TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminite models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminite Top Color
10. Worksurface Sheen (wood models)

SAMPLE MODEL NUMBER:

25N2630WSSVWK1 M K G1C D1B478 X X N MC

• See pages 91-95 for all options available in Epic

RECTANGULAR WORKSURFACE 24" DEPTH (CONTINUED)	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET	
			D	W	H					
 <p>Grain direction runs front-to-back</p>	KNIFE RIM (CONTINUED)									
	25N2642WSSVWK1	Wood	\$ 837	25½	42½	1¾	—	—	42 lbs.	2.2
	25N2642WSSVLK1	Laminite	426	25½	42½	1¾	—	—	42 lbs.	2.2
	25N2636WSSVWK1	Wood	\$ 808	25½	36½	1¾	—	—	33 lbs.	1.8
	25N2636WSSVLK1	Laminite	389	25½	36½	1¾	—	—	33 lbs.	1.8
	25N2630WSSVWK1	Wood	\$ 785	25½	30½	1¾	—	—	28 lbs.	1.5
	25N2630WSSVLK1	Laminite	347	25½	30½	1¾	—	—	28 lbs.	1.5
	25N2760WSSVWK2	Wood	\$ 922	27	60	1¾	—	—	63 lbs.	3.1
	25N2760WSSVLK2	Laminite	592	27	60	1¾	—	—	63 lbs.	3.1
	25N2754WSSVWK2	Wood	\$ 896	27	54	1¾	—	—	56 lbs.	2.8
	25N2754WSSVLK2	Laminite	523	27	54	1¾	—	—	56 lbs.	2.8
	25N2748WSSVWK2	Wood	\$ 879	27	48½	1¾	—	—	50 lbs.	2.5
	25N2748WSSVLK2	Laminite	472	27	48½	1¾	—	—	50 lbs.	2.5
	25N2742WSSVWK2	Wood	\$ 837	27	42½	1¾	—	—	44 lbs.	2.3
	25N2742WSSVLK2	Laminite	426	27	42½	1¾	—	—	44 lbs.	2.3
	25N2736WSSVWK2	Wood	\$ 808	27	36½	1¾	—	—	33 lbs.	1.8
	25N2736WSSVLK2	Laminite	389	27	36½	1¾	—	—	33 lbs.	1.8
	25N2730WSSVWK2	Wood	\$ 785	27	30½	1¾	—	—	28 lbs.	1.5
	25N2730WSSVLK2	Laminite	347	27	30½	1¾	—	—	28 lbs.	1.5

- Wire Manager available on left side, back, right side, back & left or back & right; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Worksurfaces can be ordered in ¼" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- Grain direction runs front-to-back
- For use with 23" deep pedestals
- Intended to be used when building an L or U configuration utilizing components
- For worksurfaces with grain direction running left-to-right, refer to pages 158-162
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 211
- For Epicenter depth worksurfaces see pages 247-251
- For undersurface wire managers, see page 685

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 96 for grommet locations; and page 94 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 211 for support options
- Refer to pages 663-705 for accessories

BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

RECTANGULAR WORKSURFACE 18" DEPTH	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
			D	W	H	A	KW		
	SOFTENED RIM								
	25N1896WSSW Wood	\$ 960	18 $\frac{1}{2}$ "	95 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	75 lbs.	3.0
	25N1896WSSL Laminate	565	18 $\frac{1}{2}$ "	95 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	75 lbs.	3.0
	25N1890WSSW Wood	\$ 917	18 $\frac{1}{2}$ "	89 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	71 lbs.	2.9
	25N1890WSSL Laminate	543	18 $\frac{1}{2}$ "	89 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	71 lbs.	2.9
	25N1884WSSW Wood	\$ 874	18 $\frac{1}{2}$ "	83 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	66 lbs.	2.7
	25N1884WSSL Laminate	521	18 $\frac{1}{2}$ "	83 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	66 lbs.	2.7
	25N1878WSSW Wood	\$ 788	18 $\frac{1}{2}$ "	77 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	61 lbs.	2.5
	25N1878WSSL Laminate	462	18 $\frac{1}{2}$ "	77 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	61 lbs.	2.5
	25N1872WSSW Wood	\$ 706	18 $\frac{1}{2}$ "	71 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	57 lbs.	2.3
	25N1872WSSL Laminate	402	18 $\frac{1}{2}$ "	71 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	57 lbs.	2.3
	25N1866WSSW Wood	\$ 679	18 $\frac{1}{2}$ "	66"	1 $\frac{3}{16}$ "	—	—	52 lbs.	2.2
	25N1866WSSL Laminate	373	18 $\frac{1}{2}$ "	66"	1 $\frac{3}{16}$ "	—	—	52 lbs.	2.2
	25N1860WSSW Wood	\$ 659	18 $\frac{1}{2}$ "	60"	1 $\frac{3}{16}$ "	—	—	48 lbs.	2.0
	25N1860WSSL Laminate	355	18 $\frac{1}{2}$ "	60"	1 $\frac{3}{16}$ "	—	—	48 lbs.	2.0
	25N1854WSSW Wood	\$ 643	18 $\frac{1}{2}$ "	54"	1 $\frac{3}{16}$ "	—	—	43 lbs.	1.8
	25N1854WSSL Laminate	314	18 $\frac{1}{2}$ "	54"	1 $\frac{3}{16}$ "	—	—	43 lbs.	1.8
	25N1848WSSW Wood	\$ 629	18 $\frac{1}{2}$ "	48 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	38 lbs.	1.6
	25N1848WSSL Laminate	283	18 $\frac{1}{2}$ "	48 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	38 lbs.	1.6

- Wire Manager available on left side, back, right side, back & left or back & right; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Worksurfaces can be ordered in $\frac{1}{16}$ " increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 17" deep pedestals
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 211
- For Epicenter depth worksurfaces see pages 247-251
- For undersurface wire managers, see page 685

TO ORDER, SPECIFY:


1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminite models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminite Top Color
10. Worksurface Sheen (wood models)

SAMPLE MODEL NUMBER:

25N1860WSSW M V G1C D1B425 X X R CW

• See pages 91-95 for all options available in Epic

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS				CARTONED WEIGHT	CUBIC FEET
		D	W	H	A		
RECTANGULAR WORKSURFACE 18" DEPTH (CONTINUED)							
SOFTENED RIM (CONTINUED)							
25N1842WSSW Wood	\$ 600	18 $\frac{1}{2}$	42 $\frac{1}{2}$	1 $\frac{1}{2}$	—	34 lbs.	1.5
25N1842WSSL Laminate	256	18 $\frac{1}{2}$	42 $\frac{1}{2}$	1 $\frac{1}{2}$	—	34 lbs.	1.5
25N1836WSSW Wood	\$ 578	18 $\frac{1}{2}$	36 $\frac{1}{2}$	1 $\frac{1}{2}$	—	29 lbs.	1.3
25N1836WSSL Laminate	233	18 $\frac{1}{2}$	36 $\frac{1}{2}$	1 $\frac{1}{2}$	—	29 lbs.	1.3
25N1830WSSW Wood	\$ 563	18 $\frac{1}{2}$	30 $\frac{1}{2}$	1 $\frac{1}{2}$	—	24 lbs.	1.1
25N1830WSSL Laminate	210	18 $\frac{1}{2}$	30 $\frac{1}{2}$	1 $\frac{1}{2}$	—	24 lbs.	1.1
KNIFE RIM							
25N2096WSSWK1 Wood	\$ 1179	19 $\frac{1}{2}$	95 $\frac{1}{2}$	1 $\frac{1}{2}$	—	75 lbs.	3.0
25N2096WSSLK1 Laminate	763	19 $\frac{1}{2}$	95 $\frac{1}{2}$	1 $\frac{1}{2}$	—	75 lbs.	3.0
25N2090WSSWK1 Wood	\$ 1128	19 $\frac{1}{2}$	89 $\frac{1}{2}$	1 $\frac{1}{2}$	—	71 lbs.	2.9
25N2090WSSLK1 Laminate	733	19 $\frac{1}{2}$	89 $\frac{1}{2}$	1 $\frac{1}{2}$	—	71 lbs.	2.9
25N2084WSSWK1 Wood	\$ 1075	19 $\frac{1}{2}$	83 $\frac{1}{2}$	1 $\frac{1}{2}$	—	66 lbs.	2.7
25N2084WSSLK1 Laminate	704	19 $\frac{1}{2}$	83 $\frac{1}{2}$	1 $\frac{1}{2}$	—	66 lbs.	2.7
25N2078WSSWK1 Wood	\$ 971	19 $\frac{1}{2}$	77 $\frac{1}{2}$	1 $\frac{1}{2}$	—	61 lbs.	2.5
25N2078WSSLK1 Laminate	622	19 $\frac{1}{2}$	77 $\frac{1}{2}$	1 $\frac{1}{2}$	—	61 lbs.	2.5
25N2072WSSWK1 Wood	\$ 867	19 $\frac{1}{2}$	71 $\frac{1}{2}$	1 $\frac{1}{2}$	—	57 lbs.	2.3
25N2072WSSLK1 Laminate	543	19 $\frac{1}{2}$	71 $\frac{1}{2}$	1 $\frac{1}{2}$	—	57 lbs.	2.3
25N2066WSSWK1 Wood	\$ 835	19 $\frac{1}{2}$	66	1 $\frac{1}{2}$	—	52 lbs.	2.2
25N2066WSSLK1 Laminate	504	19 $\frac{1}{2}$	66	1 $\frac{1}{2}$	—	52 lbs.	2.2



- Wire Manager available on left side, back, right side, back & left or back & right; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Worksurfaces can be ordered in $\frac{1}{8}$ " increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 17" deep pedestals
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 211
- For Epicenter depth worksurfaces see pages 247-251
- For undersurface wire managers, see page 685

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 96 for grommet locations; and page 94 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 211 for support options
- Refer to pages 663-705 for accessories

BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

RECTANGULAR WORKSURFACE 18" DEPTH (CONTINUED)	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
			D	W	H	A	KW		
	25N2060WSSWK1 Wood	\$ 812	19%	60	1 $\frac{3}{8}$ "	—	—	48 lbs.	2.0
	25N2060WSSLK1 Laminate	478	19%	60	1 $\frac{3}{8}$ "	—	—	48 lbs.	2.0
	25N2054WSSWK1 Wood	\$ 788	19%	54	1 $\frac{3}{8}$ "	—	—	43 lbs.	1.8
	25N2054WSSLK1 Laminate	424	19%	54	1 $\frac{3}{8}$ "	—	—	43 lbs.	1.8
	25N2048WSSWK1 Wood	\$ 774	19%	48 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	38 lbs.	1.6
	25N2048WSSLK1 Laminate	383	19%	48 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	38 lbs.	1.6
	25N2042WSSWK1 Wood	\$ 738	19%	42 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	34 lbs.	1.5
	25N2042WSSLK1 Laminate	344	19%	42 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	34 lbs.	1.5
	25N2036WSSWK1 Wood	\$ 711	19%	36 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	29 lbs.	1.3
	25N2036WSSLK1 Laminate	315	19%	36 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	29 lbs.	1.3
	25N2030WSSWK1 Wood	\$ 692	19%	30 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	24 lbs.	1.1
	25N2030WSSLK1 Laminate	283	19%	30 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	24 lbs.	1.1

- Wire Manager available on left side, back, right side, back & left or back & right; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Worksurfaces can be ordered in $\frac{1}{8}$ " increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 17" deep pedestals
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 211
- For Epicenter depth worksurfaces see pages 247-251
- For undersurface wire managers, see page 685

TO ORDER, SPECIFY:


1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminate Top Color
10. Worksurface Sheen (wood models)

SAMPLE MODEL NUMBER:

25N2060WSSWK1 M K G1C X R MH

• See pages 91-95 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET	
			D	W	H					
RECTANGULAR WORKSURFACE 18" DEEP FOR STORAGE CREDENZAS	SOFTENED RIM									
	25N18A96WSSL	Laminate	\$ 565	18 $\frac{1}{2}$ "	96 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	75 lbs.	3.0
	25N18A90WSSL	Laminate	543	18 $\frac{1}{2}$ "	90 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	71 lbs.	2.9
	25N18A84WSSL	Laminate	521	18 $\frac{1}{2}$ "	84 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	66 lbs.	2.7
	25N18A78WSSL	Laminate	462	18 $\frac{1}{2}$ "	78 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	61 lbs.	2.5
	25N1872WSSL	Laminate	402	18 $\frac{1}{2}$ "	72 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	57 lbs.	2.3
	25N18A66WSSL	Laminate	373	18 $\frac{1}{2}$ "	66 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	52 lbs.	2.2
	25N18A60WSSL	Laminate	355	18 $\frac{1}{2}$ "	60 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	48 lbs.	2.0
	KNIFE RIM									
	25N20A96WSSLK1	Laminate	\$ 763	19 $\frac{1}{2}$ "	96 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	75 lbs.	3.0
25N20A90WSSLK1	Laminate	733	19 $\frac{1}{2}$ "	90 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	71 lbs.	2.9	
25N20A84WSSLK1	Laminate	704	19 $\frac{1}{2}$ "	84 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	66 lbs.	2.7	
25N20A78WSSLK1	Laminate	622	19 $\frac{1}{2}$ "	78 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	61 lbs.	2.5	
25N20A72WSSLK1	Laminate	543	19 $\frac{1}{2}$ "	72 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	57 lbs.	2.3	
25N20A66WSSLK1	Laminate	504	19 $\frac{1}{2}$ "	66 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	52 lbs.	2.2	
25N20A60WSSLK1	Laminate	478	19 $\frac{1}{2}$ "	60 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	—	—	48 lbs.	2.0	



- Wire Manager available on left side, back, right side, back & left or back & right; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Worksurfaces can be ordered in 1/8" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 17" deep pedestals
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 211
- For Epicenter depth worksurfaces see pages 247-251
- For undersurface wire managers, see page 685

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 96 for grommet locations; and page 94 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 211 for support options
- Refer to pages 663-705 for accessories


BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
		D	W	H	A	KW		
TAPERED WORKSURFACE								
SOFTENED RIM								
LEFT								
RIGHT								
25N3684WSTLW	\$ 1171	36 $\frac{1}{16}$	83 $\frac{15}{16}$	1 $\frac{3}{16}$	—	—	103 lbs. 4.2	
25N3684WSTLL	846	36 $\frac{1}{16}$	83 $\frac{15}{16}$	1 $\frac{3}{16}$	—	—	103 lbs. 4.2	
25N3672WSTLW	\$ 1122	36 $\frac{1}{16}$	71 $\frac{15}{16}$	1 $\frac{3}{16}$	—	—	95 lbs. 4.0	
25N3672WSTLL	795	36 $\frac{1}{16}$	71 $\frac{15}{16}$	1 $\frac{3}{16}$	—	—	95 lbs. 4.0	
25N3084WSTLW	\$ 1122	30 $\frac{1}{16}$	83 $\frac{15}{16}$	1 $\frac{3}{16}$	—	—	95 lbs. 4.0	
25N3084WSTLL	795	30 $\frac{1}{16}$	83 $\frac{15}{16}$	1 $\frac{3}{16}$	—	—	95 lbs. 4.0	
25N3072WSTLW	\$ 940	30 $\frac{1}{16}$	71 $\frac{15}{16}$	1 $\frac{3}{16}$	—	—	95 lbs. 4.0	
25N3072WSTLL	613	30 $\frac{1}{16}$	71 $\frac{15}{16}$	1 $\frac{3}{16}$	—	—	95 lbs. 4.0	
25N3066WSTLW	\$ 911	30 $\frac{1}{16}$	66	1 $\frac{3}{16}$	—	—	88 lbs. 3.7	
25N3066WSTLL	571	30 $\frac{1}{16}$	66	1 $\frac{3}{16}$	—	—	88 lbs. 3.7	
25N3060WSTLW	\$ 891	30 $\frac{1}{16}$	60	1 $\frac{3}{16}$	—	—	81 lbs. 3.3	
25N3060WSTLL	528	30 $\frac{1}{16}$	60	1 $\frac{3}{16}$	—	—	81 lbs. 3.3	
25N3054WSTLW	\$ 874	30 $\frac{1}{16}$	54	1 $\frac{3}{16}$	—	—	74 lbs. 3.0	
25N3054WSTLL	493	30 $\frac{1}{16}$	54	1 $\frac{3}{16}$	—	—	74 lbs. 3.0	
25N3048WSTLW	\$ 859	30 $\frac{1}{16}$	48 $\frac{1}{16}$	1 $\frac{3}{16}$	—	—	67 lbs. 2.7	
25N3048WSTLL	457	30 $\frac{1}{16}$	48 $\frac{1}{16}$	1 $\frac{3}{16}$	—	—	67 lbs. 2.7	



Right shown

- 36" depth tapers to 30" and 30" depth tapers to 24"
- Wire Manager available on left side, back, right side, back & left or back & right; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Modified width and depth not available on this shape
- For undersurface wire managers, see page 685

TO ORDER, SPECIFY:


1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Wire Manager
7. Veneer Top Finish/Laminated Top Color
8. Worksurface Sheen (wood models)

SAMPLE MODEL NUMBER:

25N3684WSTLL M V478 X X 478

• See pages 91-95 for all options available in Epic

**TAPERED WORKSURFACE
(CONTINUED)**



Right shown

MODEL NO./DESCRIPTION			LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET
				D	W	H				
KNIFE RIM										
	LEFT	RIGHT								
25N3884WSTLWK1	25N3884WSTRWK1	Wood	\$ 1525	37 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	108 lbs.	4.4
25N3884WSTLLK1	25N3884WSTRLK1	Laminate	1312	37 ⁷ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	108 lbs.	4.4
25N3872WSTLWK1	25N3872WSTRWK1	Wood	\$ 1460	37 ⁷ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	100 lbs.	4.2
25N3872WSTLLK1	25N3872WSTRLK1	Laminate	1233	37 ⁷ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	100 lbs.	4.2
25N3284WSTLWK1	25N3284WSTRWK1	Wood	\$ 1460	31 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	100 lbs.	4.2
25N3284WSTLLK1	25N3284WSTRLK1	Laminate	1233	31 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	100 lbs.	4.2
25N3272WSTLWK1	25N3272WSTRWK1	Wood	\$ 1223	31 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	100 lbs.	4.2
25N3272WSTLLK1	25N3272WSTRLK1	Laminate	950	31 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	100 lbs.	4.2
25N3266WSTLWK1	25N3266WSTRWK1	Wood	\$ 1185	31 ¹ / ₁₆	66	1 ³ / ₁₆	—	—	92 lbs.	3.9
25N3266WSTLLK1	25N3266WSTRLK1	Laminate	884	31 ¹ / ₁₆	66	1 ³ / ₁₆	—	—	92 lbs.	3.9
25N3260WSTLWK1	25N3260WSTRWK1	Wood	\$ 1159	31 ¹ / ₁₆	60	1 ³ / ₁₆	—	—	85 lbs.	3.5
25N3260WSTLLK1	25N3260WSTRLK1	Laminate	818	31 ¹ / ₁₆	60	1 ³ / ₁₆	—	—	85 lbs.	3.5
25N3254WSTLWK1	25N3254WSTRWK1	Wood	\$ 1137	31 ¹ / ₁₆	54	1 ³ / ₁₆	—	—	78 lbs.	3.2
25N3254WSTLLK1	25N3254WSTRLK1	Laminate	764	31 ¹ / ₁₆	54	1 ³ / ₁₆	—	—	78 lbs.	3.2
25N3248WSTLWK1	25N3248WSTRWK1	Wood	\$ 1116	31 ¹ / ₁₆	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	70 lbs.	2.8
25N3248WSTLLK1	25N3248WSTRLK1	Laminate	708	31 ¹ / ₁₆	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	70 lbs.	2.8
25N3984WSTLWK2	25N3984WSTRWK2	Wood	\$ 1525	39 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	113 lbs.	4.6
25N3984WSTLLK2	25N3984WSTRLK2	Laminate	1312	39 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	113 lbs.	4.6
25N3972WSTLWK2	25N3972WSTRWK2	Wood	\$ 1460	39 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	105 lbs.	4.4
25N3972WSTLLK2	25N3972WSTRLK2	Laminate	1233	39 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	105 lbs.	4.4

- 36" depth tapers to 30" and 30" depth tapers to 24"
- Wire Manager available on left side, back, right side, back & left or back & right; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Modified width and depth not available on this shape
- For undersurface wire managers, see page 685

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 96 for grommet locations; and page 94 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 211 for support options
- Refer to pages 663-705 for accessories

BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

	MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
				D	W	H	A	KW			
TAPERED WORKSURFACE (CONTINUED)	KNIFE RIM (CONTINUED)										
	LEFT	RIGHT									
<p>Right shown</p>	25N3384WSTLWK2	25N3384WSTRWK2	Wood	\$ 1460	33 ³ / ₁₆	83 ¹⁵ / ₁₆	1 ³ / ₁₆	—	—	105 lbs.	4.4
	25N3384WSTLLK2	25N3384WSTRLK2	Laminate	1233	33 ³ / ₁₆	83 ¹⁵ / ₁₆	1 ³ / ₁₆	—	—	105 lbs.	4.4
	25N3372WSTLWK2	25N3372WSTRWK2	Wood	\$ 1223	33 ³ / ₁₆	71 ¹⁵ / ₁₆	1 ³ / ₁₆	—	—	105 lbs.	4.4
	25N3372WSTLLK2	25N3372WSTRLK2	Laminate	950	33 ³ / ₁₆	71 ¹⁵ / ₁₆	1 ³ / ₁₆	—	—	105 lbs.	4.4
	25N3366WSTLWK2	25N3366WSTRWK2	Wood	\$ 1185	33 ³ / ₁₆	66	1 ³ / ₁₆	—	—	97 lbs.	4.1
	25N3366WSTLLK2	25N3366WSTRLK2	Laminate	884	33 ³ / ₁₆	66	1 ³ / ₁₆	—	—	97 lbs.	4.1
	25N3360WSTLWK2	25N3360WSTRWK2	Wood	\$ 1159	33 ³ / ₁₆	60	1 ³ / ₁₆	—	—	89 lbs.	3.6
	25N3360WSTLLK2	25N3360WSTRLK2	Laminate	818	33 ³ / ₁₆	60	1 ³ / ₁₆	—	—	89 lbs.	3.6
	25N3354WSTLWK2	25N3354WSTRWK2	Wood	\$ 1137	33 ³ / ₁₆	54	1 ³ / ₁₆	—	—	81 lbs.	3.3
	25N3354WSTLLK2	25N3354WSTRLK2	Laminate	764	33 ³ / ₁₆	54	1 ³ / ₁₆	—	—	81 lbs.	3.3
	25N3348WSTLWK2	25N3348WSTRWK2	Wood	\$ 1116	33 ³ / ₁₆	48 ³ / ₁₆	1 ³ / ₁₆	—	—	74 lbs.	3.0
	25N3348WSTLLK2	25N3348WSTRLK2	Laminate	708	33 ³ / ₁₆	48 ³ / ₁₆	1 ³ / ₁₆	—	—	74 lbs.	3.0

- 36" depth tapers to 30" and 30" depth tapers to 24"
- Wire Manager available on left side, back, right side, back & left or back & right; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Modified width and depth not available on this shape
- For undersurface wire managers, see page 685

TO ORDER, SPECIFY:


1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Wire Manager
7. Veneer Top Finish/Laminated Top Color
8. Worksurface Sheen (wood models)

SAMPLE MODEL NUMBER:


25N3084WSGRW M V X D1B485 N MH

• See pages 91-95 for all options available in Epic

**ANGLED WORKSURFACE
30" DEPTH**



Left shown



Right shown

MODEL NO./DESCRIPTION

LIST PRICE

DIMENSIONS

D W H A KW

CARTONED WEIGHT CUBIC FEET

**SOFTENED RIM
LEFT RIGHT**

25N3084WSGLW	25N3084WSGRW	Wood	\$ 1286	30 1/2	83 1/2	1 3/8	-	-	88 lbs.	3.7
25N3084WSGLL	25N3084WSGRL	Laminate	771	30 1/2	83 1/2	1 3/8	-	-	88 lbs.	3.7
25N3072WSGLW	25N3072WSGRW	Wood	\$ 1060	30 1/2	71 1/2	1 3/8	-	-	77 lbs.	3.5
25N3072WSGLL	25N3072WSGRL	Laminate	621	30 1/2	71 1/2	1 3/8	-	-	77 lbs.	3.5
25N3066WSGLW	25N3066WSGRW	Wood	\$ 1021	30 1/2	66	1 3/8	-	-	71 lbs.	3.4
25N3066WSGLL	25N3066WSGRL	Laminate	573	30 1/2	66	1 3/8	-	-	71 lbs.	3.4
25N3060WSGLW	25N3060WSGRW	Wood	\$ 998	30 1/2	60	1 3/8	-	-	66 lbs.	3.2
25N3060WSGLL	25N3060WSGRL	Laminate	522	30 1/2	60	1 3/8	-	-	66 lbs.	3.2

**KNIFE RIM
LEFT RIGHT**

25N3286WSGLWK1	25N3286WSGRWK1	Wood	\$ 1673	31 1/2	85 1/2	1 3/8	-	-	92 lbs.	3.9
25N3286WSGLLK1	25N3286WSGRLK1	Laminate	1194	31 1/2	85 1/2	1 3/8	-	-	92 lbs.	3.9
25N3274WSGLWK1	25N3274WSGRWK1	Wood	\$ 1379	31 1/2	73 1/2	1 3/8	-	-	81 lbs.	3.7
25N3274WSGLLK1	25N3274WSGRLK1	Laminate	964	31 1/2	73 1/2	1 3/8	-	-	81 lbs.	3.7
25N3268WSGLWK1	25N3268WSGRWK1	Wood	\$ 1326	31 1/2	67 1/2	1 3/8	-	-	75 lbs.	3.6
25N3268WSGLLK1	25N3268WSGRLK1	Laminate	887	31 1/2	67 1/2	1 3/8	-	-	75 lbs.	3.6
25N3262WSGLWK1	25N3262WSGRWK1	Wood	\$ 1299	31 1/2	61 1/2	1 3/8	-	-	69 lbs.	3.4
25N3262WSGLLK1	25N3262WSGRLK1	Laminate	809	31 1/2	61 1/2	1 3/8	-	-	69 lbs.	3.4
25N3386WSGLWK2	25N3386WSGRWK2	Wood	\$ 1673	33 1/2	85 1/2	1 3/8	-	-	97 lbs.	4.1
25N3386WSGLLK2	25N3386WSGRLK2	Laminate	1194	33 1/2	85 1/2	1 3/8	-	-	97 lbs.	4.1

- Wire Manager available on left side, back or right side; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Requires support at end of surface and on the outside corner
- Modified width and depth not available on this shape
- For undersurface wire managers, see page 685

PRODUCT SPECIFICATIONS



- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Knife rim profile always on extension
- Component worksurfaces can be used with assembled units
- Refer to page 96 for grommet locations; and page 94 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 211 for support options
- Refer to pages 663-705 for accessories

BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

	MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET		
				D	W	H	A	KW				
<p>ANGLED WORKSURFACE 30" DEPTH (CONTINUED)</p>  <p>Left shown</p>  <p>Right shown</p>	KNIFE RIM (CONTINUED)											
		LEFT	RIGHT									
		25N3374WSGLWK2	25N3374WSGRWK2	Wood	\$ 1379	33 3/16	73 3/16	1 3/16	-	-	85 lbs.	3.9
		25N3374WSGLLK2	25N3374WSGRLK2	Laminate	964	33 3/16	73 3/16	1 3/16	-	-	85 lbs.	3.9
		25N3368WSGLWK2	25N3368WSGRWK2	Wood	\$ 1326	33 3/16	67 1/2	1 3/16	-	-	78 lbs.	3.7
		25N3368WSGLLK2	25N3368WSGRLK2	Laminate	887	33 3/16	67 1/2	1 3/16	-	-	78 lbs.	3.7
		25N3362WSGLWK2	25N3362WSGRWK2	Wood	\$ 1299	33 3/16	61 1/2	1 3/16	-	-	73 lbs.	3.5
		25N3362WSGLLK2	25N3362WSGRLK2	Laminate	809	33 3/16	61 1/2	1 3/16	-	-	73 lbs.	3.5

- Wire Manager available on left side or right side; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Requires support at end of surface and on the outside corner
- Modified width and depth not available on this shape
- For undersurface wire managers, see page 685

TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Wire Manager
7. Veneer Top Finish/Laminated Top Color
8. Worksurface Sheen (wood models)


SAMPLE MODEL NUMBER:

25N2484WSGRL E VMC G11SNLR D1B485 MC


• See pages 91-95 for all options available in Epic

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET		
		D	W	H						
ANGLED WORKSURFACE 24" DEPTH										
SOFTENED RIM										
LEFT				RIGHT						
25N2484WSGLW	25N2484WSGRW	Wood	\$ 1175	24	83 ¹ / ₈ "	1 ³ / ₈ "	—	—	72 lbs.	3.4
25N2484WSGLL	25N2484WSGRL	Laminate	673	24	83 ¹ / ₈ "	1 ³ / ₈ "	—	—	72 lbs.	3.4
25N2472WSGLW	25N2472WSGRW	Wood	\$ 948	24	71 ¹ / ₈ "	1 ³ / ₈ "	—	—	63 lbs.	3.2
25N2472WSGLL	25N2472WSGRL	Laminate	522	24	71 ¹ / ₈ "	1 ³ / ₈ "	—	—	63 lbs.	3.2
25N2466WSGLW	25N2466WSGRW	Wood	\$ 914	24	66"	1 ³ / ₈ "	—	—	59 lbs.	3.0
25N2466WSGLL	25N2466WSGRL	Laminate	484	24	66"	1 ³ / ₈ "	—	—	59 lbs.	3.0
25N2460WSGLW	25N2460WSGRW	Wood	\$ 887	24	60"	1 ³ / ₈ "	—	—	55 lbs.	3.0
25N2460WSGLL	25N2460WSGRL	Laminate	458	24	60"	1 ³ / ₈ "	—	—	55 lbs.	3.0
KNIFE RIM										
LEFT				RIGHT						
25N2686WSGLWK1	25N2686WSGRWK1	Wood	\$ 1528	25 ¹ / ₂ "	85 ¹ / ₈ "	1 ³ / ₈ "	—	—	76 lbs.	3.6
25N2686WSGLLK1	25N2686WSGRLK1	Laminate	1043	25 ¹ / ₂ "	85 ¹ / ₈ "	1 ³ / ₈ "	—	—	76 lbs.	3.6
25N2674WSGLWK1	25N2674WSGRWK1	Wood	\$ 1233	25 ¹ / ₂ "	73 ¹ / ₈ "	1 ³ / ₈ "	—	—	66 lbs.	3.4
25N2674WSGLLK1	25N2674WSGRLK1	Laminate	809	25 ¹ / ₂ "	73 ¹ / ₈ "	1 ³ / ₈ "	—	—	66 lbs.	3.4
25N2668WSGLWK1	25N2668WSGRWK1	Wood	\$ 1189	25 ¹ / ₂ "	67 ¹ / ₂ "	1 ³ / ₈ "	—	—	62 lbs.	3.2
25N2668WSGLLK1	25N2668WSGRLK1	Laminate	750	25 ¹ / ₂ "	67 ¹ / ₂ "	1 ³ / ₈ "	—	—	62 lbs.	3.2
25N2662WSGLWK1	25N2662WSGRWK1	Wood	\$ 1153	25 ¹ / ₂ "	61 ¹ / ₂ "	1 ³ / ₈ "	—	—	58 lbs.	3.2
25N2662WSGLLK1	25N2662WSGRLK1	Laminate	710	25 ¹ / ₂ "	61 ¹ / ₂ "	1 ³ / ₈ "	—	—	58 lbs.	3.2
25N2786WSGLWK2	25N2786WSGRWK2	Wood	\$ 1528	27"	85 ¹ / ₈ "	1 ³ / ₈ "	—	—	79 lbs.	3.7
25N2786WSGLLK2	25N2786WSGRLK2	Laminate	1043	27"	85 ¹ / ₈ "	1 ³ / ₈ "	—	—	79 lbs.	3.7

ANGLED WORKSURFACE 24" DEPTH



Left shown



Right shown

- Wire Manager available on left side, back or right side; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Requires support at end of surface and on the outside corner
- Modified width and depth not available on this shape
- For undersurface wire managers, see page 685

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Knife rim profile always on extension
- Component worksurfaces can be used with assembled units
- Refer to page 96 for grommet locations; and page 94 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 211 for support options
- Refer to pages 663-705 for accessories

BASE MODEL KEY


- W Wood Unit
- L Laminate Unit

DIMENSION KEY


- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET		
		D	W	H	A	KW				
ANGLED WORKSURFACE 24" DEPTH (CONTINUED)										
KNIFE RIM (CONTINUED)										
		LEFT	RIGHT							
25N2774WSGLWK2	25N2774WSGRWK2	Wood	\$ 1233	27	73 ³ / ₁₆	1 ³ / ₁₆	—	—	69 lbs.	3.5
25N2774WSGLLK2	25N2774WSGRLK2	Laminate	809	27	73 ³ / ₁₆	1 ³ / ₁₆	—	—	69 lbs.	3.5
25N2768WSGLWK2	25N2768WSGRWK2	Wood	\$ 1189	27	67 ¹ / ₂	1 ³ / ₁₆	—	—	65 lbs.	3.3
25N2768WSGLLK2	25N2768WSGRLK2	Laminate	750	27	67 ¹ / ₂	1 ³ / ₁₆	—	—	65 lbs.	3.3
25N2762WSGLWK2	25N2762WSGRWK2	Wood	\$ 1153	27	61 ¹ / ₂	1 ³ / ₁₆	—	—	61 lbs.	3.3
25N2762WSGLLK2	25N2762WSGRLK2	Laminate	710	27	61 ¹ / ₂	1 ³ / ₁₆	—	—	61 lbs.	3.3

**ANGLED WORKSURFACE
24" DEPTH
(CONTINUED)**



Left shown



Right shown

- Wire Manager available on left side or right side; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Requires support at end of surface and on the outside corner
- Modified width and depth not available on this shape
- For undersurface wire managers, see page 685

TO ORDER, SPECIFY:


1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Wire Manager
7. Veneer Top Finish/Laminate Top Color
8. Worksurface Sheen (wood models)

SAMPLE MODEL NUMBER:

25N3696WSCERW2 M V G1A X R MC

• See pages 91-95 for all options available in Epic

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS				CARTONED WEIGHT	CUBIC FEET
		D	W	H	A		
EXTENDED CORNER WORKSURFACE							
SOFTENED RIM LEFT							
RIGHT							
25N3696WSCELW2	\$ 1684	35 ³ / ₁₆ "	95 ³ / ₁₆ "	1 ³ / ₁₆ "	—	106 lbs.	5.9
25N3696WSCERL2	1215	35 ³ / ₁₆ "	95 ³ / ₁₆ "	1 ³ / ₁₆ "	—	106 lbs.	5.9
25N3690WSCELW2	\$ 1655	35 ³ / ₁₆ "	89 ³ / ₁₆ "	1 ³ / ₁₆ "	—	100 lbs.	5.6
25N3690WSCERL2	1179	35 ³ / ₁₆ "	89 ³ / ₁₆ "	1 ³ / ₁₆ "	—	100 lbs.	5.6
25N3684WSCELW2	\$ 1627	35 ³ / ₁₆ "	83 ³ / ₁₆ "	1 ³ / ₁₆ "	—	93 lbs.	5.2
25N3684WSCERL2	1145	35 ³ / ₁₆ "	83 ³ / ₁₆ "	1 ³ / ₁₆ "	—	93 lbs.	5.2
25N3678WSCELW2	\$ 1460	35 ³ / ₁₆ "	77 ³ / ₁₆ "	1 ³ / ₁₆ "	—	86 lbs.	4.6
25N3678WSCERL2	1112	35 ³ / ₁₆ "	77 ³ / ₁₆ "	1 ³ / ₁₆ "	—	86 lbs.	4.6
25N3672WSCELW2	\$ 1291	35 ³ / ₁₆ "	72"	1 ³ / ₁₆ "	—	79 lbs.	3.9
25N3672WSCERL2	1077	35 ³ / ₁₆ "	72"	1 ³ / ₁₆ "	—	79 lbs.	3.9
25N3666WSCELW2	\$ 1247	35 ³ / ₁₆ "	66"	1 ³ / ₁₆ "	—	72 lbs.	3.6
25N3666WSCERL2	1023	35 ³ / ₁₆ "	66"	1 ³ / ₁₆ "	—	72 lbs.	3.6
25N3660WSCELW2	\$ 1163	35 ³ / ₁₆ "	60"	1 ³ / ₁₆ "	—	65 lbs.	3.3
25N3660WSCERL2	971	35 ³ / ₁₆ "	60"	1 ³ / ₁₆ "	—	65 lbs.	3.3
25N3654WSCELW2	\$ 1121	35 ³ / ₁₆ "	54"	1 ³ / ₁₆ "	—	58 lbs.	3.0
25N3654WSCERL2	941	35 ³ / ₁₆ "	54"	1 ³ / ₁₆ "	—	58 lbs.	3.0
25N3696WSCELW2K1	\$ 2188	36 ³ / ₁₆ "	95 ³ / ₁₆ "	1 ³ / ₁₆ "	—	106 lbs.	5.9
25N3696WSCERL2K1	1883	36 ³ / ₁₆ "	95 ³ / ₁₆ "	1 ³ / ₁₆ "	—	106 lbs.	5.9
25N3690WSCELW2K1	\$ 2151	36 ³ / ₁₆ "	90"	1 ³ / ₁₆ "	—	100 lbs.	5.6
25N3690WSCERL2K1	1829	36 ³ / ₁₆ "	90"	1 ³ / ₁₆ "	—	100 lbs.	5.6



- Wire Manager available on left side, back or right side; see page 279 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 457
- For additional worksurface support, specify Undersurface Support Rail, see page 453
- Modified width and depth not available on this shape
- Intended for use with 24" deep worksurfaces
- For undersurface wire managers, see page 685

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 96 for grommet locations; and page 94 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 211 for support options
- Refer to pages 663-705 for accessories


BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
		D	W	H	A	KW		
EXTENDED CORNER WORKSURFACE (CONTINUED)								
KNIFE RIM LEFT								
25N3684WSECELW2K1	\$ 2114	36 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	93 lbs. 5.2	
25N3684WSECELW2K1	1776	36 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	93 lbs. 5.2	
RIGHT								
25N3678WSECELW2K1	\$ 1898	36 ¹ / ₁₆	78	1 ³ / ₁₆	—	—	86 lbs. 4.6	
25N3678WSECELW2K1	1722	36 ¹ / ₁₆	78	1 ³ / ₁₆	—	—	86 lbs. 4.6	
25N3672WSECELW2K1	\$ 1680	36 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	79 lbs. 3.9	
25N3672WSECELW2K1	1671	36 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	79 lbs. 3.9	
25N3666WSECELW2K1	\$ 1622	36 ¹ / ₁₆	66	1 ³ / ₁₆	—	—	72 lbs. 3.6	
25N3666WSECELW2K1	1586	36 ¹ / ₁₆	66	1 ³ / ₁₆	—	—	72 lbs. 3.6	
25N3660WSECELW2K1	\$ 1511	36 ¹ / ₁₆	60	1 ³ / ₁₆	—	—	65 lbs. 3.3	
25N3660WSECELW2K1	1506	36 ¹ / ₁₆	60	1 ³ / ₁₆	—	—	65 lbs. 3.3	
25N3654WSECELW2K1	\$ 1459	36 ¹ / ₁₆	54	1 ³ / ₁₆	—	—	58 lbs. 3.0	
25N3654WSECELW2K1	1460	36 ¹ / ₁₆	54	1 ³ / ₁₆	—	—	58 lbs. 3.0	
25N3896WSECELW2K2	\$ 2188	37 ¹ / ₂	95 ¹ / ₁₆	1 ³ / ₁₆	—	—	106 lbs. 5.9	
25N3896WSECELW2K2	1883	37 ¹ / ₂	95 ¹ / ₁₆	1 ³ / ₁₆	—	—	106 lbs. 5.9	
25N3890WSECELW2K2	\$ 2151	37 ¹ / ₂	90	1 ³ / ₁₆	—	—	100 lbs. 5.6	
25N3890WSECELW2K2	1829	37 ¹ / ₂	90	1 ³ / ₁₆	—	—	100 lbs. 5.6	
25N3884WSECELW2K2	\$ 2114	37 ¹ / ₂	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	93 lbs. 5.2	
25N3884WSECELW2K2	1776	37 ¹ / ₂	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	93 lbs. 5.2	
25N3878WSECELW2K2	\$ 1898	37 ¹ / ₂	78	1 ³ / ₁₆	—	—	86 lbs. 4.6	
25N3878WSECELW2K2	1722	37 ¹ / ₂	78	1 ³ / ₁₆	—	—	86 lbs. 4.6	



Left shown

- Wire Manager available on left side, back or right side; see page 279 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 457
- For additional worksurface support, specify Undersurface Support Rail, see page 453
- Modified width and depth not available on this shape
- Intended for use with 24" deep worksurfaces
- For undersurface wire managers, see page 685

TO ORDER, SPECIFY:


1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Wire Manager
7. Veneer Top Finish/Laminated Top Color
8. Worksurface Sheen (wood models)

SAMPLE MODEL NUMBER:

25N3696WSCCELL2K1 E K405 X D1B405 405

• See pages 91-95 for all options available in Epic

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS				CARTONED WEIGHT	CUBIC FEET
		D	W	H	A		
EXTENDED CORNER WORKSURFACE (CONTINUED)							
KNIFE RIM (CONTINUED)							
LEFT							
RIGHT							
25N3872WSCCELW2K2 25N3872WSCERW2K2 Wood	\$ 1680	37½	71¾	1¾	—	79 lbs.	3.9
25N3872WSCCELL2K2 25N3872WSCERL2K2 Laminate	1671	37½	71¾	1¾	—	79 lbs.	3.9
25N3866WSCCELW2K2 25N3866WSCERW2K2 Wood	\$ 1622	37½	66	1¾	—	72 lbs.	3.6
25N3866WSCCELL2K2 25N3866WSCERL2K2 Laminate	1586	37½	66	1¾	—	72 lbs.	3.6
25N3860WSCCELW2K2 25N3860WSCERW2K2 Wood	\$ 1511	37½	60	1¾	—	65 lbs.	3.3
25N3860WSCCELL2K2 25N3860WSCERL2K2 Laminate	1506	37½	60	1¾	—	65 lbs.	3.3
25N3854WSCCELW2K2 25N3854WSCERW2K2 Wood	\$ 1459	37½	54	1¾	—	58 lbs.	3.0
25N3854WSCCELL2K2 25N3854WSCERL2K2 Laminate	1460	37½	54	1¾	—	58 lbs.	3.0



Left shown

- Wire Manager available on left side, back or right side; see page 279 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 457
- For additional work surface support, specify Undersurface Support Rail, see page 453
- Modified width and depth not available on this shape
- Intended for use with 24" deep work surfaces
- For undersurface wire managers, see page 685

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 96 for grommet locations; and page 94 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 211 for support options
- Refer to pages 663-705 for accessories

BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang; Approach Side
- KW Kneespace Width

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
			D	W	H	A	KW			
U-SHAPED WORKSURFACE 	SOFTENED RIM									
	25N3672WSUW	Wood	\$ 1442	36 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	90 lbs.	3.8
	25N3672WSUL	Laminate	789	36 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	90 lbs.	3.8
	25N3072WSUW	Wood	\$ 1264	30 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	76 lbs.	3.6
	25N3072WSUL	Laminate	607	30 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	76 lbs.	3.6
	25N3066WSUW	Wood	\$ 1193	30 ¹ / ₁₆	66	1 ³ / ₁₆	—	—	70 lbs.	3.3
	25N3066WSUL	Laminate	540	30 ¹ / ₁₆	66	1 ³ / ₁₆	—	—	70 lbs.	3.3
	25N2460WSUW	Wood	\$ 778	24	60	1 ³ / ₁₆	—	—	69 lbs.	2.8
	25N2460WSUL	Laminate	434	24	60	1 ³ / ₁₆	—	—	69 lbs.	2.8
	25N2448WSUW	Wood	\$ 686	24	48	1 ³ / ₁₆	—	—	57 lbs.	2.3
	25N2448WSUL	Laminate	381	24	48	1 ³ / ₁₆	—	—	57 lbs.	2.3

- To add full modesty panel, specify a panel that is 18" shorter than the width of the top; end panel, support base, and support base bracket must also be ordered; see page 214 for support base bracket
- Wire Manager available on back, the straight edge of the worksurface; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Worksurfaces can be ordered in 1/8" increments in width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired width
- Modified depth not available on this shape
- For undersurface wire managers, see page 685
- Not recommended for use with Epicenter slat wall

TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Wire Manager
7. Modified Width
8. Veneer Top Finish/Laminated Top Color
9. Worksurface Sheen (wood models)

SAMPLE MODEL NUMBER:

25N3672WSUW M V X D1B461 X R HN

• See pages 91-95 for all options available in Epic

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS				CARTONED WEIGHT	CUBIC FEET
		D	W	H	A		
U-SHAPED WORKSURFACE (CONTINUED)							
KNIFE RIM							
25N3974WSUWK1 Wood	\$ 1878	39½	73½	1¾	—	95 lbs.	4.0
25N3974WSULK1 Laminate	1222	39½	73½	1¾	—	95 lbs.	4.0
25N3374WSUWK1 Wood	\$ 1641	33½	73½	1¾	—	80 lbs.	3.8
25N3374WSULK1 Laminate	940	33½	73½	1¾	—	80 lbs.	3.8
25N3368WSUWK1 Wood	\$ 1550	33½	67½	1¾	—	74 lbs.	3.5
25N3368WSULK1 Laminate	836	33½	67½	1¾	—	74 lbs.	3.5
25N2762WSUWK1 Wood	\$ 1009	27	61½	1¾	—	72 lbs.	2.9
25N2762WSULK1 Laminate	673	27	61½	1¾	—	72 lbs.	2.9
25N2750WSUWK1 Wood	\$ 892	27	49½	1¾	—	60 lbs.	2.4
25N2750WSULK1 Laminate	592	27	49½	1¾	—	60 lbs.	2.4



- To add full modesty panel, specify a panel that is 18" shorter than the width of the top; end panel, support base, and support base bracket must also be ordered; see page 214 for support base bracket
- Wire Manager available on back, the straight edge of the worksurface; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Worksurfaces can be ordered in ½" increments in width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired width
- Modified depth not available on this shape
- For undersurface wire managers, see page 685
- Not recommended for use with Epicenter slat wall

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 96 for grommet locations; and page 94 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 211 for support options
- Refer to pages 663-705 for accessories

BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

	MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET	
				D	W	H					
<p>EXTENDED U-SHAPED WORKSURFACE</p> <p>Left shown</p>	SOFTENED RIM										
		LEFT	RIGHT								
	25N3672WSUELW2	25N3672WSUERW2	Wood	\$ 1459	36 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	90 lbs.	3.8
	25N3672WSUELL2	25N3672WSUERL2	Laminate	932	36 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	90 lbs.	3.8
	25N3672WSUELW3	25N3672WSUERW3	Wood	\$ 1508	36 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	90 lbs.	3.8
	25N3672WSUELL3	25N3672WSUERL3	Laminate	967	36 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	90 lbs.	3.8
		KNIFE RIM									
		LEFT	RIGHT								
	25N3874WSUELW2K1	25N3874WSUERW2K1	Wood	\$ 1896	37 ⁷ / ₁₆	73 ⁷ / ₁₆	1 ³ / ₁₆	—	—	95 lbs.	4.0
	25N3874WSUELL2K1	25N3874WSUERL2K1	Laminate	1444	37 ⁷ / ₁₆	73 ⁷ / ₁₆	1 ³ / ₁₆	—	—	95 lbs.	4.0
25N3874WSUELW3K1	25N3874WSUERW3K1	Wood	\$ 1960	37 ⁷ / ₁₆	73 ⁷ / ₁₆	1 ³ / ₁₆	—	—	95 lbs.	4.0	
25N3874WSUELL3K1	25N3874WSUERL3K1	Laminate	1499	37 ⁷ / ₁₆	73 ⁷ / ₁₆	1 ³ / ₁₆	—	—	95 lbs.	4.0	

- Wire Manager available on back; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Modified depth and width not available on this shape
- For undersurface wire managers, see page 685
- Not recommended for use with Epicenter slat wall
- Models ending in 2 – utilize with 24" deep worksurfaces
- Models ending in 3 – utilize with 30" deep worksurfaces

	MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET	
				D	W	H					
<p>P-SHAPED WORKSURFACE</p> <p>Right shown</p>	SOFTENED RIM										
		LEFT	RIGHT								
	25N3072WSPWLW	25N3072WSPRW	Wood	\$ 1513	30 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	69 lbs.	3.6
	25N3072WSPLL	25N3072WSPRL	Laminate	1046	30 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	69 lbs.	3.6
		KNIFE RIM									
		LEFT	RIGHT								
	25N3374WSPWLK1	25N3374WSPRWK1	Wood	\$ 1967	33 ³ / ₁₆	73 ³ / ₁₆	1 ³ / ₁₆	—	—	72 lbs.	3.8
	25N3374WSPLLK1	25N3374WSPRLK1	Laminate	1621	33 ³ / ₁₆	73 ³ / ₁₆	1 ³ / ₁₆	—	—	72 lbs.	3.8

- To add full modesty panel, specify a panel that is 18" shorter than the width of the top; end panel, support base, and support base bracket must also be ordered; see page 214 for support base bracket
- Wire Manager available on back, the straight edge of the worksurface; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Worksurfaces can be ordered in 1/8" increments in width to a minimum of 59¹/₁₆" at no upcharge
- When ordering a worksurface with a size modification, specify desired width
- Modified depth not available on this shape
- For undersurface wire managers, see page 685
- Not recommended for use with Epicenter slat wall

TO ORDER, SPECIFY:

1. Model Number
 2. Worksurface Type
 3. Rim Profile
 4. PVC Rim Color (laminite models)
 5. Grommet
 6. Wire Manager
 7. Modified Width
 8. Veneer Top Finish/Laminite Top Color
 9. Worksurface Sheen (wood models)
- See pages 91-95 for all options available in Epic

SAMPLE MODEL NUMBERS:

25N3072WSPLL E VCW G1C D1B485 70.5 CW
 25N3672WSUERW2 M V X X N MC

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS				CARTONED WEIGHT	CUBIC FEET				
		D	W	H	A						
EXTENDED CORNER P-SHAPED WORKSURFACE											
SOFTENED RIM											
LEFT				RIGHT							
25N3672WSPWLW2		25N3672WSPERW2	Wood	\$ 1697	35 ³ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	–	–	73 lbs.	4.9
25N3672WSPWLL2		25N3672WSPERL2	Laminite	1181	35 ³ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	–	–	73 lbs.	4.9
25N3672WSPWLW3		25N3672WSPERW3	Wood	\$ 1747	35 ³ / ₁₆	73 ³ / ₁₆	1 ³ / ₁₆	–	–	73 lbs.	4.9
25N3672WSPWLL3		25N3672WSPERL3	Laminite	1217	35 ³ / ₁₆	73 ³ / ₁₆	1 ³ / ₁₆	–	–	73 lbs.	4.9
KNIFE RIM											
LEFT				RIGHT							
25N3874WSPWLW2K1		25N3874WSPERW2K1	Wood	\$ 2205	37 ⁷ / ₁₆	73 ³ / ₁₆	1 ³ / ₁₆	–	–	77 lbs.	5.1
25N3874WSPWLL2K1		25N3874WSPERL2K1	Laminite	1834	37 ⁷ / ₁₆	73 ³ / ₁₆	1 ³ / ₁₆	–	–	77 lbs.	5.1
25N3874WSPWLW3K1		25N3874WSPERW3K1	Wood	\$ 2272	37 ⁷ / ₁₆	73 ³ / ₁₆	1 ³ / ₁₆	–	–	77 lbs.	5.1
25N3874WSPWLL3K1		25N3874WSPERL3K1	Laminite	1888	37 ⁷ / ₁₆	73 ³ / ₁₆	1 ³ / ₁₆	–	–	77 lbs.	5.1

- Models ending in 2 - utilize with 24" deep worksurfaces
- Models ending in 3 - utilize with 30" deep worksurfaces
- To add full modesty panel, specify a panel that is 18" shorter than the width of the top; end panel, support base, and support base bracket must also be ordered; see page 214 for support base bracket
- Wire Manager available on back, the straight edge of the worksurface; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Modified depth and width not available on this shape
- For undersurface wire managers, see page 685

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile available on user side (indicated by K1)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 96 for grommet locations; and page 94 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 211 for support options
- Refer to pages 663-705 for accessories

BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

	MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
				D	W	H	A	KW			
<p>J-SHAPED WORKSURFACE</p>  <p>Left shown</p>	SOFTENED RIM										
	LEFT	RIGHT									
	25N4272WSJLW	25N4272WSJRW	Wood	\$ 1726	42	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	103 lbs.	4.0
	25N4272WSJLL	25N4272WSJRL	Laminate	1206	42	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	103 lbs.	4.0
	KNIFE RIM										
	LEFT	RIGHT									
	25N4574WSJLWK1	25N4574WSJRWK1	Wood	\$ 2244	43 ¹ / ₂	73 ⁷ / ₁₆	1 ³ / ₁₆	—	—	108 lbs.	4.2
	25N4574WSJLLK1	25N4574WSJRLK1	Laminate	1869	43 ¹ / ₂	73 ⁷ / ₁₆	1 ³ / ₁₆	—	—	108 lbs.	4.2

- Wire Manager available on back, the straight edge of the worksurface; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- To add full modesty panel, specify a panel that is 18" shorter than the width of the top; end panel, support base, and support base bracket must also be ordered; see page 214 for support base bracket
- Modified depth and width not available on this shape
- For undersurface wire managers, see page 685

TO ORDER, SPECIFY:


1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Wire Manager
7. Veneer Top Finish/Laminated Top Color
8. Worksurface Sheen (wood models)

SAMPLE MODEL NUMBERS:

25N4272WSJLL E VMC G1C X MC
 25N4242WSCSW2 V G1C X R MC

• See pages 91-95 for all options available in Epic

CORNER WORKSURFACE



Grain direction runs diagonally

MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS				A	KW	CARTONED WEIGHT	CUBIC FEET
			D	W	H					
SOFTENED RIM										
25N4242WSCSW2	Wood	\$ 1048	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ¹ / ₁₆	—	—	59 lbs.	3.8	
25N4242WSCSL2	Laminate	659	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ¹ / ₁₆	—	—	59 lbs.	3.8	
25N4242WSCSW3	Wood	\$ 1154	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ¹ / ₁₆	—	—	59 lbs.	3.8	
25N4242WSCSL3	Laminate	726	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ¹ / ₁₆	—	—	59 lbs.	3.8	
25N4242WSCSW7	Wood	\$ 1154	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ¹ / ₁₆	—	—	59 lbs.	3.8	
25N4242WSCSL7	Laminate	726	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ¹ / ₁₆	—	—	59 lbs.	3.8	
25N4242WSCSW9	Wood	\$ 1154	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ¹ / ₁₆	—	—	59 lbs.	3.8	
25N4242WSCSL9	Laminate	726	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ¹ / ₁₆	—	—	59 lbs.	3.8	
25N3636WSCSW2	Wood	\$ 965	36 ¹ / ₁₆	36 ¹ / ₁₆	1 ¹ / ₁₆	—	—	45 lbs.	3.8	
25N3636WSCSL2	Laminate	605	36 ¹ / ₁₆	36 ¹ / ₁₆	1 ¹ / ₁₆	—	—	45 lbs.	3.8	

- Grain direction runs diagonally
- Will accommodate 24" deep extension worksurfaces on both sides
- Models ending in 2 - utilize with 24" deep worksurfaces
- Models ending in 3 - utilize with 30" deep worksurfaces
- Models ending in 7 - utilize with 1 left 30" deep and 1 right 24" deep worksurfaces
- Models ending in 9 - utilize with 1 left 24" deep and 1 right 30" deep worksurfaces
- 42" corner worksurfaces have 25" on front edge
- 36" corner worksurfaces have 17" on front edge
- Corner worksurface assembled to corner unit is not intended for freestanding unit
- Wire Manager available on left side, right side or left & right sides; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Modified depth and width not available on this shape
- For undersurface wire managers, see page 685

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 96 for grommet locations; and page 94 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 211 for support options
- Refer to pages 663-705 for accessories


BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

CORNER WORKSURFACE (CONTINUED)



Grain direction runs diagonally

MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
			D	W	H	A	KW		
KNIFE RIM									
25N4242WSCSW2K1	Wood	\$ 1363	42½"	42½"	1¾"	—	—	62 lbs.	4.0
25N4242WSCSL2K1	Laminate	1023	42½"	42½"	1¾"	—	—	62 lbs.	4.0
<hr/>									
25N4242WSCSW3K1	Wood	\$ 1501	42½"	42½"	1¾"	—	—	62 lbs.	4.0
25N4242WSCSL3K1	Laminate	1126	42½"	42½"	1¾"	—	—	62 lbs.	4.0
<hr/>									
25N4242WSCSW7K1	Wood	\$ 1501	42½"	42½"	1¾"	—	—	62 lbs.	4.0
25N4242WSCSL7K1	Laminate	1126	42½"	42½"	1¾"	—	—	62 lbs.	4.0
<hr/>									
25N4242WSCSW9K1	Wood	\$ 1501	42½"	42½"	1¾"	—	—	62 lbs.	4.0
25N4242WSCSL9K1	Laminate	1126	42½"	42½"	1¾"	—	—	62 lbs.	4.0
<hr/>									
25N3636WSCSW2K1	Wood	\$ 1253	36½"	36½"	1¾"	—	—	47 lbs.	4.0
25N3636WSCSL2K1	Laminate	938	36½"	36½"	1¾"	—	—	47 lbs.	4.0

- Grain direction runs diagonally
- Will accommodate 24" deep extension worksurfaces on both sides
- Models ending in 2 - utilize with 24" deep worksurfaces
- Models ending in 3 - utilize with 30" deep worksurfaces
- Models ending in 7 - utilize with 1 left 30" deep and 1 right 24" deep worksurfaces
- Models ending in 9 - utilize with 1 left 24" deep and 1 right 30" deep worksurfaces
- 42" corner worksurfaces have 25" on front edge
- 36" corner worksurfaces have 17" on front edge
- Corner worksurface assembled to corner unit is not intended for freestanding unit
- Wire Manager available on left side, right side or left & right sides; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Modified depth and width not available on this shape
- For undersurface wire managers, see page 685

TO ORDER, SPECIFY:


1. Model Number
2. Rim Profile
3. PVC Rim Color (laminated models)
4. Grommet
5. Wire Manager
6. Veneer Top Finish/Laminated Top Color
7. Worksurface Sheen (wood models)

SAMPLE MODEL NUMBERS:

25N4242WSCSW2K1 K G1C X R CL
 25N60WSHRL VCL G1C D1B405 CL

• See pages 91-95 for all options available in Epic

HALF-ROUND WORKSURFACE



MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS				A	KW	CARTONED WEIGHT	CUBIC FEET
			D	W	H					
SOFTENED RIM										
25N60WSHRW	Wood	\$ 743	30	60	1 ³ / ₁₆	—	—	69 lbs.	2.8	
25N60WSHRL	Laminate	425	30	60	1 ³ / ₁₆	—	—	69 lbs.	2.8	
KNIFE RIM										
25N48WSHRW	Wood	\$ 617	24	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	57 lbs.	2.3	
25N48WSHRL	Laminate	355	24	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	57 lbs.	2.3	
25N63WSHRWK1	Wood	\$ 964	31 ¹ / ₂	63	1 ³ / ₁₆	—	—	72 lbs.	2.9	
25N63WSHRLK1	Laminate	657	31 ¹ / ₂	63	1 ³ / ₁₆	—	—	72 lbs.	2.9	
25N51WSHRWK1	Wood	\$ 802	25 ¹ / ₂	51 ¹ / ₁₆	1 ³ / ₁₆	—	—	60 lbs.	2.4	
25N51WSHRLK1	Laminate	550	25 ¹ / ₂	51 ¹ / ₁₆	1 ³ / ₁₆	—	—	60 lbs.	2.4	

- Rim profile on radius edge of surface only
- Only available grommet option is center location
- Wire Manager available on back side-the straight side of the worksurface; see page 92 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 214
- Modified depth and width not available on this shape
- For undersurface wire managers, see page 685

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on all 4 sides for round and square tops
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 96 for grommet locations; and page 94 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 211 for support options
- Refer to pages 663-705 for accessories

BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
			D	W	H	A	KW			
<p>ROUND TABLE TOP</p> 	SOFTENED RIM		DI		H					
	25N48WSRNW	Wood	\$ 967	48 ¹ / ₁₆	—	1 ³ / ₁₆	—	—	71 lbs.	4.5
	25N48WSRNL	Laminate	469	48 ¹ / ₁₆	—	1 ³ / ₁₆	—	—	71 lbs.	4.5
	25N42WSRNW	Wood	\$ 857	42 ¹ / ₁₆	—	1 ³ / ₁₆	—	—	54 lbs.	3.8
	25N42WSRNL	Laminate	402	42 ¹ / ₁₆	—	1 ³ / ₁₆	—	—	54 lbs.	3.8
	25N36WSRNW	Wood	\$ 718	36 ¹ / ₁₆	—	1 ³ / ₁₆	—	—	40 lbs.	3.0
	25N36WSRNL	Laminate	312	36 ¹ / ₁₆	—	1 ³ / ₁₆	—	—	40 lbs.	3.0
	25N30WSRNW	Wood	\$ 609	30 ¹ / ₁₆	—	1 ³ / ₁₆	—	—	33 lbs.	2.0
	25N30WSRNL	Laminate	265	30 ¹ / ₁₆	—	1 ³ / ₁₆	—	—	33 lbs.	2.0
	KNIFE RIM									
	25N48WSRNWK1	Wood	\$ 1258	48 ¹ / ₁₆	—	1 ³ / ₁₆	—	—	75 lbs.	4.7
	25N48WSRNLK1	Laminate	727	48 ¹ / ₁₆	—	1 ³ / ₁₆	—	—	75 lbs.	4.7
	25N42WSRNWK1	Wood	\$ 1113	42 ¹ / ₁₆	—	1 ³ / ₁₆	—	—	57 lbs.	4.0
	25N42WSRNLK1	Laminate	626	42 ¹ / ₁₆	—	1 ³ / ₁₆	—	—	57 lbs.	4.0
	25N36WSRNWK1	Wood	\$ 932	36 ¹ / ₁₆	—	1 ³ / ₁₆	—	—	42 lbs.	3.2
	25N36WSRNLK1	Laminate	484	36 ¹ / ₁₆	—	1 ³ / ₁₆	—	—	42 lbs.	3.2
	25N30WSRNWK1	Wood	\$ 794	30 ¹ / ₁₆	—	1 ³ / ₁₆	—	—	33 lbs.	2.0
	25N30WSRNLK1	Laminate	412	30 ¹ / ₁₆	—	1 ³ / ₁₆	—	—	33 lbs.	2.0

- Reference pages 576-579 for applicable bases
- Do not specify worksurface type
- (K1) knife edge on all 4 sides

TO ORDER, SPECIFY:


1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Veneer Top Finish/Laminated Top Color
7. Worksurface Sheen (wood models)

SAMPLE MODEL NUMBERS:

25N48WSRNL VCL G1C CL
 25N4848WSSQL M VCL G1C CL

• See pages 91-95 for all options available in Epic

SQUARE TABLE TOP



MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS				A	KW	CARTONED WEIGHT	CUBIC FEET
		D	W	H					
SOFTENED RIM									
25N4848WSSQW Wood	\$ 952	48 ¹ / ₁₆	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	76 lbs.	4.5	
25N4848WSSQL Laminate	459	48 ¹ / ₁₆	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	76 lbs.	4.5	
<hr/>									
25N4242WSSQW Wood	\$ 838	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	59 lbs.	3.8	
25N4242WSSQL Laminate	399	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	59 lbs.	3.8	
<hr/>									
25N3636WSSQW Wood	\$ 709	36 ¹ / ₁₆	36 ¹ / ₁₆	1 ³ / ₁₆	—	—	45 lbs.	3.0	
25N3636WSSQL Laminate	306	36 ¹ / ₁₆	36 ¹ / ₁₆	1 ³ / ₁₆	—	—	45 lbs.	3.0	
<hr/>									
25N3030WSSQW Wood	\$ 603	30 ¹ / ₁₆	30 ¹ / ₁₆	1 ³ / ₁₆	—	—	33 lbs.	2.0	
25N3030WSSQL Laminate	260	30 ¹ / ₁₆	30 ¹ / ₁₆	1 ³ / ₁₆	—	—	33 lbs.	2.0	
<hr/>									
KNIFE RIM									
25N4848WSSQWK1 Wood	\$ 1238	48 ¹ / ₁₆	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	80 lbs.	4.7	
25N4848WSSQLK1 Laminate	712	48 ¹ / ₁₆	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	80 lbs.	4.7	
<hr/>									
25N4242WSSQWK1 Wood	\$ 1091	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	62 lbs.	4.0	
25N4242WSSQLK1 Laminate	618	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	62 lbs.	4.0	
<hr/>									
25N3636WSSQWK1 Wood	\$ 922	36 ¹ / ₁₆	36 ¹ / ₁₆	1 ³ / ₁₆	—	—	47 lbs.	3.2	
25N3636WSSQLK1 Laminate	472	36 ¹ / ₁₆	36 ¹ / ₁₆	1 ³ / ₁₆	—	—	47 lbs.	3.2	
<hr/>									
25N3030WSSQWK1 Wood	\$ 783	30 ¹ / ₁₆	30 ¹ / ₁₆	1 ³ / ₁₆	—	—	33 lbs.	2.0	
25N3030WSSQLK1 Laminate	401	30 ¹ / ₁₆	30 ¹ / ₁₆	1 ³ / ₁₆	—	—	33 lbs.	2.0	

- Reference pages 576-579 for applicable bases
- (K1) knife edge on all 4 sides

PRODUCT SPECIFICATIONS

- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 214) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended


BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY


- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

	MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET
				D	W	H				
PEDESTAL - UNDERSURFACE BOX/BOX/FILE 29" DEEP	25N291829PUBBFW	Wood	\$ 1564	28 ³ / ₈	17 ¹ / ₂	27 ³ / ₄	—	—	95 lbs.	10.6
	25N291829PUBBFL	Laminate	981	28 ³ / ₈	17 ¹ / ₂	27 ³ / ₄	—	—	95 lbs.	10.6
	25N291529PUBBFW	Wood	\$ 1474	28 ³ / ₈	14 ¹ / ₂	27 ³ / ₄	—	—	83 lbs.	8.5
	25N291529PUBBFL	Laminate	926	28 ³ / ₈	14 ¹ / ₂	27 ³ / ₄	—	—	83 lbs.	8.5



- Specify component worksurfaces and backs to finish as needed
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
- Not intended for use in a freestanding application

PEDESTAL - UNDERSURFACE BOX/BOX/FILE 23" DEEP	25N231829PUBBFW	Wood	\$ 1466	22 ³ / ₈	17 ¹ / ₂	27 ³ / ₄	—	—	75 lbs.	11.4
	25N231829PUBBFL	Laminate	922	22 ³ / ₈	17 ¹ / ₂	27 ³ / ₄	—	—	75 lbs.	11.4
	25N231529PUBBFW	Wood	\$ 1386	22 ³ / ₈	14 ¹ / ₂	27 ³ / ₄	—	—	70 lbs.	9.9
	25N231529PUBBFL	Laminate	866	22 ³ / ₈	14 ¹ / ₂	27 ³ / ₄	—	—	70 lbs.	9.9




- Specify component worksurfaces and backs to finish as needed
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
- Not intended for use in a freestanding application

PEDESTAL - UNDERSURFACE BOX/BOX/FILE 17" DEEP	25N171829PUBBFW	Wood	\$ 1466	16 ¹ / ₂	17 ¹ / ₂	27 ³ / ₄	—	—	50 lbs.	9.1
	25N171829PUBBFL	Laminate	922	16 ¹ / ₂	17 ¹ / ₂	27 ³ / ₄	—	—	50 lbs.	9.1
	25N171529PUBBFW	Wood	\$ 1386	16 ¹ / ₂	14 ¹ / ₂	27 ³ / ₄	—	—	49 lbs.	8.1
	25N171529PUBBFL	Laminate	866	16 ¹ / ₂	14 ¹ / ₂	27 ³ / ₄	—	—	49 lbs.	8.1



- Specify component worksurfaces and backs to finish as needed
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
- Not intended for use in a freestanding application

PEDESTAL - UNDERSURFACE FILE/FILE 29" DEEP	25N291829PUFFW	Wood	\$ 1564	28 ³ / ₈	17 ¹ / ₂	27 ³ / ₄	—	—	95 lbs.	10.6
	25N291829PUFFL	Laminate	981	28 ³ / ₈	17 ¹ / ₂	27 ³ / ₄	—	—	95 lbs.	10.6
	25N291529PUFFW	Wood	\$ 1474	28 ³ / ₈	14 ¹ / ₂	27 ³ / ₄	—	—	83 lbs.	8.5
	25N291529PUFFL	Laminate	926	28 ³ / ₈	14 ¹ / ₂	27 ³ / ₄	—	—	83 lbs.	8.5




- Specify component worksurfaces and backs to finish as needed
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
- Not intended for use in a freestanding application

TO ORDER, SPECIFY:

1. Model Number
 2. Pull
 3. Pedestal Grommet
 4. Locking
 5. Foot Color
 6. Laminate Door/Drawer Color
 7. Veneer Chassis Finish/Laminate Chassis Color
- See pages 91-95 for all options available in Epic


SAMPLE MODEL NUMBERS:

25N291829PUBBFL 89MB KRB G22 FR462 405 MH
 25N351829SESLW G22 FR462 MH

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET
			D	W	H				
	25N231829PUFFW Wood	\$ 1466	22 ³ / ₁₆	17 ¹ / ₁₆	27 ³ / ₄	–	–	75 lbs.	11.4
	25N231829PUFFL Laminate	922	22 ³ / ₁₆	17 ¹ / ₁₆	27 ³ / ₄	–	–	75 lbs.	11.4
	25N231529PUFFW Wood	\$ 1386	22 ³ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	–	–	70 lbs.	9.9
	25N231529PUFFL Laminate	866	22 ³ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	–	–	70 lbs.	9.9

- Specify component worksurfaces and backs to finish as needed
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
- Not intended for use in a freestanding application

PEDESTAL - UNDERSURFACE FILE/FILE 17" DEEP

	25N171829PUFFW Wood	\$ 1466	16 ¹ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	–	–	50 lbs.	9.1
	25N171829PUFFL Laminate	922	16 ¹ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	–	–	50 lbs.	9.1
	25N171529PUFFW Wood	\$ 1386	16 ¹ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	–	–	49 lbs.	8.1
	25N171529PUFFL Laminate	866	16 ¹ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	–	–	49 lbs.	8.1

- Specify component worksurfaces and backs to finish as needed
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
- Not intended for use in a freestanding application

SUPPORT PEDESTAL

	LEFT	RIGHT									
	25N351829SESLW	25N351829SESRL	Wood	\$ 1082	35 ¹ / ₁₆	17 ¹ / ₁₆	27 ³ / ₄	–	–	101 lbs.	11.1
	25N351829SESLW	25N351829SESRL	Laminate	667	35 ¹ / ₁₆	17 ¹ / ₁₆	27 ³ / ₄	–	–	101 lbs.	11.1
	25N351529SESLW	25N351529SESRL	Wood	\$ 1023	35 ¹ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	–	–	89 lbs.	9.1
	25N351529SESLW	25N351529SESRL	Laminate	630	35 ¹ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	–	–	89 lbs.	9.1
	25N291829SESLW	25N291829SESRL	Wood	\$ 1018	28 ⁷ / ₁₆	17 ¹ / ₁₆	27 ³ / ₄	–	–	95 lbs.	10.6
	25N291829SESLW	25N291829SESRL	Laminate	628	28 ⁷ / ₁₆	17 ¹ / ₁₆	27 ³ / ₄	–	–	95 lbs.	10.6
	25N291529SESLW	25N291529SESRL	Wood	\$ 960	28 ⁷ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	–	–	83 lbs.	8.5
	25N291529SESLW	25N291529SESRL	Laminate	592	28 ⁷ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	–	–	83 lbs.	8.5
	25N231829SESLW	25N231829SESRL	Wood	\$ 953	22 ³ / ₁₆	17 ¹ / ₁₆	27 ³ / ₄	–	–	95 lbs.	10.6
	25N231829SESLW	25N231829SESRL	Laminate	591	22 ³ / ₁₆	17 ¹ / ₁₆	27 ³ / ₄	–	–	95 lbs.	10.6
	25N231529SESLW	25N231529SESRL	Wood	\$ 902	22 ³ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	–	–	83 lbs.	8.5
	25N231529SESLW	25N231529SESRL	Laminate	552	22 ³ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	–	–	83 lbs.	8.5

- Specify component worksurfaces and backs to finish as needed
- For use when creating single pedestal desks from components or with U-surfaces or P-surfaces
- Not intended for use in a freestanding application

PRODUCT SPECIFICATIONS

- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 214) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended


BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width


**LATERAL FILE UNIT
UNDERSURFACE -
2 DRAWER**



MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
		D	W	H	A	KW		
23" DEPTH								
25N2336LFM2W Wood	\$ 1867	22 ³ / ₁₆	35 ⁷ / ₈	27 ³ / ₄	-	-	120 lbs.	20.4
25N2336LFM2L Laminate	1035	22 ³ / ₁₆	35 ⁷ / ₈	27 ³ / ₄	-	-	120 lbs.	20.4
17" DEPTH								
25N1736LFM2W Wood	\$ 1867	16 ³ / ₁₆	35 ⁷ / ₈	27 ³ / ₄	-	-	119 lbs.	16.3
25N1736LFM2L Laminate	1035	16 ³ / ₁₆	35 ⁷ / ₈	27 ³ / ₄	-	-	119 lbs.	16.3
25N1730LFM2W Wood	\$ 1721	16 ³ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	-	-	102 lbs.	13.7
25N1730LFM2L Laminate	1007	16 ³ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	-	-	102 lbs.	13.7

- Specify component worksurfaces and backs to finish as needed
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
- When specifying Horizon pulls, lateral files will have 2 pulls on each drawer front

**LATERAL FILE UNIT
UNDERSURFACE -
3 DRAWER**



25N2436LFM3W Wood	\$ 3368	23 ³ / ₁₆	35 ⁷ / ₈	40 ³ / ₁₆	-	-	210 lbs.	30.0
25N2436LFM3L Laminate	2154	23 ³ / ₁₆	35 ⁷ / ₈	40 ³ / ₁₆	-	-	210 lbs.	30.0
25N2430LFM3W Wood	\$ 3199	23 ³ / ₁₆	29 ¹ / ₁₆	40 ³ / ₁₆	-	-	210 lbs.	30.0
25N2430LFM3L Laminate	2046	23 ³ / ₁₆	29 ¹ / ₁₆	40 ³ / ₁₆	-	-	210 lbs.	30.0

- Top of unit is finished with flat edge detail
- Interlock mechanism allows only 1 drawer to be open at a time
- For use with component common top when ganging units together
- Unit has full finished back
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
- When specifying Horizon pulls, lateral files will have 2 pulls on each drawer front

TO ORDER, SPECIFY:


1. Model Number
2. Pull
3. Pedestal Grommet
4. Locking
5. Foot Color
6. Laminate Door/Drawer Color
7. Veneer Chassis Finish/Laminate Chassis Color

SAMPLE MODEL NUMBERS:

25N2336LFM2L 89MB KRB X FR462 CW CW
 25N2436LFM3L 89MB KS1B FR462 2977 480 462

• See pages 91-95 for all options available in Epic


**LATERAL FILE UNIT
 UNDERSURFACE -
 4 DRAWER**



MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS				KW	CARTONED WEIGHT	CUBIC FEET
		D	W	H	A			
25N2436LFM4W Wood	\$ 3915	23 ³ / ₁₆	35 ⁷ / ₁₆	52 ¹ / ₁₆	—	—	265 lbs.	33.4
25N2436LFM4L Laminate	2478	23 ³ / ₁₆	35 ⁷ / ₁₆	52 ¹ / ₁₆	—	—	265 lbs.	33.4
25N2430LFM4W Wood	\$ 3718	23 ³ / ₁₆	29 ¹ / ₁₆	52 ¹ / ₁₆	—	—	265 lbs.	33.4
25N2430LFM4L Laminate	2355	23 ³ / ₁₆	29 ¹ / ₁₆	52 ¹ / ₁₆	—	—	265 lbs.	33.4

- Top of unit is finished with flat edge detail
- Interlock mechanism allows only 1 drawer to be open at a time
- For use with component common top when ganging units together
- Unit has full finished back
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
- When specifying Horizon pulls, lateral files will have 2 pulls on each drawer front

**DOUBLE DOOR UNIT
 UNDERSURFACE**



23" DEPTH								
25N233629PUHW Wood	\$ 1496	22 ³ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	110 lbs.	20.4
25N233629PUHL Laminate	900	22 ³ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	110 lbs.	20.4
25N233029PUHW Wood	\$ 1350	22 ³ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	91 lbs.	17.4
25N233029PUHL Laminate	849	22 ³ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	91 lbs.	17.4
25N232429PUHW Wood	\$ 1297	22 ³ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	80 lbs.	16.0
25N232429PUHL Laminate	797	22 ³ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	80 lbs.	16.0

17" DEPTH								
25N173629PUHW Wood	\$ 1496	16 ¹ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	119 lbs.	16.3
25N173629PUHL Laminate	900	16 ¹ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	119 lbs.	16.3
25N173029PUHW Wood	\$ 1350	16 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	90 lbs.	13.7
25N173029PUHL Laminate	849	16 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	90 lbs.	13.7
25N172429PUHW Wood	\$ 1297	16 ¹ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	75 lbs.	10.8
25N172429PUHL Laminate	797	16 ¹ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	75 lbs.	10.8

- Specify component worksurfaces and backs to finish as needed
- Unit features an adjustable shelf
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available

PRODUCT SPECIFICATIONS

- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 214) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended
- Sliding doors feature a face mount powder coated aluminum track on top and bottom of cabinet

BASE MODEL KEY

- W Wood Unit
- L Laminate Unit


DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

MODEL NO./DESCRIPTION		GRADE 1	GRADE 2	LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET
					D	W	H				
DOUBLE DOOR UNIT SLIDING DOORS UNDERSURFACE											
RESIN DOORS 23" DEPTH											
25N233629PUSAW	Wood	\$ 2550	\$ 2847	\$ 2953	22 ³ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	110 lbs.	20.4
25N233629PUSAL	Laminate	1552	1849	1955	22 ³ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	110 lbs.	20.4
25N233029PUSAW	Wood	\$ 2442	\$ 2688	\$ 2776	22 ³ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	91 lbs.	17.4
25N233029PUSAL	Laminate	1464	1710	1798	22 ³ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	91 lbs.	17.4
25N232429PUSAW	Wood	\$ 2347	\$ 2543	\$ 2613	22 ³ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	80 lbs.	16.0
25N232429PUSAL	Laminate	1374	1570	1640	22 ³ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	80 lbs.	16.0
17" DEPTH											
25N173629PUSAW	Wood	\$ 2550	\$ 2847	\$ 2953	16 ¹ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	119 lbs.	16.3
25N173629PUSAL	Laminate	1552	1849	1955	16 ¹ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	119 lbs.	16.3
25N173029PUSAW	Wood	\$ 2442	\$ 2688	\$ 2776	16 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	90 lbs.	13.7
25N173029PUSAL	Laminate	1464	1710	1798	16 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	90 lbs.	13.7
25N172429PUSAW	Wood	\$ 2347	\$ 2543	\$ 2613	16 ¹ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	75 lbs.	10.8
25N172429PUSAL	Laminate	1374	1570	1640	16 ¹ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	75 lbs.	10.8

- Specify component worksurfaces and backs to finish as needed
- Unit features an adjustable shelf

**DOUBLE DOOR UNIT
SLIDING DOORS
UNDERSURFACE**



TO ORDER, SPECIFY:


1. Model Number
2. Pull
3. Pedestal Grommet
4. Locking
5. Resin Grade/Door Color
6. Metal Door Color
7. Foot Color
8. Laminate Door/Drawer Color
9. Veneer Chassis Finish/Laminate Chassis Color
10. Door Track Paint Color

SAMPLE MODEL NUMBERS:

25N233629PUSAW G22 2 FR462 FR462 MH 501
 25N233629PUSMW G22 462 MH 501

• See pages 91-95 for all options available in Epic

**DOUBLE DOOR UNIT
 SLIDING DOORS
 UNDERSURFACE
 (CONTINUED)**



MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS				CARTONED WEIGHT	CUBIC FEET
		D	W	H	A		
METAL DOORS							
23" DEPTH							
25N233629PUSMW Wood	\$ 2550	22 ³ / ₈	35 ⁷ / ₈	27 ³ / ₄	—	110 lbs.	20.4
25N233629PUSML Laminate	1552	22 ³ / ₈	35 ⁷ / ₈	27 ³ / ₄	—	110 lbs.	20.4
<hr/>							
25N233029PUSMW Wood	\$ 2442	22 ³ / ₈	29 ¹ / ₂	27 ³ / ₄	—	91 lbs.	17.4
25N233029PUSML Laminate	1464	22 ³ / ₈	29 ¹ / ₂	27 ³ / ₄	—	91 lbs.	17.4
<hr/>							
25N232429PUSMW Wood	\$ 2347	22 ³ / ₈	23 ³ / ₄	27 ³ / ₄	—	80 lbs.	16.0
25N232429PUSML Laminate	1374	22 ³ / ₈	23 ³ / ₄	27 ³ / ₄	—	80 lbs.	16.0
<hr/>							
17" DEPTH							
25N173629PUSMW Wood	\$ 2550	16 ¹ / ₂	35 ⁷ / ₈	27 ³ / ₄	—	119 lbs.	16.3
25N173629PUSML Laminate	1552	16 ¹ / ₂	35 ⁷ / ₈	27 ³ / ₄	—	119 lbs.	16.3
<hr/>							
25N173029PUSMW Wood	\$ 2442	16 ¹ / ₂	29 ¹ / ₂	27 ³ / ₄	—	90 lbs.	13.7
25N173029PUSML Laminate	1464	16 ¹ / ₂	29 ¹ / ₂	27 ³ / ₄	—	90 lbs.	13.7
<hr/>							
25N172429PUSMW Wood	\$ 2347	16 ¹ / ₂	23 ³ / ₄	27 ³ / ₄	—	75 lbs.	10.8
25N172429PUSML Laminate	1374	16 ¹ / ₂	23 ³ / ₄	27 ³ / ₄	—	75 lbs.	10.8

- Specify component worksurfaces and backs to finish as needed
- Unit features an adjustable shelf

PRODUCT SPECIFICATIONS

- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 214) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended


BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

**OPEN BOOKCASE
UNDERSURFACE**



MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
		D	W	H	A	KW		
23" DEPTH								
25N233629PUOSW Wood	\$ 1344	22	35 ⁵ / ₈	27 ³ / ₄	—	—	90 lbs.	20.4
25N233629PUOSL Laminate	810	22	35 ⁵ / ₈	27 ³ / ₄	—	—	90 lbs.	20.4
<hr/>								
25N233029PUOSW Wood	\$ 1285	22	29 ¹ / ₂	27 ³ / ₄	—	—	85 lbs.	18.0
25N233029PUOSL Laminate	781	22	29 ¹ / ₂	27 ³ / ₄	—	—	85 lbs.	18.0
<hr/>								
25N232429PUOSW Wood	\$ 1236	22	23 ³ / ₄	27 ³ / ₄	—	—	80 lbs.	16.0
25N232429PUOSL Laminate	752	22	23 ³ / ₄	27 ³ / ₄	—	—	80 lbs.	16.0
<hr/>								
17" DEPTH								
25N173629PUOSW Wood	\$ 1344	16 ¹ / ₂	35 ⁵ / ₈	27 ³ / ₄	—	—	119 lbs.	16.3
25N173629PUOSL Laminate	810	16 ¹ / ₂	35 ⁵ / ₈	27 ³ / ₄	—	—	119 lbs.	16.3
<hr/>								
25N173029PUOSW Wood	\$ 1285	16 ¹ / ₂	29 ¹ / ₂	27 ³ / ₄	—	—	90 lbs.	13.7
25N173029PUOSL Laminate	781	16 ¹ / ₂	29 ¹ / ₂	27 ³ / ₄	—	—	90 lbs.	13.7
<hr/>								
25N172429PUOSW Wood	\$ 1236	16 ¹ / ₂	23 ³ / ₄	27 ³ / ₄	—	—	75 lbs.	10.8
25N172429PUOSL Laminate	752	16 ¹ / ₂	23 ³ / ₄	27 ³ / ₄	—	—	75 lbs.	10.8

- Specify component worksurfaces and backs to finish as needed
- Unit features an adjustable shelf


TO ORDER, SPECIFY:

1. Model Number
 2. Pull
 3. Pedestal Grommet
 4. Locking
 5. Metal Door or Shelf Color
 6. Foot Color
 7. Laminate Door/Drawer Color
 8. Veneer Chassis Finish/Laminate Chassis Color
- See pages 91-95 for all options available in Epic

SAMPLE MODEL NUMBER:


25N233629PUOSSL G22 501 FR50 MH
1

**STORAGE CABINET
METAL SLIDING SHELVES**



MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS				CARTONED WEIGHT	CUBIC FEET
		D	W	H	A		
25N233629PUOSSW Wood	\$ 2737	22	35 $\frac{1}{8}$	27 $\frac{3}{4}$	—	90 lbs.	20.4
25N233629PUOSSL Laminate	1843	22	35 $\frac{1}{8}$	27 $\frac{3}{4}$	—	90 lbs.	20.4
• Weight capacity: 49 pounds per shelf							
25N233029PUOSSW Wood	\$ 2693	22	29 $\frac{1}{8}$	27 $\frac{3}{4}$	—	85 lbs.	18.0
25N233029PUOSSL Laminate	1812	22	29 $\frac{1}{8}$	27 $\frac{3}{4}$	—	85 lbs.	18.0
• Weight capacity: 40 pounds per shelf							
25N232429PUOSSW Wood	\$ 2648	22	23 $\frac{3}{4}$	27 $\frac{3}{4}$	—	80 lbs.	16.0
25N232429PUOSSL Laminate	1782	22	23 $\frac{3}{4}$	27 $\frac{3}{4}$	—	80 lbs.	16.0
• Weight capacity: 31 pounds per shelf							
• Specify component worksurfaces and backs to finish as needed							
• Unit features 4 metal shelves on full extension slides							
• Shelf sizes are: 18 $\frac{1}{4}$ D x 32 $\frac{1}{8}$ W, 18 $\frac{1}{4}$ D x 26 $\frac{1}{8}$ W, or 18 $\frac{1}{4}$ D x 20 $\frac{1}{8}$ W of storage space and feature a non skid surface							

**MIXED-STORAGE CABINET
UNDERSURFACE**



Left shown

OPEN STORAGE ON LEFT 23" DEPTH		OPEN STORAGE ON RIGHT		LIST PRICE	DIMENSIONS				CARTONED WEIGHT	CUBIC FEET
MODEL NO.	DESCRIPTION	MODEL NO.	DESCRIPTION		D	W	H	A		
25N233629PU33W	25N233629PU32W	Wood		\$ 2215	22 $\frac{1}{8}$	35 $\frac{1}{8}$	27 $\frac{3}{4}$	—	90 lbs.	20.4
25N233629PU33L	25N233629PU32L	Laminate		1385	22 $\frac{1}{8}$	35 $\frac{1}{8}$	27 $\frac{3}{4}$	—	90 lbs.	20.4
25N233029PU33W	25N233029PU32W	Wood		\$ 2070	22 $\frac{1}{8}$	29 $\frac{1}{8}$	27 $\frac{3}{4}$	—	85 lbs.	18.0
25N233029PU33L	25N233029PU32L	Laminate		1358	22 $\frac{1}{8}$	29 $\frac{1}{8}$	27 $\frac{3}{4}$	—	85 lbs.	18.0
17" DEPTH				LIST PRICE	DIMENSIONS				CARTONED WEIGHT	CUBIC FEET
MODEL NO.	DESCRIPTION	MODEL NO.	DESCRIPTION		D	W	H	A		
25N173629PU33W	25N173629PU32W	Wood		\$ 2215	16 $\frac{1}{8}$	35 $\frac{1}{8}$	27 $\frac{3}{4}$	—	119 lbs.	16.3
25N173629PU33L	25N173629PU32L	Laminate		1385	16 $\frac{1}{8}$	35 $\frac{1}{8}$	27 $\frac{3}{4}$	—	119 lbs.	16.3
25N173029PU33W	25N173029PU32W	Wood		\$ 2070	16 $\frac{1}{8}$	29 $\frac{1}{8}$	27 $\frac{3}{4}$	—	90 lbs.	13.7
25N173029PU33L	25N173029PU32L	Laminate		1358	16 $\frac{1}{8}$	29 $\frac{1}{8}$	27 $\frac{3}{4}$	—	90 lbs.	13.7

- Specify component worksurfaces and backs to finish as needed
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
- When specifying Horizon pulls, lateral files will have 2 pulls on each drawer front

PRODUCT SPECIFICATIONS


- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 214) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended

BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

	MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
				D	W	H	A	KW			
MULTI-FILE STORAGE UNDERSURFACE  Left shown	FILE STORAGE ON LEFT	FILE STORAGE ON RIGHT									
	23" DEPTH										
	25N233629PU11W	25N233629PU10W	Wood	\$ 2714	22 ³ / ₁₆	35 ⁷ / ₈	27 ³ / ₄	—	—	90 lbs.	20.4
	25N233629PU11L	25N233629PU10L	Laminate	1890	22 ³ / ₁₆	35 ⁷ / ₈	27 ³ / ₄	—	—	90 lbs.	20.4
	17" DEPTH										
	25N233029PU11W	25N233029PU10W	Wood	\$ 2572	22 ³ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	85 lbs.	18.0
	25N233029PU11L	25N233029PU10L	Laminate	1863	22 ³ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	85 lbs.	18.0
	25N173629PU11W	25N173629PU10W	Wood	\$ 2714	16 ¹ / ₁₆	35 ⁷ / ₈	27 ³ / ₄	—	—	119 lbs.	16.3
25N173629PU11L	25N173629PU10L	Laminate	1890	16 ¹ / ₁₆	35 ⁷ / ₈	27 ³ / ₄	—	—	119 lbs.	16.3	
25N173029PU11W	25N173029PU10W	Wood	\$ 2572	16 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	90 lbs.	13.7	
25N173029PU11L	25N173029PU10L	Laminate	1863	16 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	90 lbs.	13.7	

- Specify component worksurfaces and backs to finish as needed
- Locking only on file drawer and lateral file
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
- When specifying Horizon pulls, lateral files will have 2 pulls on each drawer front


TO ORDER, SPECIFY:

1. Model Number
 2. Pull
 3. Pedestal Grommet
 4. Locking
 5. Metal Door or Shelf Color
 6. Foot Color
 7. Laminate Door/Drawer Color
 8. Veneer Chassis Finish/Laminate Chassis Color
- See pages 91-95 for all options available in Epic

SAMPLE MODEL NUMBER:

25N233629PU11L 89PL G22 KRS FR501 MC MC

**OPEN BOOKCASE
UNDERSURFACE
BOX/FILE HEIGHT**



MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS				A	KW	CARTONED WEIGHT	CUBIC FEET
		D	W	H					
23" DEPTH									
25N233622PUOSW Wood	\$ 1344	22	35 ¹ / ₂	21 ¹ / ₂	-	-	90 lbs.	20.4	
25N233622PUOSL Laminate	810	22	35 ¹ / ₂	21 ¹ / ₂	-	-	90 lbs.	20.4	
23" DEPTH									
25N233022PUOSW Wood	\$ 1285	22	29 ¹ / ₂	21 ¹ / ₂	-	-	85 lbs.	18.0	
25N233022PUOSL Laminate	781	22	29 ¹ / ₂	21 ¹ / ₂	-	-	85 lbs.	18.0	
23" DEPTH									
25N232422PUOSW Wood	\$ 1236	22	23 ³ / ₄	21 ¹ / ₂	-	-	80 lbs.	16.0	
25N232422PUOSL Laminate	752	22	23 ³ / ₄	21 ¹ / ₂	-	-	80 lbs.	16.0	
17" DEPTH									
25N173622PUOSW Wood	\$ 1344	16 ¹ / ₂	35 ¹ / ₂	21 ¹ / ₂	-	-	95 lbs.	12.5	
25N173622PUOSL Laminate	810	16 ¹ / ₂	35 ¹ / ₂	21 ¹ / ₂	-	-	95 lbs.	12.5	
17" DEPTH									
25N173022PUOSW Wood	\$ 1285	16 ¹ / ₂	29 ¹ / ₂	21 ¹ / ₂	-	-	97 lbs.	10.8	
25N173022PUOSL Laminate	781	16 ¹ / ₂	29 ¹ / ₂	21 ¹ / ₂	-	-	97 lbs.	10.8	
17" DEPTH									
25N172422PUOSW Wood	\$ 1236	16 ¹ / ₂	23 ³ / ₄	21 ¹ / ₂	-	-	67 lbs.	8.4	
25N172422PUOSL Laminate	752	16 ¹ / ₂	23 ³ / ₄	21 ¹ / ₂	-	-	67 lbs.	8.4	

- Specify component worksurfaces and backs to finish as needed
- Unit features an adjustable shelf

PRODUCT SPECIFICATIONS

- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 214) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended
- Panels shipped with appropriate hardware by specifying modesty type; see page 93 for details
- Modesty and back panels are for use in conjunction with undersurface component worksurfaces to create a finished back or enclosed kneewell
- Sliding doors feature a face mount powder coated aluminum track on top and bottom of cabinet

BASE MODEL KEY

- W Wood Unit
- L Laminate Unit


DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

MODEL NO./DESCRIPTION			LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET	
				D	W	H					
SLIDING DOUBLE DOOR UNDERSURFACE BOX/FILE HEIGHT		GRADE 1	GRADE 2	GRADE 3							
RESIN DOORS 23" DEPTH											
25N233622PUSAW	Wood	\$ 2550	\$ 2752	\$ 2824	22 ³ / ₁₆	35 ⁷ / ₁₆	21 ⁷ / ₁₆	—	—	90 lbs.	20.4
25N233622PUSAL	Laminate	1395	1597	1669	22 ³ / ₁₆	35 ⁷ / ₁₆	21 ⁷ / ₁₆	—	—	90 lbs.	20.4
25N233022PUSAW	Wood	\$ 2442	\$ 2610	\$ 2670	22 ³ / ₁₆	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	85 lbs.	18.0
25N233022PUSAL	Laminate	1316	1484	1544	22 ³ / ₁₆	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	85 lbs.	18.0
25N232422PUSAW	Wood	\$ 2347	\$ 2481	\$ 2529	22 ³ / ₁₆	23 ³ / ₄	21 ⁷ / ₁₆	—	—	80 lbs.	16.0
25N232422PUSAL	Laminate	1237	1371	1419	22 ³ / ₁₆	23 ³ / ₄	21 ⁷ / ₁₆	—	—	80 lbs.	16.0
17" DEPTH											
25N173622PUSAW	Wood	\$ 2550	\$ 2752	\$ 2824	16 ¹ / ₁₆	35 ⁷ / ₁₆	21 ⁷ / ₁₆	—	—	95 lbs.	12.5
25N173622PUSAL	Laminate	1395	1597	1669	16 ¹ / ₁₆	35 ⁷ / ₁₆	21 ⁷ / ₁₆	—	—	95 lbs.	12.5
25N173022PUSAW	Wood	\$ 2442	\$ 2610	\$ 2670	16 ¹ / ₁₆	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	97 lbs.	10.8
25N173022PUSAL	Laminate	1316	1484	1544	16 ¹ / ₁₆	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	97 lbs.	10.8
25N172422PUSAW	Wood	\$ 2347	\$ 2481	\$ 2529	16 ¹ / ₁₆	23 ³ / ₄	21 ⁷ / ₁₆	—	—	67 lbs.	8.4
25N172422PUSAL	Laminate	1237	1371	1419	16 ¹ / ₁₆	23 ³ / ₄	21 ⁷ / ₁₆	—	—	67 lbs.	8.4

- Specify component worksurfaces and backs to finish as needed
- Unit features an adjustable shelf

SLIDING DOUBLE DOOR UNDERSURFACE BOX/FILE HEIGHT




TO ORDER, SPECIFY:

SAMPLE MODEL NUMBERS:

1. Model Number
 2. Pull
 3. Pedestal Grommet
 4. Locking
 5. Metal Shelf Color
 6. Foot Color
 7. Laminate Door/Drawer Color
 8. Veneer Chassis Finish/Laminate Chassis Color
 9. Door Track Paint Color
- See pages 91-95 for all options available in Epic

**SLIDING DOUBLE DOOR
UNDERSURFACE
BOX/FILE HEIGHT**



MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS				CARTONED WEIGHT	CUBIC FEET
		D	W	H	A		
METAL DOORS 23" DEPTH							
25N233622PUSMW Wood	\$ 2550	22 ³ / ₁₆	35 ⁷ / ₈	21 ¹ / ₁₆	—	90 lbs.	20.4
25N233622PUSML Laminate	1395	22 ³ / ₁₆	35 ⁷ / ₈	21 ¹ / ₁₆	—	90 lbs.	20.4
<hr/>							
25N233022PUSMW Wood	\$ 2442	22 ³ / ₁₆	29 ¹ / ₁₆	21 ¹ / ₁₆	—	85 lbs.	18.0
25N233022PUSML Laminate	1316	22 ³ / ₁₆	29 ¹ / ₁₆	21 ¹ / ₁₆	—	85 lbs.	18.0
<hr/>							
25N232422PUSMW Wood	\$ 2347	22 ³ / ₁₆	23 ³ / ₄	21 ¹ / ₁₆	—	80 lbs.	16.0
25N232422PUSML Laminate	1237	22 ³ / ₁₆	23 ³ / ₄	21 ¹ / ₁₆	—	80 lbs.	16.0
<hr/>							
17" DEPTH							
25N173622PUSMW Wood	\$ 2550	16 ¹ / ₁₆	35 ⁷ / ₈	21 ¹ / ₁₆	—	85 lbs.	12.5
25N173622PUSML Laminate	1395	16 ¹ / ₁₆	35 ⁷ / ₈	21 ¹ / ₁₆	—	85 lbs.	12.5
<hr/>							
25N173022PUSMW Wood	\$ 2442	16 ¹ / ₁₆	29 ¹ / ₁₆	21 ¹ / ₁₆	—	80 lbs.	10.8
25N173022PUSML Laminate	1316	16 ¹ / ₁₆	29 ¹ / ₁₆	21 ¹ / ₁₆	—	80 lbs.	10.8
<hr/>							
25N172422PUSMW Wood	\$ 2347	16 ¹ / ₁₆	23 ³ / ₄	21 ¹ / ₁₆	—	75 lbs.	8.4
25N172422PUSML Laminate	1237	16 ¹ / ₁₆	23 ³ / ₄	21 ¹ / ₁₆	—	75 lbs.	8.4

- Specify component worksurfaces and backs to finish as needed
- Unit features an adjustable shelf

PRODUCT SPECIFICATIONS


- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 214) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended
- Panels shipped with appropriate hardware by specifying modesty type; see page 93 for details
- Modesty and back panels are for use in conjunction with undersurface component worksurfaces to create a finished back or enclosed kneewell
- Sliding doors feature a face mount powder coated aluminum track on top and bottom of cabinet


BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

	MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
				D	W	H	A	KW			
STORAGE CABINET METAL SLIDING SHELVES UNDERSURFACE BOX/FILE HEIGHT 	25N233622PUOSSW	Wood	\$ 2528	22	35 $\frac{1}{2}$	21 $\frac{1}{2}$	—	—	90 lbs.	20.4	
	25N233622PUOSSL	Laminate	1702	22	35 $\frac{1}{2}$	21 $\frac{1}{2}$	—	—	90 lbs.	20.4	
	• Weight capacity: 49 pounds per shelf										
	25N233022PUOSSW	Wood	\$ 2484	22	29 $\frac{1}{2}$	21 $\frac{1}{2}$	—	—	85 lbs.	18.0	
	25N233022PUOSSL	Laminate	1672	22	29 $\frac{1}{2}$	21 $\frac{1}{2}$	—	—	85 lbs.	18.0	
	• Weight capacity: 40 pounds per shelf										
	25N232422PUOSSW	Wood	\$ 2439	22	23 $\frac{3}{4}$	21 $\frac{1}{2}$	—	—	80 lbs.	16.0	
	25N232422PUOSSL	Laminate	1642	22	23 $\frac{3}{4}$	21 $\frac{1}{2}$	—	—	80 lbs.	16.0	
	• Weight capacity: 31 pounds per shelf										
	• Specify component worksurfaces and backs to finish as needed										
	• Unit features 3 metal shelves on full extension slides										
	• Shelf sizes are: 18 $\frac{1}{4}$ D x 32 $\frac{1}{2}$ W, 18 $\frac{1}{4}$ D x 26 $\frac{1}{2}$ W, or 18 $\frac{1}{4}$ D x 20 $\frac{1}{2}$ W of storage space and a non skid surface										

	MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
				D	W	H	A	KW			
BOX/LATERAL FILE UNDERSURFACE BOX/FILE HEIGHT 	23" DEPTH										
	25N233622PUBBLW	Wood	\$ 1814	22 $\frac{1}{2}$	35 $\frac{1}{2}$	21 $\frac{1}{2}$	—	—	90 lbs.	20.4	
	25N233622PUBBLL	Laminate	981	22 $\frac{1}{2}$	35 $\frac{1}{2}$	21 $\frac{1}{2}$	—	—	90 lbs.	20.4	
	• Weight capacity: 49 pounds per shelf										
	25N233022PUBBLW	Wood	\$ 1669	22 $\frac{1}{2}$	29 $\frac{1}{2}$	21 $\frac{1}{2}$	—	—	85 lbs.	18.0	
	25N233022PUBBLL	Laminate	953	22 $\frac{1}{2}$	29 $\frac{1}{2}$	21 $\frac{1}{2}$	—	—	85 lbs.	18.0	
	• Weight capacity: 40 pounds per shelf										
	17" DEPTH										
	25N173622PUBBLW	Wood	\$ 1814	16 $\frac{1}{2}$	35 $\frac{1}{2}$	21 $\frac{1}{2}$	—	—	95 lbs.	12.5	
	25N173622PUBBLL	Laminate	981	16 $\frac{1}{2}$	35 $\frac{1}{2}$	21 $\frac{1}{2}$	—	—	95 lbs.	12.5	
	• Weight capacity: 49 pounds per shelf										
	25N173022PUBBLW	Wood	\$ 1669	16 $\frac{1}{2}$	29 $\frac{1}{2}$	21 $\frac{1}{2}$	—	—	67 lbs.	11.2	
25N173022PUBBLL	Laminate	953	16 $\frac{1}{2}$	29 $\frac{1}{2}$	21 $\frac{1}{2}$	—	—	67 lbs.	11.2		
• Specify component worksurfaces and backs to finish as needed											
• Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available											
• When specifying Horizon pulls, lateral files will have 2 pulls on each drawer front											

TO ORDER, SPECIFY:


1. Model Number
2. Pull
3. Pedestal Grommet
4. Locking
5. Metal Shelf Color
6. Foot Color
7. Laminate Door/Drawer Color
8. Veneer Chassis Finish/Laminate Chassis Color
9. Door Track Paint Color

SAMPLE MODEL NUMBERS:

25N233622PUBLL 89PL G22 KS1S FR501 MC MC
 25N233622PUOSSL G22 501 FR501 478

• See pages 91-95 for all options available in Epic

**BOX/FILE
 UNDERSURFACE
 BOX/FILE HEIGHT**



MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS				A	KW	CARTONED WEIGHT	CUBIC FEET
			D	W	H					
23" DEPTH										
25N231822PUBFW	Wood	\$ 1415	22 ³ / ₁₆	17 ¹ / ₁₆	21 ⁷ / ₁₆	-	-	70 lbs.	10.0	
25N231822PUBFL	Laminate	868	22 ³ / ₁₆	17 ¹ / ₁₆	21 ⁷ / ₁₆	-	-	70 lbs.	10.0	
25N231522PUBFW										
25N231522PUBFW	Wood	\$ 1334	22 ³ / ₁₆	14 ¹ / ₁₆	21 ⁷ / ₁₆	-	-	65 lbs.	8.0	
25N231522PUBFL	Laminate	812	22 ³ / ₁₆	14 ¹ / ₁₆	21 ⁷ / ₁₆	-	-	65 lbs.	8.0	
17" DEPTH										
25N171822PUBFW	Wood	\$ 1415	16 ¹ / ₁₆	17 ¹ / ₁₆	21 ⁷ / ₁₆	-	-	65 lbs.	7.3	
25N171822PUBFL	Laminate	868	16 ¹ / ₁₆	17 ¹ / ₁₆	21 ⁷ / ₁₆	-	-	65 lbs.	7.3	
25N171522PUBFW										
25N171522PUBFW	Wood	\$ 1334	16 ¹ / ₁₆	14 ¹ / ₁₆	21 ⁷ / ₁₆	-	-	60 lbs.	6.5	
25N171522PUBFL	Laminate	812	16 ¹ / ₁₆	14 ¹ / ₁₆	21 ⁷ / ₁₆	-	-	60 lbs.	6.5	

- Specify component worksurfaces and backs to finish as needed
- Not intended to be used as a hanging pedestal
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
- Not intended for use in a freestanding application

PRODUCT SPECIFICATIONS

- Panels shipped with appropriate hardware by specifying modesty type; see page 93 for details
- Modesty and back panels are for use in conjunction with undersurface component worksurfaces to create a finished back or enclosed kneewell


BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang; Approach Side
- KW Kneespace Width

MODESTY PANEL WORKSURFACE HEIGHT



MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
		D	W	H	A	KW		
25N9625MPW Wood	\$ 693	¾	95%	25%	–	–	57 lbs.	3.0
25N9625MPL Laminate	366	¾	95%	25%	–	–	57 lbs.	3.0
25N9025MPW Wood	\$ 654	¾	89%	25%	–	–	54 lbs.	3.0
25N9025MPL Laminate	347	¾	89%	25%	–	–	54 lbs.	3.0
25N8425MPW Wood	\$ 617	¾	83%	25%	–	–	51 lbs.	3.0
25N8425MPL Laminate	327	¾	83%	25%	–	–	51 lbs.	3.0
25N7825MPW Wood	\$ 583	¾	77%	25%	–	–	48 lbs.	2.8
25N7825MPL Laminate	309	¾	77%	25%	–	–	48 lbs.	2.8
25N7225MPW Wood	\$ 549	¾	71%	25%	–	–	45 lbs.	2.8
25N7225MPL Laminate	290	¾	71%	25%	–	–	45 lbs.	2.8
25N6625MPW Wood	\$ 520	¾	65 ¹ / ₁₆	25%	–	–	42 lbs.	2.7
25N6625MPL Laminate	277	¾	65 ¹ / ₁₆	25%	–	–	42 lbs.	2.7
25N6025MPW Wood	\$ 489	¾	59 ¹ / ₁₆	25%	–	–	39 lbs.	2.7
25N6025MPL Laminate	255	¾	59 ¹ / ₁₆	25%	–	–	39 lbs.	2.7
25N5425MPW Wood	\$ 463	¾	53 ¹ / ₁₆	25%	–	–	36 lbs.	2.6
25N5425MPL Laminate	243	¾	53 ¹ / ₁₆	25%	–	–	36 lbs.	2.6
25N4825MPW Wood	\$ 427	¾	47 ³ / ₄	25%	–	–	33 lbs.	2.5
25N4825MPL Laminate	224	¾	47 ³ / ₄	25%	–	–	33 lbs.	2.5
25N4225MPW Wood	\$ 413	¾	41 ³ / ₄	25%	–	–	31 lbs.	2.5
25N4225MPL Laminate	199	¾	41 ³ / ₄	25%	–	–	31 lbs.	2.5
25N3625MPW Wood	\$ 395	¾	35 ³ / ₄	25%	–	–	28 lbs.	2.4
25N3625MPL Laminate	178	¾	35 ³ / ₄	25%	–	–	28 lbs.	2.4

- Modified widths are available on modesty panels in 1/16" increments; when ordering a modified width, specify the modesty panel 3/16" narrower than the corresponding worksurface
- Wood modesty panels have vertical grain
- Laminate modesty panels have horizontal grain

TO ORDER, SPECIFY:

1. Model Number
2. Modesty Type
3. Modesty Grommet
4. Modified Width
5. Veneer Finish/Laminate Color


SAMPLE MODEL NUMBER:

25N9625MPW M G21 X CW

• See pages 91-95 for all options available in Epic

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS				CARTONED WEIGHT	CUBIC FEET
		D	W	H	A		
25N3025MPW Wood	\$ 363	¾"	29¾"	25¾"	—	—	25 lbs. 2.3
25N3025MPL Laminate	157	¾"	29¾"	25¾"	—	—	25 lbs. 2.3
25N2425MPW Wood	\$ 356	¾"	23¾"	25¾"	—	—	22 lbs. 2.3
25N2425MPL Laminate	147	¾"	23¾"	25¾"	—	—	22 lbs. 2.3
25N1825MPW Wood	\$ 348	¾"	17 ¹³ / ₁₆ "	25¾"	—	—	19 lbs. 2.2
25N1825MPL Laminate	134	¾"	17 ¹³ / ₁₆ "	25¾"	—	—	19 lbs. 2.2
25N1525MPW Wood	\$ 342	¾"	14 ¹³ / ₁₆ "	25¾"	—	—	17 lbs. 2.2
25N1525MPL Laminate	116	¾"	14 ¹³ / ₁₆ "	25¾"	—	—	17 lbs. 2.2


MODESTY PANEL WORKSURFACE HEIGHT (CONTINUED)



- Except for models 1825 and 1525, modified widths are available on modesty panels in 1/16" increments; when ordering a modified width, specify the modesty panel 1/16" narrower than the corresponding worksurface
- Wood modesty panels have vertical grain
- Laminate modesty panels have horizontal grain

25N6025MPVL Laminate	\$ 255	¾"	59 ¹¹ / ₁₆ "	25¾"	—	—	39 lbs. 2.7
25N5425MPVL Laminate	243	¾"	53 ¹¹ / ₁₆ "	25¾"	—	—	36 lbs. 2.6
25N4825MPVL Laminate	224	¾"	47¾"	25¾"	—	—	33 lbs. 2.5
25N4225MPVL Laminate	199	¾"	41¾"	25¾"	—	—	31 lbs. 2.5
25N3625MPVL Laminate	178	¾"	35¾"	25¾"	—	—	28 lbs. 2.4
25N3025MPVL Laminate	157	¾"	29¾"	25¾"	—	—	25 lbs. 2.3
25N2425MPVL Laminate	147	¾"	23¾"	25¾"	—	—	22 lbs. 2.3
25N1825MPVL Laminate	134	¾"	17 ¹³ / ₁₆ "	25¾"	—	—	19 lbs. 2.2
25N1525MPVL Laminate	116	¾"	14 ¹³ / ₁₆ "	25¾"	—	—	17 lbs. 2.2

MODESTY PANEL WORKSURFACE HEIGHT



- Except for models 1825 and 1525, modified widths are available on modesty panels in 1/16" increments; when ordering a modified width, specify the modesty panel 1/16" narrower than the corresponding worksurface
- Grain direction runs vertically

PRODUCT SPECIFICATIONS

- Panels shipped with appropriate hardware by specifying modesty type; see page 93 for details
- Modesty and back panels are for use in conjunction with undersurface component worksurfaces to create a finished back or enclosed kneewell


BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width


**MODESTY PANEL
WORKSURFACE HEIGHT**



MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
			D	W	H	A	KW		
KNIFE RIM RETURN MODESTY									
25N7425MPW	Wood	\$ 549	¾	73¾"	25¾"	—	—	46 lbs.	2.8
25N7425MPL	Laminate	290	¾	73¾"	25¾"	—	—	46 lbs.	2.8
<hr/>									
25N6825MPW	Wood	\$ 520	¾	67¾"	25¾"	—	—	43 lbs.	2.7
25N6825MPL	Laminate	277	¾	67¾"	25¾"	—	—	43 lbs.	2.7
<hr/>									
25N6225MPW	Wood	\$ 489	¾	61¾"	25¾"	—	—	40 lbs.	2.7
25N6225MPL	Laminate	255	¾	61¾"	25¾"	—	—	40 lbs.	2.7
<hr/>									
25N5625MPW	Wood	\$ 463	¾	55¾"	25¾"	—	—	37 lbs.	2.6
25N5625MPL	Laminate	243	¾	55¾"	25¾"	—	—	37 lbs.	2.6
<hr/>									
25N5025MPW	Wood	\$ 427	¾	49¾"	25¾"	—	—	34 lbs.	2.5
25N5025MPL	Laminate	224	¾	49¾"	25¾"	—	—	34 lbs.	2.5
<hr/>									
25N4425MPW	Wood	\$ 413	¾	43¾"	25¾"	—	—	31 lbs.	2.5
25N4425MPL	Laminate	199	¾	43¾"	25¾"	—	—	31 lbs.	2.5

- For use when creating a return using component knife rim surfaces
- Wood modesty panels have vertical grain
- Laminate modesty panels have horizontal grain

**MODESTY PANEL
WORKSURFACE HEIGHT**



KNIFE RIM RETURN MODESTY									
25N5625MPVL	Laminate	\$ 243	¾	55¾"	25¾"	—	—	37 lbs.	2.6
25N5025MPVL	Laminate	224	¾	49¾"	25¾"	—	—	34 lbs.	2.5
25N4425MPVL	Laminate	199	¾	43¾"	25¾"	—	—	31 lbs.	2.5


- For use when creating a return using component knife rim surfaces
- Grain direction runs vertically

TO ORDER, SPECIFY:

1. Model Number
2. Modesty Type
3. Modesty Grommet
4. Modified Width
5. Veneer Finish/Laminate Color

• See pages 91-95 for all options available in Epic


**MODESTY PANEL
WORKSURFACE HEIGHT**



MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
			D	W	H	A	KW		
KNIFE RIM BRIDGE MODESTY									
25N7525MPW	Wood	\$ 549	¾	74 ¹ / ₁₆	25 ³ / ₈	—	—	47 lbs.	2.8
25N7525MPL	Laminate	290	¾	74 ¹ / ₁₆	25 ³ / ₈	—	—	47 lbs.	2.8
<hr/>									
25N6925MPW	Wood	\$ 520	¾	69	25 ³ / ₈	—	—	45 lbs.	2.8
25N6925MPL	Laminate	277	¾	69	25 ³ / ₈	—	—	45 lbs.	2.8
<hr/>									
25N6325MPW	Wood	\$ 489	¾	63	25 ³ / ₈	—	—	42 lbs.	2.7
25N6325MPL	Laminate	255	¾	63	25 ³ / ₈	—	—	42 lbs.	2.7
<hr/>									
25N5725MPW	Wood	\$ 463	¾	57	25 ³ / ₈	—	—	39 lbs.	2.6
25N5725MPL	Laminate	243	¾	57	25 ³ / ₈	—	—	39 lbs.	2.6
<hr/>									
25N5125MPW	Wood	\$ 427	¾	51	25 ³ / ₈	—	—	36 lbs.	2.6
25N5125MPL	Laminate	224	¾	51	25 ³ / ₈	—	—	36 lbs.	2.6
<hr/>									
25N4525MPW	Wood	\$ 413	¾	45	25 ³ / ₈	—	—	33 lbs.	2.5
25N4525MPL	Laminate	199	¾	45	25 ³ / ₈	—	—	33 lbs.	2.5

- For use when creating a bridge using component knife rim surfaces
- Wood modesty panels have vertical grain
- Laminate modesty panels have horizontal grain

**MODESTY PANEL
WORKSURFACE HEIGHT**



KNIFE RIM BRIDGE MODESTY									
25N5725MPVL	Laminate	\$ 243	¾	58 ³ / ₁₆	25 ³ / ₈	—	—	39 lbs.	2.6
25N5125MPVL	Laminate	224	¾	52 ¹ / ₄	25 ³ / ₈	—	—	36 lbs.	2.6
25N4525MPVL	Laminate	199	¾	46 ¹ / ₄	25 ³ / ₈	—	—	33 lbs.	2.5

- For use when creating a bridge using component knife rim surfaces
- Grain direction runs vertically

PRODUCT SPECIFICATIONS

- Panels shipped with appropriate hardware by specifying modesty type; see page 93 for details
- Modesty and back panels are for use in conjunction with undersurface component worksurfaces to create a finished back or enclosed kneewell


BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

**MODESTY PANEL
BOX/FILE HEIGHT**



MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
		D	W	H	A	KW		
25N9620MPW Wood	\$ 569	¾	95%	18%	–	–	45 lbs.	2.8
25N9620MPL Laminate	305	¾	95%	18%	–	–	45 lbs.	2.8
25N9020MPW Wood	\$ 531	¾	89%	18%	–	–	43 lbs.	2.7
25N9020MPL Laminate	285	¾	89%	18%	–	–	43 lbs.	2.7
25N8420MPW Wood	\$ 493	¾	83%	18%	–	–	41 lbs.	2.7
25N8420MPL Laminate	264	¾	83%	18%	–	–	41 lbs.	2.7
25N7820MPW Wood	\$ 460	¾	77%	18%	–	–	39 lbs.	2.6
25N7820MPL Laminate	245	¾	77%	18%	–	–	39 lbs.	2.6
25N7220MPW Wood	\$ 425	¾	71%	18%	–	–	36 lbs.	2.6
25N7220MPL Laminate	228	¾	71%	18%	–	–	36 lbs.	2.6
25N6620MPW Wood	\$ 395	¾	65 ¹ / ₁₆	18%	–	–	34 lbs.	2.5
25N6620MPL Laminate	213	¾	65 ¹ / ₁₆	18%	–	–	34 lbs.	2.5
25N6020MPW Wood	\$ 364	¾	59 ¹ / ₁₆	18%	–	–	32 lbs.	2.5
25N6020MPL Laminate	191	¾	59 ¹ / ₁₆	18%	–	–	32 lbs.	2.5
25N5420MPW Wood	\$ 340	¾	53 ¹ / ₁₆	18%	–	–	30 lbs.	2.4
25N5420MPL Laminate	187	¾	53 ¹ / ₁₆	18%	–	–	30 lbs.	2.4
25N4820MPW Wood	\$ 305	¾	47 ³ / ₄	18%	–	–	28 lbs.	2.4
25N4820MPL Laminate	180	¾	47 ³ / ₄	18%	–	–	28 lbs.	2.4
25N4220MPW Wood	\$ 287	¾	41 ³ / ₄	18%	–	–	25 lbs.	2.3
25N4220MPL Laminate	167	¾	41 ³ / ₄	18%	–	–	25 lbs.	2.3
25N3620MPW Wood	\$ 271	¾	35 ³ / ₄	18%	–	–	23 lbs.	2.3
25N3620MPL Laminate	147	¾	35 ³ / ₄	18%	–	–	23 lbs.	2.3

- Modified widths are available on modesty panels in 1/16" increments; when ordering a modified width, specify the modesty panel 3/16" narrower than the corresponding worksurface
- Do not specify modesty type
- Wood modesty panels have vertical grain
- Laminate modesty panels have horizontal grain

TO ORDER, SPECIFY:

1. Model Number
2. Modesty Type
3. Modesty Grommet
4. Modified Width
5. Veneer Finish/Laminate Color


SAMPLE MODEL NUMBER:

25N9620MPL M G21 94.5 MC

• See pages 91-95 for all options available in Epic

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS				CARTONED WEIGHT	CUBIC FEET
		D	W	H	A		
25N3020MPW Wood	\$ 238	¾"	29¾"	18"	—	—	21 lbs. 2.2
25N3020MPL Laminate	128	¾"	29¾"	18"	—	—	21 lbs. 2.2
25N2420MPW Wood	\$ 224	¾"	23¾"	18"	—	—	19 lbs. 2.1
25N2420MPL Laminate	104	¾"	23¾"	18"	—	—	19 lbs. 2.1
25N1820MPW Wood	\$ 206	¾"	17 ¹³ / ₁₆ "	18"	—	—	17 lbs. 2.1
25N1820MPL Laminate	76	¾"	17 ¹³ / ₁₆ "	18"	—	—	17 lbs. 2.1
25N1520MPW Wood	\$ 175	¾"	14 ¹³ / ₁₆ "	18"	—	—	15 lbs. 2.1
25N1520MPL Laminate	58	¾"	14 ¹³ / ₁₆ "	18"	—	—	15 lbs. 2.1


MODESTY PANEL BOX/FILE HEIGHT (CONTINUED)



- Except for models 1820 and 1520, modified widths are available on modesty panels in 1/16" increments; when ordering a modified width, specify the modesty panel 1/16" narrower than the corresponding worksurface
- Wood modesty panels have vertical grain
- Laminate modesty panels have horizontal grain

25N6020MPVL Laminate	\$ 191	¾"	59 ¹¹ / ₁₆ "	18"	—	—	32 lbs. 2.5
25N5420MPVL Laminate	187	¾"	53 ¹¹ / ₁₆ "	18"	—	—	30 lbs. 2.4
25N4820MPVL Laminate	180	¾"	47¾"	18"	—	—	28 lbs. 2.4
25N4220MPVL Laminate	167	¾"	41¾"	18"	—	—	25 lbs. 2.3
25N3620MPVL Laminate	147	¾"	35¾"	18"	—	—	23 lbs. 2.3
25N3020MPVL Laminate	128	¾"	29¾"	18"	—	—	21 lbs. 2.2
25N2420MPVL Laminate	104	¾"	23¾"	18"	—	—	19 lbs. 2.1
25N1820MPVL Laminate	76	¾"	17 ¹³ / ₁₆ "	18"	—	—	17 lbs. 2.1
25N1520MPVL Laminate	58	¾"	14 ¹³ / ₁₆ "	18"	—	—	15 lbs. 2.1

MODESTY PANEL BOX/FILE HEIGHT



- Except for models 1820 and 1520, modified widths are available on modesty panels in 1/16" increments; when ordering a modified width, specify the modesty panel 1/16" narrower than the corresponding worksurface
- Grain direction runs vertically

PRODUCT SPECIFICATIONS


- Panels shipped with appropriate hardware by specifying modesty type; see page 277 for details
- Modesty and back panels are for use in conjunction with undersurface component worksurfaces to create a finished back or enclosed kneewell

BASE MODEL KEY

- W Wood Unit
- L Laminate Unit


DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang; Approach Side
- KW Kneespace Width

	MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
				D	W	H	A	KW		
MODESTY PANEL FULL OVERLAY FOR STORAGE CREDENZAS (WORKSURFACE HEIGHT) 	25N96A25MPL	Laminate	\$ 366	¾	95¾	25¾	—	—	65 lbs.	11.8
	25N90A25MPL	Laminate	347	¾	89¾	25¾	—	—	62 lbs.	11.1
	25N84A25MPL	Laminate	327	¾	83¾	25¾	—	—	58 lbs.	10.4
	25N78A25MPL	Laminate	309	¾	77¾	25¾	—	—	51 lbs.	7.2
	25N72A25MPL	Laminate	290	¾	71¾	25¾	—	—	44 lbs.	3.9
	25N66A25MPL	Laminate	277	¾	65¾	25¾	—	—	41 lbs.	3.6
	25N60A25MPL	Laminate	255	¾	59¾	25¾	—	—	38 lbs.	3.3

- Modified widths are available on modesty panels in ¼" increments; when ordering a modified width, specify the modesty panel ¼" narrower than the corresponding worksurface
- Wood modesty panels have vertical grain
- Laminate modesty panels have horizontal grain

MODESTY PANEL FULL OVERLAY FOR STORAGE CREDENZAS (WORKSURFACE HEIGHT)



	25N60A25MPVL	Laminate	\$ 255	¾	59¾	25¾	—	—	38 lbs.	3.3
--	--------------	----------	--------	---	-----	-----	---	---	---------	-----


- Modified widths are available on modesty panels in ¼" increments; when ordering a modified width, specify the modesty panel ¼" narrower than the corresponding worksurface
- Grain direction runs vertically

TO ORDER, SPECIFY:

1. Model Number
2. Modesty Type
3. Modesty Grommet
4. Modified Width
5. Veneer Chassis Finish/Laminate Chassis Color


• See pages 275-279 for all options available in WaveWorks

SAMPLE MODEL NUMBER:

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
			D	W	H	A	KW		
MODESTY PANEL FULL OVERLAY FOR STORAGE CREDENZAS BOX/FILE HEIGHT 	25N96A20MPL Laminate	\$ 305	¾	95¾	19½	–	–	60 lbs.	4.1
	25N90A20MPL Laminate	285	¾	89¾	19½	–	–	57 lbs.	4.0
	25N84A20MPL Laminate	264	¾	83¾	19½	–	–	53 lbs.	3.9
	25N78A20MPL Laminate	245	¾	77¾	19½	–	–	46 lbs.	3.8
	Q25N72A20MPL Laminate	228	¾	71¾	19½	–	–	39 lbs.	3.7
	25N72A20MPL Laminate	228	¾	71¾	19½	–	–	39 lbs.	3.7
	25N66A20MPL Laminate	213	¾	65¾	19½	–	–	36 lbs.	3.4
	Q25N60A20MPL Laminate	191	¾	59¾	19½	–	–	33 lbs.	3.1
	25N60A20MPL Laminate	191	¾	59¾	19½	–	–	33 lbs.	3.1

- Full Overlay Modesty to be used on box/file height storage and when layering surfaces
- Modified widths are available on modesty panels in ¼" increments; when ordering a modified width, specify the modesty panel ¼" narrower than the corresponding worksurface
- Wood modesty panels have vertical grain
- Laminate modesty panels have horizontal grain

MODESTY PANEL FULL OVERLAY FOR STORAGE CREDENZAS BOX/FILE HEIGHT



25N60A20MPVL Laminate	\$ 191	¾	59¾	19½	–	–	33 lbs.	3.1
-----------------------	--------	---	-----	-----	---	---	---------	-----

- Full Overlay Modesty to be used on box/file height storage and when layering surfaces
- Modified widths are available on modesty panels in ¼" increments; when ordering a modified width, specify the modesty panel ¼" narrower than the corresponding worksurface
- Grain direction runs vertically

EPIC

PRODUCT SPECIFICATIONS

- End panels, filler panels and support panels shipped with appropriate hardware


BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width


END PANEL (WORKSURFACE HEIGHT)



MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
			D	W	H	A	KW		
25N3528EPW	Wood	\$ 528	35 ¹ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	–	–	35 lbs.	1.9
25N3528EPL	Laminate	318	35 ¹ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	–	–	35 lbs.	1.9
25N2928EPW	Wood	\$ 477	29 ¹ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	–	–	30 lbs.	1.3
25N2928EPL	Laminate	272	29 ¹ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	–	–	30 lbs.	1.3
25N2328EPW	Wood	\$ 463	22 ¹ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	–	–	25 lbs.	1.1
25N2328EPL	Laminate	249	22 ¹ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	–	–	25 lbs.	1.1
25N1728EPW	Wood	\$ 434	17 ¹ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	–	–	18 lbs.	1.1
25N1728EPL	Laminate	231	17 ¹ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	–	–	18 lbs.	1.1

- End panels are required when pedestals are not used to support the end of a unit or workstation
- End panels are 1" shallower than worksurfaces to accommodate a modesty panel or filler strip
- Modified depth available on 35", 29", and 23" models only
- Modesty panels are recommended when building a shell unit

END PANEL (BOX/FILE HEIGHT)



25N2321EPW	Wood	\$ 447	22 ¹ / ₁₆	1 ³ / ₁₆	21 ⁷ / ₁₆	–	–	25 lbs.	1.1
25N2321EPL	Laminate	231	22 ¹ / ₁₆	1 ³ / ₁₆	21 ⁷ / ₁₆	–	–	25 lbs.	1.1
25N1721EPW	Wood	\$ 418	17 ¹ / ₁₆	1 ³ / ₁₆	21 ⁷ / ₁₆	–	–	15 lbs.	1.0
25N1721EPL	Laminate	217	17 ¹ / ₁₆	1 ³ / ₁₆	21 ⁷ / ₁₆	–	–	15 lbs.	1.0

- End panels are required when pedestals are not used to support the end of a unit or workstation
- End panels are 1" shallower than worksurfaces to accommodate a modesty panel or filler strip
- Modified depth available on 23" models only
- Modesty panels are recommended when building a shell unit

TO ORDER, SPECIFY:


1. Model Number
2. Modesty/End Panel Grommet
3. Modified Depth
4. Modified Width
5. Veneer Finish/Laminate Color

SAMPLE MODEL NUMBERS:

25N3020MPW G21 X TF
 25N3528EPL GE1L X 425


• See pages 91-95 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET
			D	W	H				
SUPPORT PANEL (WORKSURFACE HEIGHT)	25N1228SSW Wood	\$ 320	11 ⁷ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	—	—	15 lbs.	0.8
	25N1228SSL Laminate	116	11 ⁷ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	—	—	15 lbs.	0.8




- For use as added support
- Specify wood or laminate only

SUPPORT PANEL (BOX/FILE HEIGHT)	25N1221SSW Wood	\$ 306	11 ⁷ / ₁₆	1 ³ / ₁₆	21 ¹ / ₁₆	—	—	16 lbs.	0.8
	25N1221SSL Laminate	101	11 ⁷ / ₁₆	1 ³ / ₁₆	21 ¹ / ₁₆	—	—	16 lbs.	0.8




- For use as added support
- Specify wood or laminate only

SUPPORT PANEL U-STYLE	NAC1228UBC Concrete	\$ 383	1 ¹ / ₂	12	28	—	—	12 lbs.	3.1
	NAC1228UBB Cinder	383	1 ¹ / ₂	12	28	—	—	12 lbs.	3.1
	NAC1228UBI Iron	383	1 ¹ / ₂	12	28	—	—	12 lbs.	3.1
	NAC1228UBS Platinum Metallic	383	1 ¹ / ₂	12	28	—	—	12 lbs.	3.1
	NAC1228UBN Satin Nickel Metallic	383	1 ¹ / ₂	12	28	—	—	12 lbs.	3.1
	NAC1228UBH Designer White	383	1 ¹ / ₂	12	28	—	—	12 lbs.	3.1



- For use as added support
- Adjustable glides are standard
- Specify model number only
- Metal mounting plate attached to support panel

UNDERSURFACE SUPPORT RAIL (WORKSURFACE)	NAC0248SUR	\$ 185	2 ³ / ₄	48	1	—	—	5 lbs.	0.5
	QNAC0236SUR	158	2 ³ / ₄	36	1	—	—	3 lbs.	0.3
	NAC0236SUR	158	2 ³ / ₄	36	1	—	—	3 lbs.	0.3



- Specify model number only
- Model recommended for use when the weight on the table has a uniform weight above 125 lbs. or if the span between table legs or support structures is greater than 48" on a 1³/₁₆" worksurface and greater than 60" on a 1¹/₁₆" worksurface
- Specify the 36" model to be used up to 66" worksurfaces
- Specify the 48" model to be used up to 72" worksurfaces
- Specify with worksurfaces when overlapping box/file height storage, sit on box/file height storage and supports worksurface height worksurfaces

PRODUCT SPECIFICATIONS

- End panels, filler panels and support panels shipped with appropriate hardware


BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

**T-SUPPORT PANEL
(WORKSURFACE HEIGHT)**



MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
			D	W	H	A	KW		
25N4228STW	Wood	\$ 879	41 $\frac{1}{8}$	1 $\frac{3}{8}$	27 $\frac{3}{4}$	–	–	49 lbs.	3.4
25N4228STL	Laminate	469	41 $\frac{1}{8}$	1 $\frac{3}{8}$	27 $\frac{3}{4}$	–	–	49 lbs.	3.4
25N3628STW	Wood	\$ 834	35 $\frac{7}{8}$	1 $\frac{3}{8}$	27 $\frac{3}{4}$	–	–	43 lbs.	2.9
25N3628STL	Laminate	425	35 $\frac{7}{8}$	1 $\frac{3}{8}$	27 $\frac{3}{4}$	–	–	43 lbs.	2.9
25N3028STW	Wood	\$ 788	29 $\frac{9}{16}$	1 $\frac{3}{8}$	27 $\frac{3}{4}$	–	–	38 lbs.	2.5
25N3028STL	Laminate	379	29 $\frac{9}{16}$	1 $\frac{3}{8}$	27 $\frac{3}{4}$	–	–	38 lbs.	2.5
25N2428STW	Wood	\$ 769	22 $\frac{5}{8}$	1 $\frac{3}{8}$	27 $\frac{3}{4}$	–	–	32 lbs.	2.1
25N2428STL	Laminate	352	22 $\frac{5}{8}$	1 $\frac{3}{8}$	27 $\frac{3}{4}$	–	–	32 lbs.	2.1
25N1828STW	Wood	\$ 719	17 $\frac{1}{8}$	1 $\frac{3}{8}$	27 $\frac{3}{4}$	–	–	28 lbs.	1.4
25N1828STL	Laminate	329	17 $\frac{1}{8}$	1 $\frac{3}{8}$	27 $\frac{3}{4}$	–	–	28 lbs.	1.4

- Some assembly required
- Specify with U-surfaces, extended U-surfaces, P-surfaces, extended P-surfaces, and J-surfaces

TO ORDER, SPECIFY:


1. Model Number
2. Grommet
3. Veneer Finish/Laminate Color

• See pages 91-95 for all options available in Epic

SAMPLE MODEL NUMBER:

25N4228STL GE1R 480

**T-SUPPORT PANEL
(BOX/FILE HEIGHT)**




(Not for use with modesty panel)

MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET
			D	W	H				
25N3606STW	Wood	\$ 417	35 ⁵ / ₈	1 ³ / ₈	4 ⁷ / ₈	–	–	21 lbs.	2.0
25N3606STL	Laminate	212	35 ⁵ / ₈	1 ³ / ₈	4 ⁷ / ₈	–	–	21 lbs.	2.0
25N3006STW	Wood	\$ 395	29 ⁹ / ₁₆	1 ³ / ₈	4 ⁷ / ₈	–	–	19 lbs.	1.8
25N3006STL	Laminate	189	29 ⁹ / ₁₆	1 ³ / ₈	4 ⁷ / ₈	–	–	19 lbs.	1.8
25N2406STW	Wood	\$ 385	22 ¹ / ₂	1 ³ / ₈	4 ⁷ / ₈	–	–	16 lbs.	1.6
25N2406STL	Laminate	177	22 ¹ / ₂	1 ³ / ₈	4 ⁷ / ₈	–	–	16 lbs.	1.6
25N1806STW	Wood	\$ 360	17 ⁷ / ₁₆	1 ³ / ₈	4 ⁷ / ₈	–	–	12 lbs.	1.1
25N1806STL	Laminate	163	17 ⁷ / ₁₆	1 ³ / ₈	4 ⁷ / ₈	–	–	12 lbs.	1.1

- Some assembly required
- Specify with worksurfaces when overlapping box/file height storage, sits on box/file height storage and supports overlapping worksurfaces
- 36, 30, 24, and 18 models not to be used with modesty panels

**T-SUPPORT PANEL
(BOX/FILE HEIGHT)**



(For use with modesty panel)

25N3506STW	Wood	\$ 396	35 ⁵ / ₈	1 ³ / ₈	4 ⁷ / ₈	–	–	21 lbs.	2.0
25N3506STL	Laminate	201	35 ⁵ / ₈	1 ³ / ₈	4 ⁷ / ₈	–	–	21 lbs.	2.0
25N2906STW	Wood	\$ 375	29 ⁹ / ₁₆	1 ³ / ₈	4 ⁷ / ₈	–	–	19 lbs.	1.8
25N2906STL	Laminate	180	29 ⁹ / ₁₆	1 ³ / ₈	4 ⁷ / ₈	–	–	19 lbs.	1.8
25N2306STW	Wood	\$ 365	22 ¹ / ₂	1 ³ / ₈	4 ⁷ / ₈	–	–	16 lbs.	1.6
25N2306STL	Laminate	167	22 ¹ / ₂	1 ³ / ₈	4 ⁷ / ₈	–	–	16 lbs.	1.6
25N1706STW	Wood	\$ 342	17 ⁷ / ₁₆	1 ³ / ₈	4 ⁷ / ₈	–	–	12 lbs.	1.1
25N1706STL	Laminate	156	17 ⁷ / ₁₆	1 ³ / ₈	4 ⁷ / ₈	–	–	12 lbs.	1.1

- Some assembly required
- Specify with worksurfaces when overlapping box/file height storage, sits on box/file height storage and supports overlapping worksurfaces
- 35, 29, 23, and 17 models are 1" shallower than worksurface to accommodate a modesty panel

PRODUCT SPECIFICATIONS

- End panels, filler panels and support panels shipped with appropriate hardware


BASE MODEL KEY

- W Wood Unit
- L Laminate Unit

DIMENSION KEY

- D Depth
- W Width
- H Height
- A Overhang: Approach Side
- KW Kneespace Width

CORNER SUPPORT PRIVACY PANEL




25N3039SLLW
Left shown

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
		D	W	H	A	KW		
LEFT HANDED								
RIGHT HANDED								
25N3039SLLW	\$ 1099	31 ³ / ₁₆	31 ¹ / ₄	39 ¹ / ₁₆	-	-	60 lbs.	2.8
25N3039SLLL	629	31 ³ / ₁₆	31 ¹ / ₄	39 ¹ / ₁₆	-	-	60 lbs.	2.8
25N2439SLLW	\$ 1067	25 ³ / ₁₆	25 ¹ / ₄	39 ¹ / ₁₆	-	-	60 lbs.	2.8
25N2439SLLL	573	25 ³ / ₁₆	25 ¹ / ₄	39 ¹ / ₁₆	-	-	60 lbs.	2.8
25N3239SLLW	\$ 1099	32 ³ / ₁₆	31 ¹ / ₄	39 ¹ / ₁₆	-	-	60 lbs.	2.8
25N3239SLLL	629	32 ³ / ₁₆	31 ¹ / ₄	39 ¹ / ₁₆	-	-	60 lbs.	2.8
25N2639SLLW	\$ 1067	26 ³ / ₁₆	25 ¹ / ₄	39 ¹ / ₁₆	-	-	60 lbs.	2.8
25N2639SLLL	573	26 ³ / ₁₆	25 ¹ / ₄	39 ¹ / ₁₆	-	-	60 lbs.	2.8

- Some assembly required
- 32" and 26" models are to be used with K1 worksurfaces
- 30" and 24" models are to be used with 30" and 24" deep worksurfaces
- Corner supports can be used in place of undersurface support or support panels


FILLER STRIP (WORKSURFACE HEIGHT)



25N28CPFSW	Wood	\$ 51	¾	2 ¹ / ₁₆	25 ³ / ₁₆	-	-	19 lbs.	1.8
25N28CPFSL	Laminate	37	¾	2 ¹ / ₁₆	25 ³ / ₁₆	-	-	19 lbs.	1.8

- When pedestals are positioned against a wall and a modesty panel is not used, specify a filler strip to fill the 1" gap between the work surface and pedestal depths


FILLER STRIP (BOX/FILE HEIGHT)



25N21CPFSW	Wood	\$ 36	¾	2 ¹ / ₁₆	18 ⁷ / ₁₆	-	-	16 lbs.	1.6
25N21CPFSL	Laminate	24	¾	2 ¹ / ₁₆	18 ⁷ / ₁₆	-	-	16 lbs.	1.6

- When pedestals are positioned against a wall and a modesty panel is not used, specify a filler strip to fill the 1" gap between the work surface and pedestal depths


SUPPORT BASE BRACKET



25N04BKT		\$ 24	¾	4 ¹ / ₁₆	-	-	-	1 lbs.	0.3
----------	--	-------	---	--------------------------------	---	---	---	--------	-----

- Specify metal paint color 462 Cinder, 501 Platinum Metallic, or 503 Satin Nickel Metallic
- For use with an extension surface and using a full modesty

WORKSURFACE WIRE MANAGER FILLER CAP



NAC01WMFM		\$ 16	1	1	1	-	-	1 lbs.	0.5
-----------	--	-------	---	---	---	---	---	--------	-----

- Specify paint color
- Paint options and recommendations are listed on page 92