
EPIC

COMPONENTS

Component Units

156



PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories

TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminate models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminate Top Color

SAMPLE MODEL NUMBER:

25N3984WSSLK2 E K405 G11MBLR D1B403 X X 807
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED CUBIC		
			D	W	H	A	KW	WEIGHT	FEET	
RECTANGULAR WORKSURFACE 36" DEPTH 	SOFTENED RIM									
	25N3684WSSW	Wood	\$ 1308	36 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	117 lbs.	4.0
	25N3684WSSL	Laminate	890	36 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	117 lbs.	4.0
	25N3678WSSW	Wood	\$ 1212	36 ¹ / ₁₆	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	108 lbs.	4.0
	25N3678WSSL	Laminate	823	36 ¹ / ₁₆	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	108 lbs.	4.0
	25N3672WSSW	Wood	\$ 1114	36 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	100 lbs.	4.0
	25N3672WSSL	Laminate	757	36 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	100 lbs.	4.0
	KNIFE RIM									
	25N3884WSSWK1	Wood	\$ 1704	37 ⁷ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	120 lbs.	4.2
	25N3884WSSLK1	Laminate	1382	37 ⁷ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	120 lbs.	4.2
	25N3878WSSWK1	Wood	\$ 1576	37 ⁷ / ₁₆	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	111 lbs.	4.2
	25N3878WSSLK1	Laminate	1274	37 ⁷ / ₁₆	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	111 lbs.	4.2
25N3872WSSWK1	Wood	\$ 1451	37 ⁷ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	103 lbs.	4.2	
25N3872WSSLK1	Laminate	1175	37 ⁷ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	103 lbs.	4.2	
25N3984WSSWK2	Wood	\$ 1704	39 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	120 lbs.	4.4	
25N3984WSSLK2	Laminate	1382	39 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	120 lbs.	4.4	
25N3978WSSWK2	Wood	\$ 1576	39 ¹ / ₁₆	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	117 lbs.	4.4	
25N3978WSSLK2	Laminate	1274	39 ¹ / ₁₆	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	117 lbs.	4.4	
25N3972WSSWK2	Wood	\$ 1451	39 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	108 lbs.	4.4	
25N3972WSSLK2	Laminate	1175	39 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	108 lbs.	4.4	

- Wire Manager available on left side, back, right side, back & left or back & right; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Worksurfaces can be ordered in 1/8" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 29" deep component pedestals
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 207
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories

TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminated Top Color

SAMPLE MODEL NUMBER:

25N3096WSSL M V405 G11MBLR X X 83½ 807
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET
			D	W	H				
RECTANGULAR WORKSURFACE 30" DEPTH 	SOFTENED RIM								
	25N3096WSSW	Wood	\$ 1212	30½	95½	1¾	—	—	111 lbs. 4.0
	25N3096WSSL	Laminate	745	30½	95½	1¾	—	—	111 lbs. 4.0
	25N3090WSSW	Wood	\$ 1164	30½	89½	1¾	—	—	104 lbs. 3.9
	25N3090WSSL	Laminate	721	30½	89½	1¾	—	—	104 lbs. 3.9
	25N3084WSSW	Wood	\$ 1114	30½	83½	1¾	—	—	97 lbs. 3.7
	25N3084WSSL	Laminate	693	30½	83½	1¾	—	—	97 lbs. 3.7
	25N3078WSSW	Wood	\$ 1015	30½	77½	1¾	—	—	90 lbs. 3.6
	25N3078WSSL	Laminate	624	30½	77½	1¾	—	—	90 lbs. 3.6
	25N3072WSSW	Wood	\$ 918	30½	71½	1¾	—	—	83 lbs. 3.5
	25N3072WSSL	Laminate	562	30½	71½	1¾	—	—	83 lbs. 3.5
	25N3066WSSW	Wood	\$ 884	30½	66	1¾	—	—	76 lbs. 3.4
	25N3066WSSL	Laminate	515	30½	66	1¾	—	—	76 lbs. 3.4
	25N3060WSSW	Wood	\$ 864	30½	60	1¾	—	—	69 lbs. 3.3
	25N3060WSSL	Laminate	469	30½	60	1¾	—	—	69 lbs. 3.3
	25N3054WSSW	Wood	\$ 844	30½	54	1¾	—	—	63 lbs. 3.0
	25N3054WSSL	Laminate	432	30½	54	1¾	—	—	63 lbs. 3.0
	25N3048WSSW	Wood	\$ 827	30½	48½	1¾	—	—	56 lbs. 2.7
	25N3048WSSL	Laminate	393	30½	48½	1¾	—	—	56 lbs. 2.7

- Wire Manager available on left side, back, right side, back & left or back & right; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Worksurfaces can be ordered in ½" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 23" or 29" deep pedestals
- Worksurfaces up to 72" wide can be used for table desking applications
- Specify center grommet only when using C-leg bases; field installed grommets are also available
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 207
- For Epicenter depth worksurfaces see pages 240-242
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories


TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminate Top Color

SAMPLE MODEL NUMBER:

25N3278WSSSLK1 M K478 G1A X X X 478
 • See pages 95-99 for all options available in Epic

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED CUBIC	
		D	W	H	A	KW	WEIGHT	FEET
RECTANGULAR WORKSURFACE 30" DEPTH (CONTINUED)								
KNIFE RIM								
25N3296WSSWK1 Wood	\$ 1576	31 ¹ / ₁₆	95 ¹ / ₁₆	1 ³ / ₁₆	—	—	119 lbs.	4.2
25N3296WSSSLK1 Laminate	1154	31 ¹ / ₁₆	95 ¹ / ₁₆	1 ³ / ₁₆	—	—	119 lbs.	4.2
25N3290WSSWK1 Wood	\$ 1512	31 ¹ / ₁₆	89 ¹ / ₁₆	1 ³ / ₁₆	—	—	111 lbs.	4.1
25N3290WSSSLK1 Laminate	1114	31 ¹ / ₁₆	89 ¹ / ₁₆	1 ³ / ₁₆	—	—	111 lbs.	4.1
25N3284WSSWK1 Wood	\$ 1451	31 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	104 lbs.	3.9
25N3284WSSSLK1 Laminate	1073	31 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	104 lbs.	3.9
25N3278WSSWK1 Wood	\$ 1321	31 ¹ / ₁₆	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	96 lbs.	3.8
25N3278WSSSLK1 Laminate	967	31 ¹ / ₁₆	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	96 lbs.	3.8
25N3272WSSWK1 Wood	\$ 1192	31 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	89 lbs.	3.7
25N3272WSSSLK1 Laminate	870	31 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	89 lbs.	3.7
25N3266WSSWK1 Wood	\$ 1147	31 ¹ / ₁₆	66	1 ³ / ₁₆	—	—	82 lbs.	3.6
25N3266WSSSLK1 Laminate	797	31 ¹ / ₁₆	66	1 ³ / ₁₆	—	—	82 lbs.	3.6
25N3260WSSWK1 Wood	\$ 1124	31 ¹ / ₁₆	60	1 ³ / ₁₆	—	—	74 lbs.	3.5
25N3260WSSSLK1 Laminate	728	31 ¹ / ₁₆	60	1 ³ / ₁₆	—	—	74 lbs.	3.5
25N3254WSSWK1 Wood	\$ 1098	31 ¹ / ₁₆	54	1 ³ / ₁₆	—	—	67 lbs.	3.2
25N3254WSSSLK1 Laminate	669	31 ¹ / ₁₆	54	1 ³ / ₁₆	—	—	67 lbs.	3.2
25N3248WSSWK1 Wood	\$ 1076	31 ¹ / ₁₆	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	59 lbs.	2.8
25N3248WSSSLK1 Laminate	609	31 ¹ / ₁₆	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	59 lbs.	2.8



- Wire Manager available on left side, back, right side, back & left or back & right; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Worksurfaces can be ordered in 1/16" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 23" or 29" deep pedestals
- Worksurfaces up to 72" wide can be used for table desking applications
- Specify center grommet only when using C-leg bases; field installed grommets are also available
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 207
- For Epicenter depth worksurfaces see pages 240-242
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories

TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminite models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminite Top Color

SAMPLE MODEL NUMBER:

25N3378WSSSLK2 M K478 G1A X X X 478
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET
			D	W	H				
RECTANGULAR WORKSURFACE 30" DEPTH (CONTINUED)	KNIFE RIM (CONTINUED)								
	25N3396WSSWK2 Wood	\$ 1576	33 ³ / ₁₆	95 ¹ / ₁₆	1 ³ / ₁₆	—	—	122 lbs.	4.4
	25N3396WSSSLK2 Laminate	1154	33 ³ / ₁₆	95 ¹ / ₁₆	1 ³ / ₁₆	—	—	122 lbs.	4.4
	25N3390WSSWK2 Wood	\$ 1512	33 ³ / ₁₆	89 ¹ / ₁₆	1 ³ / ₁₆	—	—	114 lbs.	4.3
	25N3390WSSSLK2 Laminate	1114	33 ³ / ₁₆	89 ¹ / ₁₆	1 ³ / ₁₆	—	—	114 lbs.	4.3
	25N3384WSSWK2 Wood	\$ 1451	33 ³ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	107 lbs.	4.1
	25N3384WSSSLK2 Laminate	1073	33 ³ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	107 lbs.	4.1
	25N3378WSSWK2 Wood	\$ 1321	33 ³ / ₁₆	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	99 lbs.	4.0
	25N3378WSSSLK2 Laminate	967	33 ³ / ₁₆	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	99 lbs.	4.0
	25N3372WSSWK2 Wood	\$ 1192	33 ³ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	92 lbs.	3.9
	25N3372WSSSLK2 Laminate	870	33 ³ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	92 lbs.	3.9
	25N3366WSSWK2 Wood	\$ 1147	33 ³ / ₁₆	66	1 ³ / ₁₆	—	—	84 lbs.	3.8
	25N3366WSSSLK2 Laminate	797	33 ³ / ₁₆	66	1 ³ / ₁₆	—	—	84 lbs.	3.8
	25N3360WSSWK2 Wood	\$ 1124	33 ³ / ₁₆	60	1 ³ / ₁₆	—	—	76 lbs.	3.6
	25N3360WSSSLK2 Laminate	728	33 ³ / ₁₆	60	1 ³ / ₁₆	—	—	76 lbs.	3.6
	25N3354WSSWK2 Wood	\$ 1098	33 ³ / ₁₆	54	1 ³ / ₁₆	—	—	69 lbs.	3.3
	25N3354WSSSLK2 Laminate	669	33 ³ / ₁₆	54	1 ³ / ₁₆	—	—	69 lbs.	3.3
	25N3348WSSWK2 Wood	\$ 1076	33 ³ / ₁₆	48 ³ / ₁₆	1 ³ / ₁₆	—	—	61 lbs.	3.0
	25N3348WSSSLK2 Laminate	609	33 ³ / ₁₆	48 ³ / ₁₆	1 ³ / ₁₆	—	—	61 lbs.	3.0

- Wire Manager available on left side, back, right side, back & left or back & right; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Worksurfaces can be ordered in 1/16" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 23" or 29" deep pedestals
- Worksurfaces up to 72" wide can be used for table desking applications
- Specify center grommet only when using C-leg bases; field installed grommets are also available
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 207
- For Epicenter depth worksurfaces see pages 240-242
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories


TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminite models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminate Top Color

SAMPLE MODEL NUMBER:

25N2496WSSW M V X D1B462 X 95.5 CL
 • See pages 95-99 for all options available in Epic

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED CUBIC	
		D	W	H	A	KW	WEIGHT	FEET
RECTANGULAR WORKSURFACE 24" DEPTH								
SOFTENED RIM								
25N2496WSSW Wood	\$ 1115	24	95 ¹ / ₁₆	1 ³ / ₁₆	—	—	89 lbs.	3.6
25N2496WSSL Laminate	656	24	95 ¹ / ₁₆	1 ³ / ₁₆	—	—	89 lbs.	3.6
25N2490WSSW Wood	\$ 1067	24	89 ¹ / ₁₆	1 ³ / ₁₆	—	—	83 lbs.	3.5
25N2490WSSL Laminate	630	24	89 ¹ / ₁₆	1 ³ / ₁₆	—	—	83 lbs.	3.5
25N2484WSSW Wood	\$ 1016	24	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	78 lbs.	3.2
25N2484WSSL Laminate	605	24	83 ¹ / ₁₆	1 ³ / ₁₆	—	—	78 lbs.	3.2
25N2478WSSW Wood	\$ 919	24	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	72 lbs.	3.3
25N2478WSSL Laminate	538	24	77 ¹ / ₁₆	1 ³ / ₁₆	—	—	72 lbs.	3.3
25N2472WSSW Wood	\$ 820	24	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	67 lbs.	3.3
25N2472WSSL Laminate	469	24	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	67 lbs.	3.3
25N2466WSSW Wood	\$ 788	24	66	1 ³ / ₁₆	—	—	61 lbs.	3.1
25N2466WSSL Laminate	435	24	66	1 ³ / ₁₆	—	—	61 lbs.	3.1
25N2460WSSW Wood	\$ 766	24	60	1 ³ / ₁₆	—	—	56 lbs.	2.8
25N2460WSSL Laminate	412	24	60	1 ³ / ₁₆	—	—	56 lbs.	2.8
25N2454WSSW Wood	\$ 747	24	54	1 ³ / ₁₆	—	—	50 lbs.	2.5
25N2454WSSL Laminate	364	24	54	1 ³ / ₁₆	—	—	50 lbs.	2.5
25N2448WSSW Wood	\$ 730	24	48 ³ / ₁₆	1 ³ / ₁₆	—	—	44 lbs.	2.3
25N2448WSSL Laminate	331	24	48 ³ / ₁₆	1 ³ / ₁₆	—	—	44 lbs.	2.3



- Wire Manager available on left side, back, right side, back & left or back & right; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Worksurfaces can be ordered in 1/16" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 23" deep pedestals
- Worksurfaces up to 72" wide can be used for table desking applications
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 207
- For worksurfaces with grain direction running front-to-back see pages 166-167
- For Epicenter depth worksurfaces see pages 243-247
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories

TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminate Top Color

SAMPLE MODEL NUMBER:

25N2442WSSW M V X D1B462 X 95.5 CL
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET	
			D	W	H					
RECTANGULAR WORKSURFACE 24" DEPTH (CONTINUED) 	SOFTENED RIM (CONTINUED)									
	25N2442WSSW	Wood	\$ 698	24	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	38 lbs.	2.3
	25N2442WSSL	Laminate	297	24	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	38 lbs.	2.3
	25N2436WSSW	Wood	\$ 672	24	36 ¹ / ₁₆	1 ³ / ₁₆	—	—	33 lbs.	1.8
	25N2436WSSL	Laminate	271	24	36 ¹ / ₁₆	1 ³ / ₁₆	—	—	33 lbs.	1.8
	25N2430WSSW	Wood	\$ 653	24	30 ¹ / ₁₆	1 ³ / ₁₆	—	—	28 lbs.	1.5
	25N2430WSSL	Laminate	243	24	30 ¹ / ₁₆	1 ³ / ₁₆	—	—	28 lbs.	1.5

- Wire Manager available on left side, back, right side, back & left or back & right; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Worksurfaces can be ordered in 1/8" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 23" deep pedestals
- Worksurfaces up to 72" wide can be used for table desking applications
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 207
- For worksurfaces with grain direction running front-to-back see pages 166-167
- For Epicenter depth worksurfaces see pages 243-247
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories


TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminated Top Color

SAMPLE MODEL NUMBER:

25N2696WSSWK1 F K G1LR D1B461 25 94 MC
 • See pages 95-99 for all options available in Epic

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED CUBIC	
		D	W	H	A	KW	WEIGHT	FEET
RECTANGULAR WORKSURFACE 24" DEPTH (CONTINUED)								
KNIFE RIM								
25N2696WSSWK1 Wood	\$ 1452	25½	95½	1¾	—	—	96 lbs.	3.8
25N2696WSSLK1 Laminate	1017	25½	95½	1¾	—	—	96 lbs.	3.8
25N2690WSSWK1 Wood	\$ 1385	25½	89½	1¾	—	—	89 lbs.	3.7
25N2690WSSLK1 Laminate	979	25½	89½	1¾	—	—	89 lbs.	3.7
25N2684WSSWK1 Wood	\$ 1322	25½	83½	1¾	—	—	81 lbs.	3.6
25N2684WSSLK1 Laminate	938	25½	83½	1¾	—	—	81 lbs.	3.6
25N2678WSSWK1 Wood	\$ 1193	25½	77½	1¾	—	—	78 lbs.	3.5
25N2678WSSLK1 Laminate	834	25½	77½	1¾	—	—	78 lbs.	3.5
25N2672WSSWK1 Wood	\$ 1067	25½	71½	1¾	—	—	72 lbs.	3.4
25N2672WSSLK1 Laminate	728	25½	71½	1¾	—	—	72 lbs.	3.4
25N2666WSSWK1 Wood	\$ 1029	25½	66	1¾	—	—	66 lbs.	3.3
25N2666WSSLK1 Laminate	677	25½	66	1¾	—	—	66 lbs.	3.3
25N2660WSSWK1 Wood	\$ 997	25½	60	1¾	—	—	60 lbs.	2.9
25N2660WSSLK1 Laminate	641	25½	60	1¾	—	—	60 lbs.	2.9
25N2654WSSWK1 Wood	\$ 969	25½	54	1¾	—	—	54 lbs.	2.6
25N2654WSSLK1 Laminate	566	25½	54	1¾	—	—	54 lbs.	2.6
25N2648WSSWK1 Wood	\$ 951	25½	48½	1¾	—	—	48 lbs.	2.4
25N2648WSSLK1 Laminate	511	25½	48½	1¾	—	—	48 lbs.	2.4



- Wire Manager available on left side, back, right side, back & left or back & right; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Worksurfaces can be ordered in ½" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 23" deep pedestals
- Worksurfaces up to 72" wide can be used for table desking applications
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 207
- For worksurfaces with grain direction running front-to-back see pages 166-167
- For Epicenter depth worksurfaces see pages 243-247
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories

TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminate Top Color

SAMPLE MODEL NUMBER:

25N2642WSSWK1 F K G1LR D1B461 25 94 MC
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET
			D	W	H				
RECTANGULAR WORKSURFACE 24" DEPTH (CONTINUED)	KNIFE RIM (CONTINUED)								
	25N2642WSSWK1 Wood	\$ 905	25½	42½	1¾	—	—	42 lbs. 2.4	
	25N2642WSSLK1 Laminate	461	25½	42½	1¾	—	—	42 lbs. 2.4	
	25N2636WSSWK1 Wood	\$ 874	25½	36½	1¾	—	—	36 lbs. 1.9	
	25N2636WSSLK1 Laminate	421	25½	36½	1¾	—	—	36 lbs. 1.9	
	25N2630WSSWK1 Wood	\$ 849	25½	30½	1¾	—	—	30 lbs. 1.6	
	25N2630WSSLK1 Laminate	375	25½	30½	1¾	—	—	30 lbs. 1.6	
	25N2796WSSWK2 Wood	\$ 1452	27	95½	1¾	—	—	100 lbs. 4.0	
	25N2796WSSLK2 Laminate	1017	27	95½	1¾	—	—	100 lbs. 4.0	
	25N2790WSSWK2 Wood	\$ 1385	27	89½	1¾	—	—	94 lbs. 3.9	
	25N2790WSSLK2 Laminate	979	27	89½	1¾	—	—	94 lbs. 3.9	
	25N2784WSSWK2 Wood	\$ 1322	27	83½	1¾	—	—	88 lbs. 3.7	
	25N2784WSSLK2 Laminate	938	27	83½	1¾	—	—	88 lbs. 3.7	
	25N2778WSSWK2 Wood	\$ 1193	27	77½	1¾	—	—	81 lbs. 3.6	
	25N2778WSSLK2 Laminate	834	27	77½	1¾	—	—	81 lbs. 3.6	
	25N2772WSSWK2 Wood	\$ 1067	27	71½	1¾	—	—	75 lbs. 3.5	
	25N2772WSSLK2 Laminate	728	27	71½	1¾	—	—	75 lbs. 3.5	
	25N2766WSSWK2 Wood	\$ 1029	27	66	1¾	—	—	69 lbs. 3.4	
	25N2766WSSLK2 Laminate	677	27	66	1¾	—	—	69 lbs. 3.4	

- Wire Manager available on left side, back, right side, back & left or back & right; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Worksurfaces can be ordered in ½" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 23" deep pedestals
- Worksurfaces up to 72" wide can be used for table desking applications
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 207
- For worksurfaces with grain direction running front-to-back see pages 166-167
- For Epicenter depth worksurfaces see pages 243-247
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories

TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminate models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminate Top Color

SAMPLE MODEL NUMBER:

25N2760WSSWK2 E K G1A X X X CL
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED CUBIC		
			D	W	H	A	KW	WEIGHT	FEET	
<p>RECTANGULAR WORKSURFACE 24" DEPTH (CONTINUED)</p> 	KNIFE RIM (CONTINUED)									
	25N2760WSSWK2	Wood	\$ 997	27	60	1 3/16	—	—	63 lbs.	3.1
	25N2760WSSLK2	Laminate	641	27	60	1 3/16	—	—	63 lbs.	3.1
	25N2754WSSWK2	Wood	\$ 969	27	54	1 3/16	—	—	56 lbs.	2.8
	25N2754WSSLK2	Laminate	566	27	54	1 3/16	—	—	56 lbs.	2.8
	25N2748WSSWK2	Wood	\$ 951	27	48 3/16	1 3/16	—	—	50 lbs.	2.5
	25N2748WSSLK2	Laminate	511	27	48 3/16	1 3/16	—	—	50 lbs.	2.5
	25N2742WSSWK2	Wood	\$ 905	27	42 3/16	1 3/16	—	—	44 lbs.	2.3
	25N2742WSSLK2	Laminate	461	27	42 3/16	1 3/16	—	—	44 lbs.	2.3
	25N2736WSSWK2	Wood	\$ 874	27	36 3/16	1 3/16	—	—	38 lbs.	2.0
	25N2736WSSLK2	Laminate	421	27	36 3/16	1 3/16	—	—	38 lbs.	2.0
	25N2730WSSWK2	Wood	\$ 849	27	30 3/16	1 3/16	—	—	31 lbs.	1.7
	25N2730WSSLK2	Laminate	375	27	30 3/16	1 3/16	—	—	31 lbs.	1.7

- Wire Manager available on left side, back, right side, back & left or back & right; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Worksurfaces can be ordered in 1/8" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 23" deep pedestals
- Worksurfaces up to 72" wide can be used for table desking applications
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 207
- For worksurfaces with grain direction running front-to-back see pages 166-167
- For Epicenter depth worksurfaces see pages 243-247
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories

TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminite models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminite Top Color

SAMPLE MODEL NUMBER:

25N26A96WSSLK1 E K G1A X X X CL
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET
			D	W	H				
RECTANGULAR WORKSURFACE 24" DEEP FOR STORAGE CREDENZAS 	SOFTENED RIM								
	25N24A96WSSL	Laminite	\$ 656	24	96 ¹ / ₁₆	1 ³ / ₁₆	—	—	89 lbs. 3.6
	25N24A90WSSL	Laminite	630	24	90 ¹ / ₁₆	1 ³ / ₁₆	—	—	83 lbs. 3.5
	25N24A84WSSL	Laminite	605	24	84 ¹ / ₁₆	1 ³ / ₁₆	—	—	78 lbs. 3.2
	25N24A78WSSL	Laminite	538	24	78 ¹ / ₁₆	1 ³ / ₁₆	—	—	72 lbs. 3.3
	25N24A72WSSL	Laminite	469	24	72 ¹ / ₁₆	1 ³ / ₁₆	—	—	67 lbs. 3.3
	25N24A66WSSL	Laminite	435	24	66 ¹ / ₁₆	1 ³ / ₁₆	—	—	61 lbs. 3.1
	25N24A60WSSL	Laminite	412	24	60 ¹ / ₁₆	1 ³ / ₁₆	—	—	56 lbs. 2.8
	KNIFE RIM								
	25N26A96WSSLK1	Laminite	\$ 1017	25 ¹ / ₂	96 ¹ / ₁₆	1 ³ / ₁₆	—	—	96 lbs. 3.8
25N26A90WSSLK1	Laminite	979	25 ¹ / ₂	90 ¹ / ₁₆	1 ³ / ₁₆	—	—	89 lbs. 3.7	
25N26A84WSSLK1	Laminite	938	25 ¹ / ₂	84 ¹ / ₁₆	1 ³ / ₁₆	—	—	81 lbs. 3.6	
25N26A78WSSLK1	Laminite	834	25 ¹ / ₂	78 ¹ / ₁₆	1 ³ / ₁₆	—	—	78 lbs. 3.5	
25N26A72WSSLK1	Laminite	728	25 ¹ / ₂	72 ¹ / ₁₆	1 ³ / ₁₆	—	—	72 lbs. 3.4	
25N26A66WSSLK1	Laminite	677	25 ¹ / ₂	66 ¹ / ₁₆	1 ³ / ₁₆	—	—	66 lbs. 3.3	
25N26A60WSSLK1	Laminite	641	25 ¹ / ₂	60 ¹ / ₁₆	1 ³ / ₁₆	—	—	60 lbs. 2.9	

- For use in storage credenza application
- Wire Manager available on left side, back, right side, back & left or back & right; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- For use with 23" deep pedestals
- For use when 2 or more laminite pedestals are ganged together under a common top

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories


TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminated Top Color

SAMPLE MODEL NUMBER:

25N2660WSSVWK1 M K G1C D1B478 X X MC
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED CUBIC	
			D	W	H	A	KW	WEIGHT	FEET
RECTANGULAR WORKSURFACE 24" DEPTH	SOFTENED RIM								
	25N2460WSSVW Wood	\$ 766	24	60	1 3/16	—	—	56 lbs.	2.8
	25N2460WSSVL Laminate	412	24	60	1 3/16	—	—	56 lbs.	2.8
	25N2454WSSVW Wood	\$ 747	24	54	1 3/16	—	—	50 lbs.	2.5
	25N2454WSSVL Laminate	364	24	54	1 3/16	—	—	50 lbs.	2.5
	25N2448WSSVW Wood	\$ 730	24	48 1/16	1 3/16	—	—	44 lbs.	2.3
	25N2448WSSVL Laminate	331	24	48 1/16	1 3/16	—	—	44 lbs.	2.3
	25N2442WSSVW Wood	\$ 698	24	42 1/16	1 3/16	—	—	38 lbs.	2.1
	25N2442WSSVL Laminate	297	24	42 1/16	1 3/16	—	—	38 lbs.	2.1
	25N2436WSSVW Wood	\$ 672	24	36 1/16	1 3/16	—	—	33 lbs.	1.8
	25N2436WSSVL Laminate	271	24	36 1/16	1 3/16	—	—	33 lbs.	1.8
	25N2430WSSVW Wood	\$ 653	24	30 1/16	1 3/16	—	—	28 lbs.	1.5
	25N2430WSSVL Laminate	243	24	30 1/16	1 3/16	—	—	28 lbs.	1.5
	KNIFE RIM								
	25N2660WSSVWK1 Wood	\$ 997	25 1/2	60	1 3/16	—	—	60 lbs.	2.9
	25N2660WSSVLK1 Laminate	641	25 1/2	60	1 3/16	—	—	60 lbs.	2.9
	25N2654WSSVWK1 Wood	\$ 969	25 1/2	54	1 3/16	—	—	54 lbs.	2.6
	25N2654WSSVLK1 Laminate	566	25 1/2	54	1 3/16	—	—	54 lbs.	2.6
	25N2648WSSVWK1 Wood	\$ 951	25 1/2	48 1/16	1 3/16	—	—	48 lbs.	2.4
	25N2648WSSVLK1 Laminate	511	25 1/2	48 1/16	1 3/16	—	—	48 lbs.	2.4



- Wire Manager available on left side, back, right side, back & left or back & right; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Worksurfaces can be ordered in 1/16" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- Grain direction runs front-to-back
- For use with 23" deep pedestals
- Intended to be used when building an L or U configuration utilizing components
- For worksurfaces with grain direction running left-to-right, refer to pages 160-164
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 207
- For Epicenter depth worksurfaces see pages 243-247
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories


TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminate Top Color

SAMPLE MODEL NUMBER:

25N2630WSSVWK1 M K G1C D1B478 X X MC
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET	
			D	W	H					
RECTANGULAR WORKSURFACE 24" DEPTH (CONTINUED)	KNIFE RIM (CONTINUED)									
	25N2642WSSVWK1	Wood	\$ 905	25½	42½	1¾	—	—	42 lbs.	2.2
	25N2642WSSVLK1	Laminate	461	25½	42½	1¾	—	—	42 lbs.	2.2
	25N2636WSSVWK1	Wood	\$ 874	25½	36¾	1¾	—	—	33 lbs.	1.8
	25N2636WSSVLK1	Laminate	421	25½	36¾	1¾	—	—	33 lbs.	1.8
	25N2630WSSVWK1	Wood	\$ 849	25½	30¾	1¾	—	—	28 lbs.	1.5
	25N2630WSSVLK1	Laminate	375	25½	30¾	1¾	—	—	28 lbs.	1.5
	25N2760WSSVWK2	Wood	\$ 997	27	60	1¾	—	—	63 lbs.	3.1
	25N2760WSSVLK2	Laminate	641	27	60	1¾	—	—	63 lbs.	3.1
	25N2754WSSVWK2	Wood	\$ 969	27	54	1¾	—	—	56 lbs.	2.8
	25N2754WSSVLK2	Laminate	566	27	54	1¾	—	—	56 lbs.	2.8
	25N2748WSSVWK2	Wood	\$ 951	27	48¾	1¾	—	—	50 lbs.	2.5
	25N2748WSSVLK2	Laminate	511	27	48¾	1¾	—	—	50 lbs.	2.5
	25N2742WSSVWK2	Wood	\$ 905	27	42¾	1¾	—	—	44 lbs.	2.3
	25N2742WSSVLK2	Laminate	461	27	42¾	1¾	—	—	44 lbs.	2.3
	25N2736WSSVWK2	Wood	\$ 874	27	36¾	1¾	—	—	33 lbs.	1.8
	25N2736WSSVLK2	Laminate	421	27	36¾	1¾	—	—	33 lbs.	1.8
	25N2730WSSVWK2	Wood	\$ 849	27	30¾	1¾	—	—	28 lbs.	1.5
	25N2730WSSVLK2	Laminate	375	27	30¾	1¾	—	—	28 lbs.	1.5



- Wire Manager available on left side, back, right side, back & left or back & right; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Worksurfaces can be ordered in ½" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- Grain direction runs front-to-back
- For use with 23" deep pedestals
- Intended to be used when building an L or U configuration utilizing components
- For worksurfaces with grain direction running left-to-right, refer to pages 160-164
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 207
- For Epicenter depth worksurfaces see pages 243-247
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories

TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminate Top Color

SAMPLE MODEL NUMBER:

25N1860WSSW M V G1C D1B425 X X CW
 • See pages 95-99 for all options available in Epic

RECTANGULAR WORKSURFACE 18" DEPTH	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED CUBIC	
			D	W	H	A	KW	WEIGHT	FEET
	SOFTENED RIM								
	25N1896WSSW Wood	\$ 1038	18 $\frac{1}{8}$ "	95 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	75 lbs.	3.0
	25N1896WSSL Laminate	612	18 $\frac{1}{8}$ "	95 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	75 lbs.	3.0
	25N1890WSSW Wood	\$ 992	18 $\frac{1}{8}$ "	89 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	71 lbs.	2.9
	25N1890WSSL Laminate	588	18 $\frac{1}{8}$ "	89 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	71 lbs.	2.9
	25N1884WSSW Wood	\$ 945	18 $\frac{1}{8}$ "	83 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	66 lbs.	2.7
	25N1884WSSL Laminate	564	18 $\frac{1}{8}$ "	83 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	66 lbs.	2.7
	25N1878WSSW Wood	\$ 853	18 $\frac{1}{8}$ "	77 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	61 lbs.	2.5
	25N1878WSSL Laminate	499	18 $\frac{1}{8}$ "	77 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	61 lbs.	2.5
	25N1872WSSW Wood	\$ 763	18 $\frac{1}{8}$ "	71 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	57 lbs.	2.3
	25N1872WSSL Laminate	435	18 $\frac{1}{8}$ "	71 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	57 lbs.	2.3
	25N1866WSSW Wood	\$ 734	18 $\frac{1}{8}$ "	66"	1 $\frac{3}{16}$ "	—	—	52 lbs.	2.2
	25N1866WSSL Laminate	404	18 $\frac{1}{8}$ "	66"	1 $\frac{3}{16}$ "	—	—	52 lbs.	2.2
	25N1860WSSW Wood	\$ 712	18 $\frac{1}{8}$ "	60"	1 $\frac{3}{16}$ "	—	—	48 lbs.	2.0
	25N1860WSSL Laminate	384	18 $\frac{1}{8}$ "	60"	1 $\frac{3}{16}$ "	—	—	48 lbs.	2.0
	25N1854WSSW Wood	\$ 696	18 $\frac{1}{8}$ "	54"	1 $\frac{3}{16}$ "	—	—	43 lbs.	1.8
	25N1854WSSL Laminate	340	18 $\frac{1}{8}$ "	54"	1 $\frac{3}{16}$ "	—	—	43 lbs.	1.8
	25N1848WSSW Wood	\$ 680	18 $\frac{1}{8}$ "	48 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	38 lbs.	1.6
	25N1848WSSL Laminate	306	18 $\frac{1}{8}$ "	48 $\frac{1}{16}$ "	1 $\frac{3}{16}$ "	—	—	38 lbs.	1.6

- Wire Manager available on left side, back, right side, back & left or back & right; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Worksurfaces can be ordered in $\frac{1}{16}$ " increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 17" deep pedestals
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 207
- For Epicenter depth worksurfaces see pages 243-247
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories


TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminated Top Color

SAMPLE MODEL NUMBER:

25N1842WSSW M V G1C D1B425 X X CW
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET	
			D	W	H					
RECTANGULAR WORKSURFACE 18" DEPTH (CONTINUED)	SOFTENED RIM (CONTINUED)									
	25N1842WSSW	Wood	\$ 649	18½"	42½"	1¾"	—	—	34 lbs.	1.5
	25N1842WSSL	Laminate	277	18½"	42½"	1¾"	—	—	34 lbs.	1.5
	25N1836WSSW	Wood	\$ 625	18½"	36½"	1¾"	—	—	29 lbs.	1.3
	25N1836WSSL	Laminate	252	18½"	36½"	1¾"	—	—	29 lbs.	1.3
	25N1830WSSW	Wood	\$ 609	18½"	30½"	1¾"	—	—	24 lbs.	1.1
	25N1830WSSL	Laminate	227	18½"	30½"	1¾"	—	—	24 lbs.	1.1
	KNIFE RIM									
	25N2096WSSWK1	Wood	\$ 1275	19½"	95½"	1¾"	—	—	75 lbs.	3.0
	25N2096WSSLK1	Laminate	826	19½"	95½"	1¾"	—	—	75 lbs.	3.0
	25N2090WSSWK1	Wood	\$ 1220	19½"	89½"	1¾"	—	—	71 lbs.	2.9
	25N2090WSSLK1	Laminate	792	19½"	89½"	1¾"	—	—	71 lbs.	2.9
	25N2084WSSWK1	Wood	\$ 1163	19½"	83½"	1¾"	—	—	66 lbs.	2.7
	25N2084WSSLK1	Laminate	761	19½"	83½"	1¾"	—	—	66 lbs.	2.7
	25N2078WSSWK1	Wood	\$ 1050	19½"	77½"	1¾"	—	—	61 lbs.	2.5
	25N2078WSSLK1	Laminate	673	19½"	77½"	1¾"	—	—	61 lbs.	2.5
	25N2072WSSWK1	Wood	\$ 938	19½"	71½"	1¾"	—	—	57 lbs.	2.3
	25N2072WSSLK1	Laminate	588	19½"	71½"	1¾"	—	—	57 lbs.	2.3
	25N2066WSSWK1	Wood	\$ 903	19½"	66"	1¾"	—	—	52 lbs.	2.2
	25N2066WSSLK1	Laminate	545	19½"	66"	1¾"	—	—	52 lbs.	2.2



- Wire Manager available on left side, back, right side, back & left or back & right; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Worksurfaces can be ordered in ½" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 17" deep pedestals
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 207
- For Epicenter depth worksurfaces see pages 243-247
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories

TO ORDER, SPECIFY:


1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminite models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminite Top Color

SAMPLE MODEL NUMBER:

25N2060WSSWK1 M K G1C X MH

- See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED CUBIC	
			D	W	H	A	KW	WEIGHT	FEET
RECTANGULAR WORKSURFACE 18" DEPTH (CONTINUED)	KNIFE RIM (CONTINUED)								
	25N2060WSSWK1 Wood	\$ 878	19%	60	1 3/16	—	—	48 lbs.	2.0
	25N2060WSSLK1 Laminate	517	19%	60	1 3/16	—	—	48 lbs.	2.0
	25N2054WSSWK1 Wood	\$ 853	19%	54	1 3/16	—	—	43 lbs.	1.8
	25N2054WSSLK1 Laminate	459	19%	54	1 3/16	—	—	43 lbs.	1.8
	25N2048WSSWK1 Wood	\$ 837	19%	48 3/16	1 3/16	—	—	38 lbs.	1.6
	25N2048WSSLK1 Laminate	414	19%	48 3/16	1 3/16	—	—	38 lbs.	1.6
	25N2042WSSWK1 Wood	\$ 799	19%	42 3/16	1 3/16	—	—	34 lbs.	1.5
	25N2042WSSLK1 Laminate	372	19%	42 3/16	1 3/16	—	—	34 lbs.	1.5
	25N2036WSSWK1 Wood	\$ 769	19%	36 3/16	1 3/16	—	—	29 lbs.	1.3
	25N2036WSSLK1 Laminate	341	19%	36 3/16	1 3/16	—	—	29 lbs.	1.3
	25N2030WSSWK1 Wood	\$ 749	19%	30 3/16	1 3/16	—	—	24 lbs.	1.1
	25N2030WSSLK1 Laminate	306	19%	30 3/16	1 3/16	—	—	24 lbs.	1.1



- Wire Manager available on left side, back, right side, back & left or back & right; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Worksurfaces can be ordered in 1/8" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 17" deep pedestals
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 207
- For Epicenter depth worksurfaces see pages 243-247
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories

TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminite models)
5. Grommet
6. Wire Manager
7. Modified Depth
8. Modified Width
9. Veneer Top Finish/Laminite Top Color

SAMPLE MODEL NUMBER:

25N20A96WSSLK1 M K G1C X MH
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
			D	W	H	A	KW			
RECTANGULAR WORKSURFACE 18" DEEP FOR STORAGE CREDENZAS 	SOFTENED RIM									
	25N18A96WSSL	Laminite	\$ 612	18½	96½	1¾	—	—	75 lbs.	3.0
	25N18A90WSSL	Laminite	588	18½	90½	1¾	—	—	71 lbs.	2.9
	25N18A84WSSL	Laminite	564	18½	84½	1¾	—	—	66 lbs.	2.7
	25N18A78WSSL	Laminite	499	18½	78½	1¾	—	—	61 lbs.	2.5
	25N18A72WSSL	Laminite	435	18½	72½	1¾	—	—	57 lbs.	2.3
	25N18A66WSSL	Laminite	404	18½	66½	1¾	—	—	52 lbs.	2.2
	25N18A60WSSL	Laminite	384	18½	60½	1¾	—	—	48 lbs.	2.0
	KNIFE RIM									
	25N20A96WSSLK1	Laminite	\$ 826	19½	96½	1¾	—	—	75 lbs.	3.0
	25N20A90WSSLK1	Laminite	792	19½	90½	1¾	—	—	71 lbs.	2.9
	25N20A84WSSLK1	Laminite	761	19½	84½	1¾	—	—	66 lbs.	2.7
	25N20A78WSSLK1	Laminite	673	19½	78½	1¾	—	—	61 lbs.	2.5
	25N20A72WSSLK1	Laminite	588	19½	72½	1¾	—	—	57 lbs.	2.3
25N20A66WSSLK1	Laminite	545	19½	66½	1¾	—	—	52 lbs.	2.2	
25N20A60WSSLK1	Laminite	517	19½	60½	1¾	—	—	48 lbs.	2.0	

- Wire Manager available on left side, back, right side, back & left or back & right; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Worksurfaces can be ordered in ½" increments in depth and/or width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired depth and/or width
- For use with 17" deep pedestals
- To provide additional worksurface support when using in table desking applications, see undersurface support rails on page 207
- For Epicenter depth worksurfaces see pages 243-247
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Knife rim profile always on extension
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories

TO ORDER, SPECIFY:


1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminite models)
5. Grommet
6. Wire Manager
7. Veneer Top Finish/Laminite Top Color

SAMPLE MODEL NUMBER:

25N3696WSCERW2 M V G1A X MC

- See pages 95-99 for all options available in Epic

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS				CARTONED CUBIC	
		D	W	H	A	KW	WEIGHT
EXTENDED CORNER WORKSURFACE							
SOFTENED RIM							
		LEFT	RIGHT				
25N3696WSCELW2	25N3696WSCERW2	Wood	\$ 1821	35 ¹ / ₁₆	95 ¹ / ₁₆	1 ³ / ₁₆	-- -- 106 lbs. 5.9
25N3696WSCCELL2	25N3696WSCERL2	Laminite	1315	35 ¹ / ₁₆	95 ¹ / ₁₆	1 ³ / ₁₆	-- -- 106 lbs. 5.9
25N3690WSCELW2	25N3690WSCERW2	Wood	\$ 1790	35 ¹ / ₁₆	89 ¹ / ₁₆	1 ³ / ₁₆	-- -- 100 lbs. 5.6
25N3690WSCCELL2	25N3690WSCERL2	Laminite	1275	35 ¹ / ₁₆	89 ¹ / ₁₆	1 ³ / ₁₆	-- -- 100 lbs. 5.6
25N3684WSCELW2	25N3684WSCERW2	Wood	\$ 1760	35 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	-- -- 93 lbs. 5.2
25N3684WSCCELL2	25N3684WSCERL2	Laminite	1239	35 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	-- -- 93 lbs. 5.2
25N3678WSCELW2	25N3678WSCERW2	Wood	\$ 1579	35 ¹ / ₁₆	77 ¹ / ₁₆	1 ³ / ₁₆	-- -- 86 lbs. 4.6
25N3678WSCCELL2	25N3678WSCERL2	Laminite	1202	35 ¹ / ₁₆	77 ¹ / ₁₆	1 ³ / ₁₆	-- -- 86 lbs. 4.6
25N3672WSCELW2	25N3672WSCERW2	Wood	\$ 1397	35 ¹ / ₁₆	72	1 ³ / ₁₆	-- -- 79 lbs. 3.9
25N3672WSCCELL2	25N3672WSCERL2	Laminite	1165	35 ¹ / ₁₆	72	1 ³ / ₁₆	-- -- 79 lbs. 3.9
25N3666WSCELW2	25N3666WSCERW2	Wood	\$ 1349	35 ¹ / ₁₆	66	1 ³ / ₁₆	-- -- 72 lbs. 3.6
25N3666WSCCELL2	25N3666WSCERL2	Laminite	1107	35 ¹ / ₁₆	66	1 ³ / ₁₆	-- -- 72 lbs. 3.6
25N3660WSCELW2	25N3660WSCERW2	Wood	\$ 1258	35 ¹ / ₁₆	60	1 ³ / ₁₆	-- -- 65 lbs. 3.3
25N3660WSCCELL2	25N3660WSCERL2	Laminite	1050	35 ¹ / ₁₆	60	1 ³ / ₁₆	-- -- 65 lbs. 3.3
25N3654WSCELW2	25N3654WSCERW2	Wood	\$ 1213	35 ¹ / ₁₆	54	1 ³ / ₁₆	-- -- 58 lbs. 3.0
25N3654WSCCELL2	25N3654WSCERL2	Laminite	1018	35 ¹ / ₁₆	54	1 ³ / ₁₆	-- -- 58 lbs. 3.0
25N3696WSCELW2K1	25N3696WSCERW2K1	Wood	\$ 2367	36 ³ / ₁₆	95 ¹ / ₁₆	1 ³ / ₁₆	-- -- 106 lbs. 5.9
25N3696WSCCELL2K1	25N3696WSCERL2K1	Laminite	2036	36 ³ / ₁₆	95 ¹ / ₁₆	1 ³ / ₁₆	-- -- 106 lbs. 5.9
25N3690WSCELW2K1	25N3690WSCERW2K1	Wood	\$ 2326	36 ³ / ₁₆	90	1 ³ / ₁₆	-- -- 100 lbs. 5.6
25N3690WSCCELL2K1	25N3690WSCERL2K1	Laminite	1978	36 ³ / ₁₆	90	1 ³ / ₁₆	-- -- 100 lbs. 5.6



- Wire Manager available on left side, back or right side; see page 99 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 532
- For additional worksurface support, specify Undersurface Support Rail, see page 528
- Modified width and depth not available on this shape
- Intended for use with 24" deep worksurfaces
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying work surface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Knife rim profile always on extension
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported work surface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories


TO ORDER, SPECIFY:

1. Model Number
2. Work surface Type
3. Rim Profile
4. PVC Rim Color (laminated models)
5. Grommet
6. Wire Manager
7. Veneer Top Finish/Laminated Top Color

SAMPLE MODEL NUMBER:

25N3684WSCCELL2K1 E K405 X D1B405 405
 • See pages 95-99 for all options available in Epic

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS				KW	CARTONED WEIGHT	CUBIC FEET		
		D	W	H	A					
EXTENDED CORNER WORKSURFACE (CONTINUED)										
KNIFE RIM LEFT										
RIGHT										
25N3684WSCCELLW2K1	25N3684WSCERW2K1	Wood	\$ 2287	36 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	--	--	93 lbs.	5.2
25N3684WSCCELL2K1	25N3684WSCERL2K1	Laminate	1921	36 ¹ / ₁₆	83 ¹ / ₁₆	1 ³ / ₁₆	--	--	93 lbs.	5.2
25N3678WSCCELLW2K1	25N3678WSCERW2K1	Wood	\$ 2053	36 ¹ / ₁₆	78	1 ³ / ₁₆	--	--	86 lbs.	4.6
25N3678WSCCELL2K1	25N3678WSCERL2K1	Laminate	1863	36 ¹ / ₁₆	78	1 ³ / ₁₆	--	--	86 lbs.	4.6
25N3672WSCCELLW2K1	25N3672WSCERW2K1	Wood	\$ 1817	36 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	--	--	79 lbs.	3.9
25N3672WSCCELL2K1	25N3672WSCERL2K1	Laminate	1808	36 ¹ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	--	--	79 lbs.	3.9
25N3666WSCCELLW2K1	25N3666WSCERW2K1	Wood	\$ 1754	36 ¹ / ₁₆	66	1 ³ / ₁₆	--	--	72 lbs.	3.6
25N3666WSCCELL2K1	25N3666WSCERL2K1	Laminate	1715	36 ¹ / ₁₆	66	1 ³ / ₁₆	--	--	72 lbs.	3.6
25N3660WSCCELLW2K1	25N3660WSCERW2K1	Wood	\$ 1634	36 ¹ / ₁₆	60	1 ³ / ₁₆	--	--	65 lbs.	3.3
25N3660WSCCELL2K1	25N3660WSCERL2K1	Laminate	1629	36 ¹ / ₁₆	60	1 ³ / ₁₆	--	--	65 lbs.	3.3
25N3654WSCCELLW2K1	25N3654WSCERW2K1	Wood	\$ 1578	36 ¹ / ₁₆	54	1 ³ / ₁₆	--	--	58 lbs.	3.0
25N3654WSCCELL2K1	25N3654WSCERL2K1	Laminate	1579	36 ¹ / ₁₆	54	1 ³ / ₁₆	--	--	58 lbs.	3.0
25N3896WSCCELLW2K2	25N3896WSCERW2K2	Wood	\$ 2367	37 ¹ / ₂	95 ¹ / ₁₆	1 ³ / ₁₆	--	--	106 lbs.	5.9
25N3896WSCCELL2K2	25N3896WSCERL2K2	Laminate	2036	37 ¹ / ₂	95 ¹ / ₁₆	1 ³ / ₁₆	--	--	106 lbs.	5.9
25N3890WSCCELLW2K2	25N3890WSCERW2K2	Wood	\$ 2326	37 ¹ / ₂	90	1 ³ / ₁₆	--	--	100 lbs.	5.6
25N3890WSCCELL2K2	25N3890WSCERL2K2	Laminate	1978	37 ¹ / ₂	90	1 ³ / ₁₆	--	--	100 lbs.	5.6
25N3884WSCCELLW2K2	25N3884WSCERW2K2	Wood	\$ 2287	37 ¹ / ₂	83 ¹ / ₁₆	1 ³ / ₁₆	--	--	93 lbs.	5.2
25N3884WSCCELL2K2	25N3884WSCERL2K2	Laminate	1921	37 ¹ / ₂	83 ¹ / ₁₆	1 ³ / ₁₆	--	--	93 lbs.	5.2
25N3878WSCCELLW2K2	25N3878WSCERW2K2	Wood	\$ 2053	37 ¹ / ₂	78	1 ³ / ₁₆	--	--	86 lbs.	4.6
25N3878WSCCELL2K2	25N3878WSCERL2K2	Laminate	1863	37 ¹ / ₂	78	1 ³ / ₁₆	--	--	86 lbs.	4.6



Left shown

- Wire Manager available on left side, back or right side; see page 99 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 532
- For additional work surface support, specify Undersurface Support Rail, see page 528
- Modified width and depth not available on this shape
- Intended for use with 24" deep work surfaces
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Knife rim profile always on extension
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories


TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminite models)
5. Grommet
6. Wire Manager
7. Veneer Top Finish/Laminite Top Color

SAMPLE MODEL NUMBER:

25N3872WSCCELL2K2 E K405 X D1B405 405
 • See pages 95-99 for all options available in Epic

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS				KW	CARTONED CUBIC			
		D	W	H	A		WEIGHT	FEET		
EXTENDED CORNER WORKSURFACE (CONTINUED)										
KNIFE RIM (CONTINUED)										
		LEFT	RIGHT							
25N3872WSCCELW2K2	25N3872WSCERW2K2	Wood	\$ 1817	37½	71½	1¾	—	—	79 lbs.	3.9
25N3872WSCCELL2K2	25N3872WSCERL2K2	Laminate	1808	37½	71½	1¾	—	—	79 lbs.	3.9
25N3866WSCCELW2K2	25N3866WSCERW2K2	Wood	\$ 1754	37½	66	1¾	—	—	72 lbs.	3.6
25N3866WSCCELL2K2	25N3866WSCERL2K2	Laminate	1715	37½	66	1¾	—	—	72 lbs.	3.6
25N3860WSCCELW2K2	25N3860WSCERW2K2	Wood	\$ 1634	37½	60	1¾	—	—	65 lbs.	3.3
25N3860WSCCELL2K2	25N3860WSCERL2K2	Laminate	1629	37½	60	1¾	—	—	65 lbs.	3.3
25N3854WSCCELW2K2	25N3854WSCERW2K2	Wood	\$ 1578	37½	54	1¾	—	—	58 lbs.	3.0
25N3854WSCCELL2K2	25N3854WSCERL2K2	Laminate	1579	37½	54	1¾	—	—	58 lbs.	3.0



Left shown

- Wire Manager available on left side, back or right side; see page 99 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 532
- For additional worksurface support, specify Undersurface Support Rail, see page 528
- Modified width and depth not available on this shape
- Intended for use with 24" deep worksurfaces
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories

TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminate models)
5. Grommet
6. Wire Manager
7. Modified Width
8. Veneer Top Finish/Laminate Top Color

SAMPLE MODEL NUMBER:

25N3672WSUW M V X D1B461 X HN
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS			A	KW	CARTONED WEIGHT	CUBIC FEET
			D	W	H				
U-SHAPED WORKSURFACE 	SOFTENED RIM								
	25N3672WSUW	Wood	\$ 1560	36 ³ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	90 lbs. 3.8
	25N3672WSUL	Laminate	854	36 ³ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	90 lbs. 3.8
	25N3072WSUW	Wood	\$ 1368	30 ³ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	76 lbs. 3.6
	25N3072WSUL	Laminate	656	30 ³ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	76 lbs. 3.6
	25N3066WSUW	Wood	\$ 1291	30 ³ / ₁₆	66	1 ³ / ₁₆	—	—	70 lbs. 3.3
	25N3066WSUL	Laminate	584	30 ³ / ₁₆	66	1 ³ / ₁₆	—	—	70 lbs. 3.3
	25N2460WSUW	Wood	\$ 841	24	60	1 ³ / ₁₆	—	—	69 lbs. 2.8
	25N2460WSUL	Laminate	469	24	60	1 ³ / ₁₆	—	—	69 lbs. 2.8
	25N2448WSUW	Wood	\$ 742	24	48	1 ³ / ₁₆	—	—	57 lbs. 2.3
	25N2448WSUL	Laminate	412	24	48	1 ³ / ₁₆	—	—	57 lbs. 2.3

- To add full modesty panel, specify a panel that is 18" shorter than the width of the top; end panel, support base, and support base bracket must also be ordered; see page 210 for support base bracket
- Wire Manager available on back, the straight edge of the worksurface; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Worksurfaces can be ordered in ¹/₁₆" increments in width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired width
- Modified depth not available on this shape
- For undersurface wire managers, see page 741
- Not recommended for use with Epicenter slat wall

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories

TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminate models)
5. Grommet
6. Wire Manager
7. Modified Width
8. Veneer Top Finish/Laminate Top Color

SAMPLE MODEL NUMBER:

25N3974WSUWK1 M V X D1B461 X HN
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED CUBIC		
			D	W	H	A	KW	WEIGHT	FEET	
U-SHAPED WORKSURFACE (CONTINUED) 	KNIFE RIM									
	25N3974WSUWK1	Wood	\$ 2031	39 ³ / ₁₆	73 ³ / ₁₆	1 ³ / ₁₆	—	—	95 lbs.	4.0
	25N3974WSULK1	Laminate	1322	39 ³ / ₁₆	73 ³ / ₁₆	1 ³ / ₁₆	—	—	95 lbs.	4.0
	25N3374WSUWK1	Wood	\$ 1775	33 ³ / ₁₆	73 ³ / ₁₆	1 ³ / ₁₆	—	—	80 lbs.	3.8
	25N3374WSULK1	Laminate	1017	33 ³ / ₁₆	73 ³ / ₁₆	1 ³ / ₁₆	—	—	80 lbs.	3.8
	25N3368WSUWK1	Wood	\$ 1676	33 ³ / ₁₆	67 ¹ / ₂	1 ³ / ₁₆	—	—	74 lbs.	3.5
	25N3368WSULK1	Laminate	904	33 ³ / ₁₆	67 ¹ / ₂	1 ³ / ₁₆	—	—	74 lbs.	3.5
	25N2762WSUWK1	Wood	\$ 1091	27	61 ¹ / ₂	1 ³ / ₁₆	—	—	72 lbs.	2.9
	25N2762WSULK1	Laminate	728	27	61 ¹ / ₂	1 ³ / ₁₆	—	—	72 lbs.	2.9
	25N2750WSUWK1	Wood	\$ 965	27	49 ¹ / ₂	1 ³ / ₁₆	—	—	60 lbs.	2.4
	25N2750WSULK1	Laminate	641	27	49 ¹ / ₂	1 ³ / ₁₆	—	—	60 lbs.	2.4

- To add full modesty panel, specify a panel that is 18" shorter than the width of the top; end panel, support base, and support base bracket must also be ordered; see page 210 for support base bracket
- Wire Manager available on back, the straight edge of the worksurface; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Worksurfaces can be ordered in ¹/₁₆" increments in width to next smallest available size at no upcharge
- When ordering a worksurface with a size modification, specify desired width
- Modified depth not available on this shape
- For undersurface wire managers, see page 741
- Not recommended for use with Epicenter slat wall

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories


TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminate models)
5. Grommet
6. Wire Manager
7. Modified Width
8. Veneer Top Finish/Laminate Top Color

SAMPLE MODEL NUMBERS:


25N3672WSUERW2 M V X X MC
 25N3072WSPLL E VCW G1C D1B485 70.5 CW

• See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS					CARTONED CUBIC		
				D	W	H	A	KW	WEIGHT	FEET	
EXTENDED U-SHAPED WORKSURFACE 	SOFTENED RIM										
	LEFT	RIGHT									
	25N3672WSUELW2	25N3672WSUERW2	Wood	\$ 1578	36 ¹ / ₁₆	71 ¹ / ₁₆	1 ¹ / ₁₆	—	—	90 lbs.	3.8
	25N3672WSUELL2	25N3672WSUERL2	Laminate	1008	36 ¹ / ₁₆	71 ¹ / ₁₆	1 ¹ / ₁₆	—	—	90 lbs.	3.8
	25N3672WSUELW3	25N3672WSUERW3	Wood	\$ 1631	36 ¹ / ₁₆	71 ¹ / ₁₆	1 ¹ / ₁₆	—	—	90 lbs.	3.8
	25N3672WSUELL3	25N3672WSUERL3	Laminate	1046	36 ¹ / ₁₆	71 ¹ / ₁₆	1 ¹ / ₁₆	—	—	90 lbs.	3.8
	KNIFE RIM										
	LEFT	RIGHT									
25N3874WSUELW2K1	25N3874WSUERW2K1	Wood	\$ 2051	37 ⁷ / ₁₆	73 ⁷ / ₁₆	1 ¹ / ₁₆	—	—	95 lbs.	4.0	
25N3874WSUELL2K1	25N3874WSUERL2K1	Laminate	1562	37 ⁷ / ₁₆	73 ⁷ / ₁₆	1 ¹ / ₁₆	—	—	95 lbs.	4.0	
25N3874WSUELW3K1	25N3874WSUERW3K1	Wood	\$ 2120	37 ⁷ / ₁₆	73 ⁷ / ₁₆	1 ¹ / ₁₆	—	—	95 lbs.	4.0	
25N3874WSUELL3K1	25N3874WSUERL3K1	Laminate	1621	37 ⁷ / ₁₆	73 ⁷ / ₁₆	1 ¹ / ₁₆	—	—	95 lbs.	4.0	

- Wire Manager available on back; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Modified depth and width not available on this shape
- For undersurface wire managers, see page 741
- Not recommended for use with Epicenter slat wall
- Models ending in 2 – utilize with 24" deep worksurfaces
- Models ending in 3 – utilize with 30" deep worksurfaces

P-SHAPED WORKSURFACE



Right shown

SOFTENED RIM										
LEFT	RIGHT									
25N3072WSPLW	25N3072WSPRW	Wood	\$ 1637	30 ³ / ₁₆	71 ¹ / ₁₆	1 ¹ / ₁₆	—	—	69 lbs.	3.6
25N3072WSPLL	25N3072WSPRL	Laminate	1132	30 ³ / ₁₆	71 ¹ / ₁₆	1 ¹ / ₁₆	—	—	69 lbs.	3.6
KNIFE RIM										
LEFT	RIGHT									
25N3374WSPLWK1	25N3374WSPRWK1	Wood	\$ 2128	33 ¹ / ₁₆	73 ⁷ / ₁₆	1 ¹ / ₁₆	—	—	72 lbs.	3.8
25N3374WSPLLK1	25N3374WSPRLK1	Laminate	1753	33 ¹ / ₁₆	73 ⁷ / ₁₆	1 ¹ / ₁₆	—	—	72 lbs.	3.8

- To add full modesty panel, specify a panel that is 18" shorter than the width of the top, end panel, support base, and support base bracket must also be ordered; see page 210 for support base bracket
- Wire Manager available on back, the straight edge of the worksurface; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Worksurfaces can be ordered in 1/8" increments in width to a minimum of 59 1/8" at no upcharge
- When ordering a worksurface with a size modification, specify desired width
- Modified depth not available on this shape
- For undersurface wire managers, see page 741
- Not recommended for use with Epicenter slat wall

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories

TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminite models)
5. Grommet
6. Wire Manager
7. Modified Width
8. Veneer Top Finish/Laminite Top Color

SAMPLE MODEL NUMBER:

25N3672WSPERW2 M V X X MC

- See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED CUBIC			
			D	W	H	A	KW	WEIGHT	FEET		
<p>EXTENDED CORNER P-SHAPED WORKSURFACE</p> <p>Left shown</p>	SOFTENED RIM										
		LEFT	RIGHT								
	25N3672WSPELW2	25N3672WSPERW2	Wood	\$ 1836	35 ³ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	73 lbs.	4.9
	25N3672WSPELL2	25N3672WSPERL2	Laminite	1277	35 ³ / ₁₆	71 ¹ / ₁₆	1 ³ / ₁₆	—	—	73 lbs.	4.9
	25N3672WSPELW3	25N3672WSPERW3	Wood	\$ 1890	35 ³ / ₁₆	73 ⁷ / ₁₆	1 ³ / ₁₆	—	—	73 lbs.	4.9
	25N3672WSPELL3	25N3672WSPERL3	Laminite	1317	35 ³ / ₁₆	73 ⁷ / ₁₆	1 ³ / ₁₆	—	—	73 lbs.	4.9
		KNIFE RIM									
		LEFT	RIGHT								
	25N3874WSPELW2K1	25N3874WSPERW2K1	Wood	\$ 2385	37 ⁹ / ₁₆	73 ⁷ / ₁₆	1 ³ / ₁₆	—	—	77 lbs.	5.1
	25N3874WSPELL2K1	25N3874WSPERL2K1	Laminite	1983	37 ⁹ / ₁₆	73 ⁷ / ₁₆	1 ³ / ₁₆	—	—	77 lbs.	5.1
	25N3874WSPELW3K1	25N3874WSPERW3K1	Wood	\$ 2458	37 ⁹ / ₁₆	73 ⁷ / ₁₆	1 ³ / ₁₆	—	—	77 lbs.	5.1
	25N3874WSPELL3K1	25N3874WSPERL3K1	Laminite	2043	37 ⁹ / ₁₆	73 ⁷ / ₁₆	1 ³ / ₁₆	—	—	77 lbs.	5.1

- Models ending in 2 - utilize with 24" deep worksurfaces
- Models ending in 3 - utilize with 30" deep worksurfaces
- To add full modesty panel, specify a panel that is 18" shorter than the width of the top; end panel, support base, and support base bracket must also be ordered; see page 210 for support base bracket
- Wire Manager available on back, the straight edge of the worksurface; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Modified depth and width not available on this shape
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on user side (indicated by K1)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories


TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminite models)
5. Grommet
6. Wire Manager
7. Veneer Top Finish/Laminite Top Color

SAMPLE MODEL NUMBER:

25N4242WSCSW2 V G1C X MC

- See pages 95-99 for all options available in Epic

CORNER WORKSURFACE	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
			D	W	H	A	KW			
 <p>Grain direction runs diagonally</p>	SOFTENED RIM									
	25N4242WSCSW2	Wood	\$ 1134	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	59 lbs.	3.8
	25N4242WSCSL2	Laminate	712	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	59 lbs.	3.8
	25N4242WSCSW3	Wood	\$ 1248	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	59 lbs.	3.8
	25N4242WSCSL3	Laminate	785	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	59 lbs.	3.8
	25N4242WSCSW7	Wood	\$ 1248	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	59 lbs.	3.8
	25N4242WSCSL7	Laminate	785	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	59 lbs.	3.8
	25N4242WSCSW9	Wood	\$ 1248	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	59 lbs.	3.8
	25N4242WSCSL9	Laminate	785	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	59 lbs.	3.8
	25N3636WSCSW2	Wood	\$ 1044	36 ¹ / ₁₆	36 ¹ / ₁₆	1 ³ / ₁₆	—	—	45 lbs.	3.8
	25N3636WSCSL2	Laminate	654	36 ¹ / ₁₆	36 ¹ / ₁₆	1 ³ / ₁₆	—	—	45 lbs.	3.8

- Grain direction runs diagonally
- Will accommodate 24" deep extension worksurfaces on both sides
- Models ending in 2 - utilize with 24" deep worksurfaces
- Models ending in 3 - utilize with 30" deep worksurfaces
- Models ending in 7 - utilize with 1 left 30" deep and 1 right 24" deep worksurfaces
- Models ending in 9 - utilize with 1 left 24" deep and 1 right 30" deep worksurfaces
- 42" corner worksurfaces have 25" on front edge
- 36" corner worksurfaces have 17" on front edge
- Corner worksurface assembled to corner unit is not intended for freestanding unit
- Wire Manager available on left side, right side or left & right sides; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Modified depth and width not available on this shape
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories


TO ORDER, SPECIFY:

1. Model Number
2. Rim Profile
3. PVC Rim Color (laminite models)
4. Grommet
5. Wire Manager
6. Veneer Top Finish/Laminate Top Color

SAMPLE MODEL NUMBER:

25N4242WSCSW2K1 K G1C X CL

- See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED CUBIC		
			D	W	H	A	KW	WEIGHT	FEET	
<p>CORNER WORKSURFACE (CONTINUED)</p>  <p>Grain direction runs diagonally</p>	KNIFE RIM									
	25N4242WSCSW2K1	Wood	\$ 1475	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	62 lbs.	4.0
	25N4242WCSL2K1	Laminate	1107	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	62 lbs.	4.0
	25N4242WSCSW3K1	Wood	\$ 1623	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	62 lbs.	4.0
	25N4242WCSL3K1	Laminate	1218	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	62 lbs.	4.0
	25N4242WSCSW7K1	Wood	\$ 1623	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	62 lbs.	4.0
	25N4242WCSL7K1	Laminate	1218	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	62 lbs.	4.0
	25N4242WSCSW9K1	Wood	\$ 1623	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	62 lbs.	4.0
	25N4242WCSL9K1	Laminate	1218	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	62 lbs.	4.0
	25N3636WSCSW2K1	Wood	\$ 1355	36 ¹ / ₁₆	36 ¹ / ₁₆	1 ³ / ₁₆	—	—	47 lbs.	4.0
	25N3636WCSL2K1	Laminate	1015	36 ¹ / ₁₆	36 ¹ / ₁₆	1 ³ / ₁₆	—	—	47 lbs.	4.0

- Grain direction runs diagonally
- Will accommodate 24" deep extension worksurfaces on both sides
- Models ending in 2 - utilize with 24" deep worksurfaces
- Models ending in 3 - utilize with 30" deep worksurfaces
- Models ending in 7 - utilize with 1 left 30" deep and 1 right 24" deep worksurfaces
- Models ending in 9 - utilize with 1 left 24" deep and 1 right 30" deep worksurfaces
- 42" corner worksurfaces have 25" on front edge
- 36" corner worksurfaces have 17" on front edge
- Corner worksurface assembled to corner unit is not intended for freestanding unit
- Wire Manager available on left side, right side or left & right sides; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Modified depth and width not available on this shape
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Knife rim profile (wood or laminate) available on user side (indicated by K1) or user and approach side (indicated by K2)
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories

TO ORDER, SPECIFY:

1. Model Number
2. Rim Profile
3. PVC Rim Color (laminate models)
4. Grommet
5. Wire Manager
6. Veneer Top Finish/Laminate Top Color

SAMPLE MODEL NUMBER:

25N60WSHRL VCL G1C D1B405 CL
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
			D	W	H	A	KW			
HALF-ROUND WORKSURFACE 	SOFTENED RIM									
	25N60WSHRW	Wood	\$ 804	30	60	1 ³ / ₁₆	—	—	69 lbs.	2.8
	25N60WSHRL	Laminate	460	30	60	1 ³ / ₁₆	—	—	69 lbs.	2.8
	25N48WSHRW	Wood	\$ 668	24	48 ³ / ₁₆	1 ³ / ₁₆	—	—	57 lbs.	2.3
	25N48WSHRL	Laminate	384	24	48 ³ / ₁₆	1 ³ / ₁₆	—	—	57 lbs.	2.3
	KNIFE RIM									
	25N63WSHRWK1	Wood	\$ 1043	31 ¹ / ₂	63	1 ³ / ₁₆	—	—	72 lbs.	2.9
	25N63WSHRLK1	Laminate	710	31 ¹ / ₂	63	1 ³ / ₁₆	—	—	72 lbs.	2.9
	25N51WSHRWK1	Wood	\$ 867	25 ¹ / ₂	51 ¹ / ₁₆	1 ³ / ₁₆	—	—	60 lbs.	2.4
	25N51WSHRLK1	Laminate	595	25 ¹ / ₂	51 ¹ / ₁₆	1 ³ / ₁₆	—	—	60 lbs.	2.4

- Rim profile on radius edge of surface only
- Only available grommet option is center location
- Wire Manager available on back side-the straight side of the worksurface; see page 96 for wire manager colors and upcharge
- When ordering a wire manager, a wire manager filler can be ordered separately; see page 210
- Modified depth and width not available on this shape
- For undersurface wire managers, see page 741

PRODUCT SPECIFICATIONS

- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on all 4 sides for round tops
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories


TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminate models)
5. Grommet
6. Veneer Top Finish/Laminate Top Color

SAMPLE MODEL NUMBER:

25N48WSRNL VCL G1C CL

- See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
			D	W	H	A	KW			
ROUND TABLE TOP 	SOFTENED RIM		DI	H						
	25N48WSRNW	Wood	\$ 1046	48 $\frac{1}{16}$	—	1 $\frac{3}{16}$	—	—	71 lbs.	4.5
	25N48WSRNL	Laminate	508	48 $\frac{1}{16}$	—	1 $\frac{3}{16}$	—	—	71 lbs.	4.5
	25N42WSRNW	Wood	\$ 927	42 $\frac{1}{16}$	—	1 $\frac{3}{16}$	—	—	54 lbs.	3.8
	25N42WSRNL	Laminate	435	42 $\frac{1}{16}$	—	1 $\frac{3}{16}$	—	—	54 lbs.	3.8
	25N36WSRNW	Wood	\$ 777	36 $\frac{1}{16}$	—	1 $\frac{3}{16}$	—	—	40 lbs.	3.0
	25N36WSRNL	Laminate	337	36 $\frac{1}{16}$	—	1 $\frac{3}{16}$	—	—	40 lbs.	3.0
	25N30WSRNW	Wood	\$ 658	30 $\frac{1}{16}$	—	1 $\frac{3}{16}$	—	—	33 lbs.	2.0
	25N30WSRNL	Laminate	287	30 $\frac{1}{16}$	—	1 $\frac{3}{16}$	—	—	33 lbs.	2.0
	KNIFE RIM									
	25N48WSRNWK1	Wood	\$ 1360	48 $\frac{1}{16}$	—	1 $\frac{3}{16}$	—	—	75 lbs.	4.7
	25N48WSRNLK1	Laminate	786	48 $\frac{1}{16}$	—	1 $\frac{3}{16}$	—	—	75 lbs.	4.7
	25N42WSRNWK1	Wood	\$ 1204	42 $\frac{1}{16}$	—	1 $\frac{3}{16}$	—	—	57 lbs.	4.0
	25N42WSRNLK1	Laminate	677	42 $\frac{1}{16}$	—	1 $\frac{3}{16}$	—	—	57 lbs.	4.0
25N36WSRNWK1	Wood	\$ 1008	36 $\frac{1}{16}$	—	1 $\frac{3}{16}$	—	—	42 lbs.	3.2	
25N36WSRNLK1	Laminate	523	36 $\frac{1}{16}$	—	1 $\frac{3}{16}$	—	—	42 lbs.	3.2	
25N30WSRNWK1	Wood	\$ 859	30 $\frac{1}{16}$	—	1 $\frac{3}{16}$	—	—	33 lbs.	2.0	
25N30WSRNLK1	Laminate	445	30 $\frac{1}{16}$	—	1 $\frac{3}{16}$	—	—	33 lbs.	2.0	

- Reference pages 641-644 for applicable bases
- Do not specify worksurface type
- (K1) knife edge on all 4 sides

PRODUCT SPECIFICATIONS


- Worksurfaces shipped with appropriate hardware by specifying worksurface type; see the specification guide for details
- Rim on all 4 sides of (wood or laminate) softened rim worksurfaces; unless a wire manager is specified then the rim would only be where the wire manager is not located
- Knife rim profile (wood or laminate) available on all 4 sides
- If specifying wood, you must specify the same finish for all options
- Component worksurfaces can be used with assembled units
- Refer to page 100 for grommet locations; and page 98 for grommet upcharge
- Unsupported worksurface spans should not exceed 48"; see page 207 for support options
- Refer to pages 717-760 for accessories

TO ORDER, SPECIFY:

1. Model Number
2. Worksurface Type
3. Rim Profile
4. PVC Rim Color (laminate models)
5. Grommet
6. Veneer Top Finish/Laminate Top Color

SAMPLE MODEL NUMBER:

25N4848WSSQL M VCL G1C CL
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
			D	W	H	A	KW			
<p>SQUARE TABLE TOP</p> 	SOFTENED RIM									
	25N4848WSSQW	Wood	\$ 1030	48 ¹ / ₁₆	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	76 lbs.	4.5
	25N4848WSSQL	Laminate	496	48 ¹ / ₁₆	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	76 lbs.	4.5
	25N4242WSSQW	Wood	\$ 907	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	59 lbs.	3.8
	25N4242WSSQL	Laminate	432	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	59 lbs.	3.8
	25N3636WSSQW	Wood	\$ 766	36 ¹ / ₁₆	36 ¹ / ₁₆	1 ³ / ₁₆	—	—	45 lbs.	3.0
	25N3636WSSQL	Laminate	331	36 ¹ / ₁₆	36 ¹ / ₁₆	1 ³ / ₁₆	—	—	45 lbs.	3.0
	25N3030WSSQW	Wood	\$ 652	30 ¹ / ₁₆	30 ¹ / ₁₆	1 ³ / ₁₆	—	—	33 lbs.	2.0
	25N3030WSSQL	Laminate	281	30 ¹ / ₁₆	30 ¹ / ₁₆	1 ³ / ₁₆	—	—	33 lbs.	2.0
	KNIFE RIM									
	25N4848WSSQWK1	Wood	\$ 1340	48 ¹ / ₁₆	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	80 lbs.	4.7
	25N4848WSSQLK1	Laminate	770	48 ¹ / ₁₆	48 ¹ / ₁₆	1 ³ / ₁₆	—	—	80 lbs.	4.7
	25N4242WSSQWK1	Wood	\$ 1180	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	62 lbs.	4.0
	25N4242WSSQLK1	Laminate	669	42 ¹ / ₁₆	42 ¹ / ₁₆	1 ³ / ₁₆	—	—	62 lbs.	4.0
	25N3636WSSQWK1	Wood	\$ 997	36 ¹ / ₁₆	36 ¹ / ₁₆	1 ³ / ₁₆	—	—	47 lbs.	3.2
	25N3636WSSQLK1	Laminate	511	36 ¹ / ₁₆	36 ¹ / ₁₆	1 ³ / ₁₆	—	—	47 lbs.	3.2
	25N3030WSSQWK1	Wood	\$ 847	30 ¹ / ₁₆	30 ¹ / ₁₆	1 ³ / ₁₆	—	—	33 lbs.	2.0
	25N3030WSSQLK1	Laminate	434	30 ¹ / ₁₆	30 ¹ / ₁₆	1 ³ / ₁₆	—	—	33 lbs.	2.0

- Reference pages 641-644 for applicable bases
- (K1) knife edge on all 4 sides

PRODUCT SPECIFICATIONS





- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 210) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended

TO ORDER, SPECIFY:

1. Model Number
2. Pull
3. Pedestal Grommet
4. Locking
5. Foot Color
6. Laminate Door/Drawer Color
7. Veneer Chassis Finish/
Laminate Chassis Color

SAMPLE MODEL NUMBER:

25N291829PUBBFL 89MB KRB G22 FR462 405 MH
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS					CARTONED CUBIC	
				D	W	H	A	KW	WEIGHT	FEET
 <p>PEDESTAL - UNDERSURFACE BOX/BOX/FILE 29" DEEP</p>	25N291829PUBBFW	Wood	\$ 1692	28 ⁷ / ₈	17 ¹ / ₂	27 ³ / ₄	—	—	95 lbs.	10.6
	25N291829PUBBFL	Laminate	1061	28 ⁷ / ₈	17 ¹ / ₂	27 ³ / ₄	—	—	95 lbs.	10.6
	25N291529PUBBFW	Wood	\$ 1594	28 ⁷ / ₈	14 ¹ / ₂	27 ³ / ₄	—	—	83 lbs.	8.5
	25N291529PUBBFL	Laminate	1002	28 ⁷ / ₈	14 ¹ / ₂	27 ³ / ₄	—	—	83 lbs.	8.5
	<ul style="list-style-type: none"> • Specify component worksurfaces and backs to finish as needed • Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available • Not intended for use in a freestanding application 									
 <p>PEDESTAL - UNDERSURFACE BOX/BOX/FILE 23" DEEP</p>	25N231829PUBBFW	Wood	\$ 1586	22 ¹ / ₂	17 ¹ / ₂	27 ³ / ₄	—	—	75 lbs.	11.4
	25N231829PUBBFL	Laminate	997	22 ¹ / ₂	17 ¹ / ₂	27 ³ / ₄	—	—	75 lbs.	11.4
	25N231529PUBBFW	Wood	\$ 1499	22 ¹ / ₂	14 ¹ / ₂	27 ³ / ₄	—	—	70 lbs.	9.9
	25N231529PUBBFL	Laminate	937	22 ¹ / ₂	14 ¹ / ₂	27 ³ / ₄	—	—	70 lbs.	9.9
	<ul style="list-style-type: none"> • Specify component worksurfaces and backs to finish as needed • Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available • Not intended for use in a freestanding application 									
 <p>PEDESTAL - UNDERSURFACE BOX/BOX/FILE 17" DEEP</p>	25N171829PUBBFW	Wood	\$ 1586	16 ¹ / ₂	17 ¹ / ₂	27 ³ / ₄	—	—	50 lbs.	9.1
	25N171829PUBBFL	Laminate	997	16 ¹ / ₂	17 ¹ / ₂	27 ³ / ₄	—	—	50 lbs.	9.1
	25N171529PUBBFW	Wood	\$ 1499	16 ¹ / ₂	14 ¹ / ₂	27 ³ / ₄	—	—	49 lbs.	8.1
	25N171529PUBBFL	Laminate	937	16 ¹ / ₂	14 ¹ / ₂	27 ³ / ₄	—	—	49 lbs.	8.1
	<ul style="list-style-type: none"> • Specify component worksurfaces and backs to finish as needed • Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available • Not intended for use in a freestanding application 									
 <p>PEDESTAL - UNDERSURFACE FILE/FILE 29" DEEP</p>	25N291829PUFFW	Wood	\$ 1692	28 ⁷ / ₈	17 ¹ / ₂	27 ³ / ₄	—	—	95 lbs.	10.6
	25N291829PUFFL	Laminate	1061	28 ⁷ / ₈	17 ¹ / ₂	27 ³ / ₄	—	—	95 lbs.	10.6
	25N291529PUFFW	Wood	\$ 1594	28 ⁷ / ₈	14 ¹ / ₂	27 ³ / ₄	—	—	83 lbs.	8.5
	25N291529PUFFL	Laminate	1002	28 ⁷ / ₈	14 ¹ / ₂	27 ³ / ₄	—	—	83 lbs.	8.5
	<ul style="list-style-type: none"> • Specify component worksurfaces and backs to finish as needed • Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available • Not intended for use in a freestanding application 									

PRODUCT SPECIFICATIONS


- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 210) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended

TO ORDER, SPECIFY:


1. Model Number
2. Pull
3. Pedestal Grommet
4. Locking
5. Foot Color
6. Laminate Door/Drawer Color
7. Veneer Chassis Finish/
Laminate Chassis Color

SAMPLE MODEL NUMBER:


25N351829SESLW G22 FR462 MH
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
			D	W	H	A	KW		
 <p>PEDESTAL - UNDERSURFACE FILE/FILE 23" DEEP</p>	25N231829PUFFW Wood	\$ 1586	22 ¹ / ₁₆	17 ¹ / ₁₆	27 ³ / ₄	—	—	75 lbs.	11.4
	25N231829PUFFL Laminate	997	22 ¹ / ₁₆	17 ¹ / ₁₆	27 ³ / ₄	—	—	75 lbs.	11.4
	25N231529PUFFW Wood	\$ 1499	22 ¹ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	—	—	70 lbs.	9.9
	25N231529PUFFL Laminate	937	22 ¹ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	—	—	70 lbs.	9.9

• Specify component worksurfaces and backs to finish as needed
 • Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
 • Not intended for use in a freestanding application

 <p>PEDESTAL - UNDERSURFACE FILE/FILE 17" DEEP</p>	25N171829PUFFW Wood	\$ 1586	16 ¹ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	—	—	50 lbs.	9.1
	25N171829PUFFL Laminate	997	16 ¹ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	—	—	50 lbs.	9.1
	25N171529PUFFW Wood	\$ 1499	16 ¹ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	—	—	49 lbs.	8.1
	25N171529PUFFL Laminate	937	16 ¹ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	—	—	49 lbs.	8.1

• Specify component worksurfaces and backs to finish as needed
 • Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
 • Not intended for use in a freestanding application

	SUPPORT PEDESTAL		LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
	LEFT	RIGHT		D	W	H	A	KW			
	25N351829SESLW	25N351829SESRL	Wood	\$ 1170	35 ⁷ / ₁₆	17 ¹ / ₁₆	27 ³ / ₄	—	—	101 lbs.	11.1
	25N351829SESLW	25N351829SESRL	Laminate	722	35 ⁷ / ₁₆	17 ¹ / ₁₆	27 ³ / ₄	—	—	101 lbs.	11.1
	25N351529SESLW	25N351529SESRL	Wood	\$ 1107	35 ⁷ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	—	—	89 lbs.	9.1
	25N351529SESLW	25N351529SESRL	Laminate	681	35 ⁷ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	—	—	89 lbs.	9.1
	25N291829SESLW	25N291829SESRL	Wood	\$ 1101	28 ⁷ / ₁₆	17 ¹ / ₁₆	27 ³ / ₄	—	—	95 lbs.	10.6
	25N291829SESLW	25N291829SESRL	Laminate	679	28 ⁷ / ₁₆	17 ¹ / ₁₆	27 ³ / ₄	—	—	95 lbs.	10.6
	25N291529SESLW	25N291529SESRL	Wood	\$ 1038	28 ⁷ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	—	—	83 lbs.	8.5
	25N291529SESLW	25N291529SESRL	Laminate	641	28 ⁷ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	—	—	83 lbs.	8.5
	25N231829SESLW	25N231829SESRL	Wood	\$ 1031	22 ¹ / ₁₆	17 ¹ / ₁₆	27 ³ / ₄	—	—	95 lbs.	10.6
	25N231829SESLW	25N231829SESRL	Laminate	640	22 ¹ / ₁₆	17 ¹ / ₁₆	27 ³ / ₄	—	—	95 lbs.	10.6
	25N231529SESLW	25N231529SESRL	Wood	\$ 976	22 ¹ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	—	—	83 lbs.	8.5
	25N231529SESLW	25N231529SESRL	Laminate	597	22 ¹ / ₁₆	14 ¹ / ₁₆	27 ³ / ₄	—	—	83 lbs.	8.5

• Specify component worksurfaces and backs to finish as needed
 • For use when creating single pedestal desks from components or with U-surfaces or P-surfaces
 • Not intended for use in a freestanding application

PRODUCT SPECIFICATIONS

- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 210) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended


TO ORDER, SPECIFY:

1. Model Number
2. Pull
3. Pedestal Grommet
4. Locking
5. Foot Color
6. Laminate Door/Drawer Color
7. Veneer Chassis Finish/
Laminate Chassis Color

SAMPLE MODEL NUMBER:

25N2336LFM2L 89MB KRB X FR462 CW CW
 • See pages 95-99 for all options available in Epic


**LATERAL FILE UNIT
UNDERSURFACE -
2 DRAWER**



MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS					CARTONED CUBIC	
			D	W	H	A	KW	WEIGHT	FEET
23" DEPTH									
25N2336LFM2W	Wood	\$ 2020	22 ¹ / ₁₆	35 ⁵ / ₁₆	27 ³ / ₄	—	—	120 lbs.	20.4
25N2336LFM2L	Laminate	1119	22 ¹ / ₁₆	35 ⁵ / ₁₆	27 ³ / ₄	—	—	120 lbs.	20.4
17" DEPTH									
25N1736LFM2W	Wood	\$ 2020	16 ¹ / ₁₆	35 ⁵ / ₁₆	27 ³ / ₄	—	—	119 lbs.	16.3
25N1736LFM2L	Laminate	1119	16 ¹ / ₁₆	35 ⁵ / ₁₆	27 ³ / ₄	—	—	119 lbs.	16.3
25N1730LFM2W	Wood	\$ 1862	16 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	102 lbs.	13.7
25N1730LFM2L	Laminate	1089	16 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	102 lbs.	13.7

- Specify component worksurfaces and backs to finish as needed
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
- When specifying Horizon pulls, lateral files will have 2 pulls on each drawer front

**LATERAL FILE UNIT
UNDERSURFACE -
3 DRAWER**



25N2436LFM3W	Wood	\$ 3643	23 ³ / ₁₆	35 ⁵ / ₁₆	40 ¹ / ₁₆	—	—	210 lbs.	30.0
25N2436LFM3L	Laminate	2330	23 ³ / ₁₆	35 ⁵ / ₁₆	40 ¹ / ₁₆	—	—	210 lbs.	30.0
25N2430LFM3W	Wood	\$ 3460	23 ³ / ₁₆	29 ¹ / ₁₆	40 ¹ / ₁₆	—	—	210 lbs.	30.0
25N2430LFM3L	Laminate	2213	23 ³ / ₁₆	29 ¹ / ₁₆	40 ¹ / ₁₆	—	—	210 lbs.	30.0

- Top of unit is finished with flat edge detail
- Interlock mechanism allows only 1 drawer to be open at a time
- For use with component common top when ganging units together
- Unit has full finished back
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
- When specifying Horizon pulls, lateral files will have 2 pulls on each drawer front

PRODUCT SPECIFICATIONS

- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 210) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended


TO ORDER, SPECIFY:

1. Model Number
2. Pull
3. Pedestal Grommet
4. Locking
5. Foot Color
6. Laminate Door/Drawer Color
7. Veneer Chassis Finish/
Laminate Chassis Color

SAMPLE MODEL NUMBER:


25N2436LFM4L 89MB KS1B FR462 2977 480 462
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
				D	W	H	A	KW		
LATERAL FILE UNIT UNDERSURFACE - 4 DRAWER	25N2436LFM4W	Wood	\$ 4235	23 ³ / ₁₆	35 ⁵ / ₁₆	52 ¹ / ₁₆	—	—	265 lbs.	33.4
	25N2436LFM4L	Laminate	2680	23 ³ / ₁₆	35 ⁵ / ₁₆	52 ¹ / ₁₆	—	—	265 lbs.	33.4
	25N2430LFM4W	Wood	\$ 4022	23 ³ / ₁₆	29 ¹ / ₁₆	52 ¹ / ₁₆	—	—	265 lbs.	33.4
	25N2430LFM4L	Laminate	2547	23 ³ / ₁₆	29 ¹ / ₁₆	52 ¹ / ₁₆	—	—	265 lbs.	33.4



- Top of unit is finished with flat edge detail
- Interlock mechanism allows only 1 drawer to be open at a time
- For use with component common top when ganging units together
- Unit has full finished back
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
- When specifying Horizon pulls, lateral files will have 2 pulls on each drawer front

**DOUBLE DOOR UNIT
UNDERSURFACE**



		23" DEPTH								
				D	W	H	A	KW	CARTONED WEIGHT	CUBIC FEET
25N233629PUHW	Wood	\$ 1618		22 ¹ / ₁₆	35 ⁵ / ₁₆	27 ³ / ₄	—	—	110 lbs.	20.4
25N233629PUHL	Laminate	973		22 ¹ / ₁₆	35 ⁵ / ₁₆	27 ³ / ₄	—	—	110 lbs.	20.4
25N233029PUHW	Wood	\$ 1460		22 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	91 lbs.	17.4
25N233029PUHL	Laminate	918		22 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	91 lbs.	17.4
25N232429PUHW	Wood	\$ 1403		22 ¹ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	80 lbs.	16.0
25N232429PUHL	Laminate	862		22 ¹ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	80 lbs.	16.0

		17" DEPTH								
				D	W	H	A	KW	CARTONED WEIGHT	CUBIC FEET
25N173629PUHW	Wood	\$ 1618		16 ¹ / ₁₆	35 ⁵ / ₁₆	27 ³ / ₄	—	—	119 lbs.	16.3
25N173629PUHL	Laminate	973		16 ¹ / ₁₆	35 ⁵ / ₁₆	27 ³ / ₄	—	—	119 lbs.	16.3
25N173029PUHW	Wood	\$ 1460		16 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	90 lbs.	13.7
25N173029PUHL	Laminate	918		16 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	90 lbs.	13.7
25N172429PUHW	Wood	\$ 1403		16 ¹ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	75 lbs.	10.8
25N172429PUHL	Laminate	862		16 ¹ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	75 lbs.	10.8

- Specify component worksurfaces and backs to finish as needed
- Unit features an adjustable shelf
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available

PRODUCT SPECIFICATIONS


- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 210) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended
- Sliding doors feature a face mount powder coated aluminum track on top and bottom of cabinet

TO ORDER, SPECIFY:

1. Model Number
2. Pull
3. Pedestal Grommet
4. Locking
5. Resin Grade/Door Color
6. Metal Door Color
7. Foot Color
8. Laminate Door/Drawer Color
9. Veneer Chassis Finish/
Laminate Chassis Color
10. Door Track Paint Color

SAMPLE MODEL NUMBER:

25N233629PUSAW G22 2 FR462 FR462 MH 501
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE			DIMENSIONS					CARTONED CUBIC		
					D	W	H	A	KW	WEIGHT	FEET	
DOUBLE DOOR UNIT SLIDING DOORS UNDERSURFACE 	RESIN DOORS											
	23" DEPTH				GRADE 1	GRADE 2	GRADE 3					
	25N233629PUSAW	Wood	\$ 2758	\$ 3076	\$ 3193	22 ¹ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	110 lbs.	20.4
	25N233629PUSAL	Laminate	1679	1997	2114	22 ¹ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	110 lbs.	20.4
	<hr/>											
	25N233029PUSAW	Wood	\$ 2642	\$ 2906	\$ 3003	22 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	91 lbs.	17.4
	25N233029PUSAL	Laminate	1584	1848	1945	22 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	91 lbs.	17.4
	<hr/>											
	25N232429PUSAW	Wood	\$ 2539	\$ 2749	\$ 2826	22 ¹ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	80 lbs.	16.0
	25N232429PUSAL	Laminate	1486	1696	1773	22 ¹ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	80 lbs.	16.0
	<hr/>											
	17" DEPTH											
	25N173629PUSAW	Wood	\$ 2758	\$ 3076	\$ 3193	16 ¹ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	119 lbs.	16.3
	25N173629PUSAL	Laminate	1679	1997	2114	16 ¹ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	119 lbs.	16.3
	<hr/>											
	25N173029PUSAW	Wood	\$ 2642	\$ 2906	\$ 3003	16 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	90 lbs.	13.7
	25N173029PUSAL	Laminate	1584	1848	1945	16 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	90 lbs.	13.7
	<hr/>											
25N172429PUSAW	Wood	\$ 2539	\$ 2749	\$ 2826	16 ¹ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	75 lbs.	10.8	
25N172429PUSAL	Laminate	1486	1696	1773	16 ¹ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	75 lbs.	10.8	
<hr/>												
				<ul style="list-style-type: none"> • Specify component worksurfaces and backs to finish as needed • Unit features an adjustable shelf 								

PRODUCT SPECIFICATIONS

- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 210) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended
- Sliding doors feature a face mount powder coated aluminum track on top and bottom of cabinet


TO ORDER, SPECIFY:

1. Model Number
2. Pull
3. Pedestal Grommet
4. Locking
5. Resin Grade/Door Color
6. Metal Door Color
7. Foot Color
8. Laminate Door/Drawer Color
9. Veneer Chassis Finish/
Laminate Chassis Color
10. Door Track Paint Color

SAMPLE MODEL NUMBER:

25N233629PUSMW G22 462 MH 501

- See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
			D	W	H	A	KW			
DOUBLE DOOR UNIT SLIDING DOORS UNDERSURFACE (CONTINUED) 	METAL DOORS 23" DEPTH									
	25N233629PUSMW	Wood	\$ 2758	22 ¹ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	110 lbs.	20.4
	25N233629PUSML	Laminate	1679	22 ¹ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	110 lbs.	20.4
	25N233029PUSMW	Wood	\$ 2642	22 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	91 lbs.	17.4
	25N233029PUSML	Laminate	1584	22 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	91 lbs.	17.4
	25N232429PUSMW	Wood	\$ 2539	22 ¹ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	80 lbs.	16.0
	25N232429PUSML	Laminate	1486	22 ¹ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	80 lbs.	16.0
	17" DEPTH									
	25N173629PUSMW	Wood	\$ 2758	16 ¹ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	119 lbs.	16.3
	25N173629PUSML	Laminate	1679	16 ¹ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	119 lbs.	16.3
	25N173029PUSMW	Wood	\$ 2642	16 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	90 lbs.	13.7
	25N173029PUSML	Laminate	1584	16 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	90 lbs.	13.7
	25N172429PUSMW	Wood	\$ 2539	16 ¹ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	75 lbs.	10.8
	25N172429PUSML	Laminate	1486	16 ¹ / ₁₆	23 ³ / ₄	27 ³ / ₄	—	—	75 lbs.	10.8
<ul style="list-style-type: none"> • Specify component worksurfaces and backs to finish as needed • Unit features an adjustable shelf 										

PRODUCT SPECIFICATIONS

- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 210) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended


TO ORDER, SPECIFY:

1. Model Number
2. Pedestal Grommet
3. Metal Shelf Color
4. Foot Color
5. Veneer Chassis Finish/Laminate Chassis Color

SAMPLE MODEL NUMBER:

25N233629PUOSL G22 501 FR501 MH
 • See pages 95-99 for all options available in Epic

**OPEN BOOKCASE
UNDERSURFACE**



MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
		D	W	H	A	KW		
23" DEPTH								
25N233629PUOSW Wood	\$ 1454	22	35 $\frac{7}{8}$	27 $\frac{3}{4}$	—	—	90 lbs.	20.4
25N233629PUOSL Laminate	876	22	35 $\frac{7}{8}$	27 $\frac{3}{4}$	—	—	90 lbs.	20.4
<hr/>								
25N233029PUOSW Wood	\$ 1389	22	29 $\frac{1}{16}$	27 $\frac{3}{4}$	—	—	85 lbs.	18.0
25N233029PUOSL Laminate	844	22	29 $\frac{1}{16}$	27 $\frac{3}{4}$	—	—	85 lbs.	18.0
<hr/>								
25N232429PUOSW Wood	\$ 1336	22	23 $\frac{3}{4}$	27 $\frac{3}{4}$	—	—	80 lbs.	16.0
25N232429PUOSL Laminate	813	22	23 $\frac{3}{4}$	27 $\frac{3}{4}$	—	—	80 lbs.	16.0
<hr/>								
17" DEPTH								
25N173629PUOSW Wood	\$ 1454	16 $\frac{1}{16}$	35 $\frac{7}{8}$	27 $\frac{3}{4}$	—	—	119 lbs.	16.3
25N173629PUOSL Laminate	876	16 $\frac{1}{16}$	35 $\frac{7}{8}$	27 $\frac{3}{4}$	—	—	119 lbs.	16.3
<hr/>								
25N173029PUOSW Wood	\$ 1389	16 $\frac{1}{16}$	29 $\frac{1}{16}$	27 $\frac{3}{4}$	—	—	90 lbs.	13.7
25N173029PUOSL Laminate	844	16 $\frac{1}{16}$	29 $\frac{1}{16}$	27 $\frac{3}{4}$	—	—	90 lbs.	13.7
<hr/>								
25N172429PUOSW Wood	\$ 1336	16 $\frac{1}{16}$	23 $\frac{3}{4}$	27 $\frac{3}{4}$	—	—	75 lbs.	10.8
25N172429PUOSL Laminate	813	16 $\frac{1}{16}$	23 $\frac{3}{4}$	27 $\frac{3}{4}$	—	—	75 lbs.	10.8

- Specify component worksurfaces and backs to finish as needed
- Unit features an adjustable shelf

PRODUCT SPECIFICATIONS


- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 210) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended

TO ORDER, SPECIFY:


1. Model Number
2. Pull
3. Pedestal Grommet
4. Locking
5. Metal Door or Shelf Color
6. Foot Color
7. Laminate Door/Drawer Color
8. Veneer Chassis Finish/Laminate Chassis Color

SAMPLE MODEL NUMBER:

25N233629PUOSSL G22 501 FR501 MH
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
			D	W	H	A	KW			
 <p>STORAGE CABINET METAL SLIDING SHELVES</p>	25N233629PUOSSW Wood	\$ 2960	22	35 $\frac{1}{8}$	27 $\frac{3}{4}$	—	—	90 lbs.	20.4	
	25N233629PUOSSL Laminate	1994	22	35 $\frac{1}{8}$	27 $\frac{3}{4}$	—	—	90 lbs.	20.4	
	• Weight capacity: 49 pounds per shelf									
	25N233029PUOSSW Wood	\$ 2913	22	29 $\frac{1}{16}$	27 $\frac{3}{4}$	—	—	85 lbs.	18.0	
	25N233029PUOSSL Laminate	1959	22	29 $\frac{1}{16}$	27 $\frac{3}{4}$	—	—	85 lbs.	18.0	
	• Weight capacity: 40 pounds per shelf									
	25N232429PUOSSW Wood	\$ 2864	22	23 $\frac{3}{4}$	27 $\frac{3}{4}$	—	—	80 lbs.	16.0	
	25N232429PUOSSL Laminate	1927	22	23 $\frac{3}{4}$	27 $\frac{3}{4}$	—	—	80 lbs.	16.0	
	• Weight capacity: 31 pounds per shelf									
	• Specify component worksurfaces and backs to finish as needed									
	• Unit features 4 metal shelves on full extension slides									
	• Shelf sizes are: 18 $\frac{1}{4}$ D x 32 $\frac{1}{16}$ W, 18 $\frac{1}{4}$ D x 26 $\frac{3}{16}$ W, or 18 $\frac{1}{4}$ D x 20 $\frac{1}{16}$ W of storage space and feature a non skid surface									

MIXED-STORAGE CABINET UNDERSURFACE



Left shown

	OPEN STORAGE ON LEFT		OPEN STORAGE ON RIGHT		LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
	MODEL NO.	DESCRIPTION	MODEL NO.	DESCRIPTION		D	W	H	A	KW		
23" DEPTH												
	25N233629PU33W	25N233629PU32W	Wood		\$ 2396	22 $\frac{1}{16}$	35 $\frac{1}{8}$	27 $\frac{3}{4}$	—	—	90 lbs.	20.4
	25N233629PU33L	25N233629PU32L	Laminate		1498	22 $\frac{1}{16}$	35 $\frac{1}{8}$	27 $\frac{3}{4}$	—	—	90 lbs.	20.4
17" DEPTH												
	25N173629PU33W	25N173629PU32W	Wood		\$ 2396	16 $\frac{1}{16}$	35 $\frac{1}{8}$	27 $\frac{3}{4}$	—	—	119 lbs.	16.3
	25N173629PU33L	25N173629PU32L	Laminate		1498	16 $\frac{1}{16}$	35 $\frac{1}{8}$	27 $\frac{3}{4}$	—	—	119 lbs.	16.3
	25N173029PU33W	25N173029PU32W	Wood		\$ 2239	16 $\frac{1}{16}$	29 $\frac{1}{16}$	27 $\frac{3}{4}$	—	—	90 lbs.	13.7
	25N173029PU33L	25N173029PU32L	Laminate		1468	16 $\frac{1}{16}$	29 $\frac{1}{16}$	27 $\frac{3}{4}$	—	—	90 lbs.	13.7
• Specify component worksurfaces and backs to finish as needed												
• Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available												
• When specifying Horizon pulls, lateral files will have 2 pulls on each drawer front												

PRODUCT SPECIFICATIONS

- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 210) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended


TO ORDER, SPECIFY:

1. Model Number
2. Pull
3. Pedestal Grommet
4. Locking
5. Metal Door or Shelf Color
6. Foot Color
7. Laminate Door/Drawer Color
8. Veneer Chassis Finish/
Laminate Chassis Color

SAMPLE MODEL NUMBER:

25N233629PU11L 89PL G22 KRS FR501 MC MC
 • See pages 95-99 for all options available in Epic

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
		D	W	H	A	KW		
MULTI-FILE STORAGE UNDERSURFACE								
FILE STORAGE ON LEFT 23" DEPTH								
25N233629PU11W	\$ 2936	22 ¹ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	90 lbs.	20.4
25N233629PU11L	2045	22 ¹ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	90 lbs.	20.4
25N233029PU11W	\$ 2782	22 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	85 lbs.	18.0
25N233029PU11L	2016	22 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	85 lbs.	18.0
17" DEPTH								
25N173629PU11W	\$ 2936	16 ¹ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	119 lbs.	16.3
25N173629PU11L	2045	16 ¹ / ₁₆	35 ⁷ / ₁₆	27 ³ / ₄	—	—	119 lbs.	16.3
25N173029PU11W	\$ 2782	16 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	90 lbs.	13.7
25N173029PU11L	2016	16 ¹ / ₁₆	29 ¹ / ₁₆	27 ³ / ₄	—	—	90 lbs.	13.7



Left shown

- Specify component worksurfaces and backs to finish as needed
- Locking only on file drawer and lateral file
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
- When specifying Horizon pulls, lateral files will have 2 pulls on each drawer front

PRODUCT SPECIFICATIONS

- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 210) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended

TO ORDER, SPECIFY:


1. Model Number
2. Pedestal Grommet
3. Metal Shelf Color
4. Foot Color
5. Veneer Chassis Finish/
Laminate Chassis Color

SAMPLE MODEL NUMBER:

25N233622PUOSL G22 501 FR501 MC

- See pages 95-99 for all options available in Epic

**OPEN BOOKCASE
UNDERSURFACE
BOX/FILE HEIGHT**



MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
		D	W	H	A	KW		
23" DEPTH								
25N233622PUOSW Wood	\$ 1454	22	35 ⁷ / ₈	21 ⁷ / ₁₆	—	—	90 lbs.	20.4
25N233622PUOSL Laminate	876	22	35 ⁷ / ₈	21 ⁷ / ₁₆	—	—	90 lbs.	20.4
<hr/>								
25N233022PUOSW Wood	\$ 1389	22	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	85 lbs.	18.0
25N233022PUOSL Laminate	844	22	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	85 lbs.	18.0
<hr/>								
25N232422PUOSW Wood	\$ 1336	22	23 ³ / ₄	21 ⁷ / ₁₆	—	—	80 lbs.	16.0
25N232422PUOSL Laminate	813	22	23 ³ / ₄	21 ⁷ / ₁₆	—	—	80 lbs.	16.0
<hr/>								
17" DEPTH								
25N173622PUOSW Wood	\$ 1454	16 ¹ / ₁₆	35 ⁷ / ₈	21 ⁷ / ₁₆	—	—	95 lbs.	12.5
25N173622PUOSL Laminate	876	16 ¹ / ₁₆	35 ⁷ / ₈	21 ⁷ / ₁₆	—	—	95 lbs.	12.5
<hr/>								
25N173022PUOSW Wood	\$ 1389	16 ¹ / ₁₆	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	97 lbs.	10.8
25N173022PUOSL Laminate	844	16 ¹ / ₁₆	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	97 lbs.	10.8
<hr/>								
25N172422PUOSW Wood	\$ 1336	16 ¹ / ₁₆	23 ³ / ₄	21 ⁷ / ₁₆	—	—	67 lbs.	8.4
25N172422PUOSL Laminate	813	16 ¹ / ₁₆	23 ³ / ₄	21 ⁷ / ₁₆	—	—	67 lbs.	8.4

- Specify component worksurfaces and backs to finish as needed
- Unit features an adjustable shelf

PRODUCT SPECIFICATIONS

- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 210) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended
- Panels shipped with appropriate hardware by specifying modesty type; see page 97 for details
- Modesty and back panels are for use in conjunction with undersurface component worksurfaces to create a finished back or enclosed kneewell
- Sliding doors feature a face mount powder coated aluminum track on top and bottom of cabinet


TO ORDER, SPECIFY:

1. Model Number
2. Pull
3. Pedestal Grommet
4. Locking
5. Metal Shelf Color
6. Foot Color
7. Laminate Door/Drawer Color
8. Veneer Chassis Finish/
Laminate Chassis Color
9. Door Track Paint Color

SAMPLE MODEL NUMBER:

25N233622PUSAW 89PL G22 KRS FR501 MC 501

- See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE			DIMENSIONS					CARTONED CUBIC		
		GRADE 1	GRADE 2	GRADE 3	D	W	H	A	KW	WEIGHT	FEET	
SLIDING DOUBLE DOOR UNDERSURFACE BOX/FILE HEIGHT 	RESIN DOORS 23" DEPTH											
	25N233622PUSAW	Wood	\$ 2758	\$ 2974	\$ 3053	22 ¹ / ₁₆	35 ⁷ / ₈	21 ⁷ / ₁₆	—	—	90 lbs.	20.4
	25N233622PUSAL	Laminate	1509	1725	1804	22 ¹ / ₁₆	35 ⁷ / ₈	21 ⁷ / ₁₆	—	—	90 lbs.	20.4
	17" DEPTH											
	25N233022PUSAW	Wood	\$ 2642	\$ 2822	\$ 2888	22 ¹ / ₁₆	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	85 lbs.	18.0
	25N233022PUSAL	Laminate	1424	1604	1670	22 ¹ / ₁₆	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	85 lbs.	18.0
	25N232422PUSAW	Wood	\$ 2539	\$ 2683	\$ 2736	22 ¹ / ₁₆	23 ³ / ₄	21 ⁷ / ₁₆	—	—	80 lbs.	16.0
	25N232422PUSAL	Laminate	1337	1481	1534	22 ¹ / ₁₆	23 ³ / ₄	21 ⁷ / ₁₆	—	—	80 lbs.	16.0
	25N173622PUSAW	Wood	\$ 2758	\$ 2974	\$ 3053	16 ¹ / ₁₆	35 ⁷ / ₈	21 ⁷ / ₁₆	—	—	95 lbs.	12.5
	25N173622PUSAL	Laminate	1509	1725	1804	16 ¹ / ₁₆	35 ⁷ / ₈	21 ⁷ / ₁₆	—	—	95 lbs.	12.5
	25N173022PUSAW	Wood	\$ 2642	\$ 2822	\$ 2888	16 ¹ / ₁₆	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	97 lbs.	10.8
	25N173022PUSAL	Laminate	1424	1604	1670	16 ¹ / ₁₆	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	97 lbs.	10.8
25N172422PUSAW	Wood	\$ 2539	\$ 2683	\$ 2736	16 ¹ / ₁₆	23 ³ / ₄	21 ⁷ / ₁₆	—	—	67 lbs.	8.4	
25N172422PUSAL	Laminate	1337	1481	1534	16 ¹ / ₁₆	23 ³ / ₄	21 ⁷ / ₁₆	—	—	67 lbs.	8.4	

- Specify component worksurfaces and backs to finish as needed
- Unit features an adjustable shelf

PRODUCT SPECIFICATIONS


- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 210) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended
- Panels shipped with appropriate hardware by specifying modesty type; see page 97 for details
- Modesty and back panels are for use in conjunction with undersurface component worksurfaces to create a finished back or enclosed kneewell
- Sliding doors feature a face mount powder coated aluminum track on top and bottom of cabinet

TO ORDER, SPECIFY:

1. Model Number
2. Pull
3. Pedestal Grommet
4. Locking
5. Metal Shelf Color
6. Foot Color
7. Laminate Door/Drawer Color
8. Veneer Chassis Finish/
Laminate Chassis Color
9. Door Track Paint Color

SAMPLE MODEL NUMBER:

25N233622PUSMW 89PL G22 KRB FR501 MC 501
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS				A	KW	CARTONED WEIGHT	CUBIC FEET
			D	W	H					
SLIDING DOUBLE DOOR UNDERSURFACE BOX/FILE HEIGHT 	METAL DOORS 23" DEPTH									
	25N233622PUSMW	Wood	\$ 2758	22 ¹ / ₁₆	35 ⁷ / ₈	21 ⁷ / ₁₆	—	—	90 lbs.	20.4
	25N233622PUSML	Laminate	1509	22 ¹ / ₁₆	35 ⁷ / ₈	21 ⁷ / ₁₆	—	—	90 lbs.	20.4
	25N233022PUSMW	Wood	\$ 2642	22 ¹ / ₁₆	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	85 lbs.	18.0
	25N233022PUSML	Laminate	1424	22 ¹ / ₁₆	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	85 lbs.	18.0
	25N232422PUSMW	Wood	\$ 2539	22 ¹ / ₁₆	23 ³ / ₄	21 ⁷ / ₁₆	—	—	80 lbs.	16.0
	25N232422PUSML	Laminate	1337	22 ¹ / ₁₆	23 ³ / ₄	21 ⁷ / ₁₆	—	—	80 lbs.	16.0
	17" DEPTH									
	25N173622PUSMW	Wood	\$ 2758	16 ¹ / ₁₆	35 ⁷ / ₈	21 ⁷ / ₁₆	—	—	85 lbs.	12.5
	25N173622PUSML	Laminate	1509	16 ¹ / ₁₆	35 ⁷ / ₈	21 ⁷ / ₁₆	—	—	85 lbs.	12.5
	25N173022PUSMW	Wood	\$ 2642	16 ¹ / ₁₆	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	80 lbs.	10.8
	25N173022PUSML	Laminate	1424	16 ¹ / ₁₆	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	80 lbs.	10.8
	25N172422PUSMW	Wood	\$ 2539	16 ¹ / ₁₆	23 ³ / ₄	21 ⁷ / ₁₆	—	—	75 lbs.	8.4
	25N172422PUSML	Laminate	1337	16 ¹ / ₁₆	23 ³ / ₄	21 ⁷ / ₁₆	—	—	75 lbs.	8.4

- Specify component worksurfaces and backs to finish as needed
- Unit features an adjustable shelf

PRODUCT SPECIFICATIONS

- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 210) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended
- Panels shipped with appropriate hardware by specifying modesty type; see page 97 for details
- Modesty and back panels are for use in conjunction with undersurface component worksurfaces to create a finished back or enclosed kneewell


TO ORDER, SPECIFY:

1. Model Number
2. Pull
3. Pedestal Grommet
4. Locking
5. Metal Shelf Color
6. Foot Color
7. Laminate Door/Drawer Color
8. Veneer Chassis Finish/
Laminate Chassis Color


SAMPLE MODEL NUMBERS:

25N233622PUBBLL 89PL G22 KS1S FR501 MC MC
25N233622PUOSSL G22 501 FR501 478

- See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED CUBIC		
			D	W	H	A	KW	WEIGHT	FEET	
STORAGE CABINET METAL SLIDING SHELVES UNDERSURFACE BOX/FILE HEIGHT 	25N233622PUOSSW Wood	\$ 2734	22	35 ⁷ / ₈	21 ⁷ / ₁₆	—	—	90 lbs.	20.4	
	25N233622PUOSSL Laminate	1841	22	35 ⁷ / ₈	21 ⁷ / ₁₆	—	—	90 lbs.	20.4	
	• Weight capacity: 49 pounds per shelf									
	25N233022PUOSSW Wood	\$ 2686	22	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	85 lbs.	18.0	
	25N233022PUOSSL Laminate	1809	22	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	85 lbs.	18.0	
	• Weight capacity: 40 pounds per shelf									
	25N232422PUOSSW Wood	\$ 2638	22	23 ³ / ₄	21 ⁷ / ₁₆	—	—	80 lbs.	16.0	
	25N232422PUOSSL Laminate	1776	22	23 ³ / ₄	21 ⁷ / ₁₆	—	—	80 lbs.	16.0	
	• Weight capacity: 31 pounds per shelf									
	• Specify component worksurfaces and backs to finish as needed									
	• Unit features 3 metal shelves on full extension slides									
	• Shelf sizes are: 18 ¹ / ₂ D x 32 ¹ / ₈ W, 18 ¹ / ₂ D x 26 ¹ / ₈ W, or 18 ¹ / ₂ D x 20 ¹ / ₈ W of storage space and a non skid surface									

BOX/LATERAL FILE UNDERSURFACE BOX/FILE HEIGHT



23" DEPTH

25N233622PUBBLW Wood	\$ 1962	22 ¹ / ₁₆	35 ⁷ / ₈	21 ⁷ / ₁₆	—	—	90 lbs.	20.4
25N233622PUBBLL Laminate	1061	22 ¹ / ₁₆	35 ⁷ / ₈	21 ⁷ / ₁₆	—	—	90 lbs.	20.4
25N233022PUBBLW Wood	\$ 1805	22 ¹ / ₁₆	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	85 lbs.	18.0
25N233022PUBBLL Laminate	1031	22 ¹ / ₁₆	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	85 lbs.	18.0

17" DEPTH

25N173622PUBBLW Wood	\$ 1962	16 ¹ / ₁₆	35 ⁷ / ₈	21 ⁷ / ₁₆	—	—	95 lbs.	12.5
25N173622PUBBLL Laminate	1061	16 ¹ / ₁₆	35 ⁷ / ₈	21 ⁷ / ₁₆	—	—	95 lbs.	12.5
25N173022PUBBLW Wood	\$ 1805	16 ¹ / ₁₆	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	67 lbs.	11.2
25N173022PUBBLL Laminate	1031	16 ¹ / ₁₆	29 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	67 lbs.	11.2

- Specify component worksurfaces and backs to finish as needed
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
- When specifying Horizon pulls, lateral files will have 2 pulls on each drawer front

PRODUCT SPECIFICATIONS


- Pedestals shipped with appropriate hardware
- Pedestals do not include back panels and are 1" less than worksurface depth to accommodate optional back or modesty panels, or to provide space for cable access
- If undersurface storage is used against a wall, a back or modesty panel may be specified, but is not required
- Filler strips (page 210) are recommended to fill the 1" gap
- If undersurface storage is used with Epicenter, a back or modesty panel is not required and pedestal grommet must NOT be specified
- If pedestals are being used in a freestanding open plan, modesty or back panels are ALWAYS recommended
- Panels shipped with appropriate hardware by specifying modesty type; see page 97 for details
- Modesty and back panels are for use in conjunction with undersurface component worksurfaces to create a finished back or enclosed kneewell

TO ORDER, SPECIFY:

1. Model Number
2. Pull
3. Pedestal Grommet
4. Locking
5. Metal Shelf Color
6. Foot Color
7. Laminate Door/Drawer Color
8. Veneer Chassis Finish/
Laminate Chassis Color

SAMPLE MODEL NUMBER:

25N231822PUBFW 89PL G22 KS1S FR501 MC
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
			D	W	H	A	KW			
BOX/FILE UNDERSURFACE BOX/FILE HEIGHT 	23" DEPTH									
	25N231822PUBFW	Wood	\$ 1531	22 ¹ / ₁₆	17 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	70 lbs.	10.0
	25N231822PUBFL	Laminate	939	22 ¹ / ₁₆	17 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	70 lbs.	10.0
	23" DEPTH									
	25N231522PUBFW	Wood	\$ 1442	22 ¹ / ₁₆	14 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	65 lbs.	8.0
	25N231522PUBFL	Laminate	878	22 ¹ / ₁₆	14 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	65 lbs.	8.0
	17" DEPTH									
	25N171822PUBFW	Wood	\$ 1531	16 ¹ / ₁₆	17 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	65 lbs.	7.3
25N171822PUBFL	Laminate	939	16 ¹ / ₁₆	17 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	65 lbs.	7.3	
17" DEPTH										
25N171522PUBFW	Wood	\$ 1442	16 ¹ / ₁₆	14 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	60 lbs.	6.5	
25N171522PUBFL	Laminate	878	16 ¹ / ₁₆	14 ¹ / ₁₆	21 ⁷ / ₁₆	—	—	60 lbs.	6.5	

- Specify component worksurfaces and backs to finish as needed
- Not intended to be used as a hanging pedestal
- Random lock core (KRB, KRS) and specified lock core (KS1B, KS1S) available
- Not intended for use in a freestanding application

PRODUCT SPECIFICATIONS

- Panels shipped with appropriate hardware by specifying modesty type; see page 97 for details
- Modesty and back panels are for use in conjunction with undersurface component worksurfaces to create a finished back or enclosed kneewell

TO ORDER, SPECIFY:


1. Model Number
2. Modesty Type
3. Modesty Grommet
4. Modified Width
5. Veneer Finish/Laminate Color

SAMPLE MODEL NUMBER:

25N9625MPW M G21 X CW

- See pages 95-99 for all options available in Epic

MODESTY PANEL WORKSURFACE HEIGHT



MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
		D	W	H	A	KW		
25N9625MPW Wood	\$ 750	¾	95%	25%	—	—	57 lbs.	3.0
25N9625MPL Laminate	396	¾	95%	25%	—	—	57 lbs.	3.0
25N9025MPW Wood	\$ 707	¾	89%	25%	—	—	54 lbs.	3.0
25N9025MPL Laminate	375	¾	89%	25%	—	—	54 lbs.	3.0
25N8425MPW Wood	\$ 668	¾	83%	25%	—	—	51 lbs.	3.0
25N8425MPL Laminate	354	¾	83%	25%	—	—	51 lbs.	3.0
25N7825MPW Wood	\$ 630	¾	77%	25%	—	—	48 lbs.	2.8
25N7825MPL Laminate	334	¾	77%	25%	—	—	48 lbs.	2.8
25N7225MPW Wood	\$ 594	¾	71%	25%	—	—	45 lbs.	2.8
25N7225MPL Laminate	314	¾	71%	25%	—	—	45 lbs.	2.8
25N6625MPW Wood	\$ 563	¾	65 ¹ / ₁₆	25%	—	—	42 lbs.	2.7
25N6625MPL Laminate	300	¾	65 ¹ / ₁₆	25%	—	—	42 lbs.	2.7
25N6025MPW Wood	\$ 529	¾	59 ¹ / ₁₆	25%	—	—	39 lbs.	2.7
25N6025MPL Laminate	276	¾	59 ¹ / ₁₆	25%	—	—	39 lbs.	2.7
25N5425MPW Wood	\$ 501	¾	53 ¹ / ₁₆	25%	—	—	36 lbs.	2.6
25N5425MPL Laminate	263	¾	53 ¹ / ₁₆	25%	—	—	36 lbs.	2.6
25N4825MPW Wood	\$ 462	¾	47 ³ / ₄	25%	—	—	33 lbs.	2.5
25N4825MPL Laminate	242	¾	47 ³ / ₄	25%	—	—	33 lbs.	2.5
25N4225MPW Wood	\$ 447	¾	41 ³ / ₄	25%	—	—	31 lbs.	2.5
25N4225MPL Laminate	215	¾	41 ³ / ₄	25%	—	—	31 lbs.	2.5
25N3625MPW Wood	\$ 427	¾	35 ³ / ₄	25%	—	—	28 lbs.	2.4
25N3625MPL Laminate	192	¾	35 ³ / ₄	25%	—	—	28 lbs.	2.4

- Modified widths are available on modesty panels in 1/16" increments; when ordering a modified width, specify the modesty panel 3/16" narrower than the corresponding worksurface
- Wood modesty panels have vertical grain
- Laminate modesty panels have horizontal grain

PRODUCT SPECIFICATIONS

- Panels shipped with appropriate hardware by specifying modesty type; see page 97 for details
- Modesty and back panels are for use in conjunction with undersurface component worksurfaces to create a finished back or enclosed kneewell


TO ORDER, SPECIFY:

1. Model Number
2. Modesty Type
3. Modesty Grommet
4. Modified Width
5. Veneer Finish/Laminate Color

SAMPLE MODEL NUMBER:


25N3025MPW M G21 X CW
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
			D	W	H	A	KW		
MODESTY PANEL WORKSURFACE HEIGHT (CONTINUED)	25N3025MPW Wood	\$ 393	¾	29¾	25¾	—	—	25 lbs.	2.3
	25N3025MPL Laminate	170	¾	29¾	25¾	—	—	25 lbs.	2.3
	25N2425MPW Wood	\$ 385	¾	23¾	25¾	—	—	22 lbs.	2.3
	25N2425MPL Laminate	159	¾	23¾	25¾	—	—	22 lbs.	2.3
	25N1825MPW Wood	\$ 376	¾	17 ¹³ / ₁₆	25¾	—	—	19 lbs.	2.2
	25N1825MPL Laminate	145	¾	17 ¹³ / ₁₆	25¾	—	—	19 lbs.	2.2
	25N1525MPW Wood	\$ 370	¾	14 ¹³ / ₁₆	25¾	—	—	17 lbs.	2.2
	25N1525MPL Laminate	126	¾	14 ¹³ / ₁₆	25¾	—	—	17 lbs.	2.2



- Except for models 1825 and 1525, modified widths are available on modesty panels in 1/16" increments; when ordering a modified width, specify the modesty panel 3/16" narrower than the corresponding worksurface
- Wood modesty panels have vertical grain
- Laminate modesty panels have horizontal grain

MODESTY PANEL WORKSURFACE HEIGHT



25N6025MPVL Laminate	\$ 276	¾	59 ¹¹ / ₁₆	25¾	—	—	39 lbs.	2.7
25N5425MPVL Laminate	263	¾	53 ¹¹ / ₁₆	25¾	—	—	36 lbs.	2.6
25N4825MPVL Laminate	242	¾	47¾	25¾	—	—	33 lbs.	2.5
25N4225MPVL Laminate	215	¾	41¾	25¾	—	—	31 lbs.	2.5
25N3625MPVL Laminate	192	¾	35¾	25¾	—	—	28 lbs.	2.4
25N3025MPVL Laminate	170	¾	29¾	25¾	—	—	25 lbs.	2.3
25N2425MPVL Laminate	159	¾	23¾	25¾	—	—	22 lbs.	2.3
25N1825MPVL Laminate	145	¾	17 ¹³ / ₁₆	25¾	—	—	19 lbs.	2.2
25N1525MPVL Laminate	126	¾	14 ¹³ / ₁₆	25¾	—	—	17 lbs.	2.2

- Except for models 1825 and 1525, modified widths are available on modesty panels in 1/16" increments; when ordering a modified width, specify the modesty panel 3/16" narrower than the corresponding worksurface
- Grain direction runs vertically

PRODUCT SPECIFICATIONS

- Panels shipped with appropriate hardware by specifying modesty type; see page 97 for details
- Modesty and back panels are for use in conjunction with undersurface component worksurfaces to create a finished back or enclosed kneewell

TO ORDER, SPECIFY:


1. Model Number
2. Modesty Type
3. Modesty Grommet
4. Modified Width
5. Veneer Finish/Laminate Color

SAMPLE MODEL NUMBER:

25N7425MPW M G21 X CW
 • See pages 95-99 for all options available in Epic

MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED CUBIC	
		D	W	H	A	KW	WEIGHT	FEET
MODESTY PANEL WORKSURFACE HEIGHT								
KNIFE RIM RETURN MODESTY								
25N7425MPW Wood	\$ 594	¾	73⅞	25⅞	—	—	46 lbs.	2.8
25N7425MPL Laminate	314	¾	73⅞	25⅞	—	—	46 lbs.	2.8
25N6825MPW Wood	\$ 563	¾	67⅞	25⅞	—	—	43 lbs.	2.7
25N6825MPL Laminate	300	¾	67⅞	25⅞	—	—	43 lbs.	2.7
25N6225MPW Wood	\$ 529	¾	61⅞	25⅞	—	—	40 lbs.	2.7
25N6225MPL Laminate	276	¾	61⅞	25⅞	—	—	40 lbs.	2.7
25N5625MPW Wood	\$ 501	¾	55⅞	25⅞	—	—	37 lbs.	2.6
25N5625MPL Laminate	263	¾	55⅞	25⅞	—	—	37 lbs.	2.6
25N5025MPW Wood	\$ 462	¾	49⅞	25⅞	—	—	34 lbs.	2.5
25N5025MPL Laminate	242	¾	49⅞	25⅞	—	—	34 lbs.	2.5
25N4425MPW Wood	\$ 447	¾	43⅞	25⅞	—	—	31 lbs.	2.5
25N4425MPL Laminate	215	¾	43⅞	25⅞	—	—	31 lbs.	2.5
<ul style="list-style-type: none"> • For use when creating a return using component knife rim surfaces • Wood modesty panels have vertical grain • Laminate modesty panels have horizontal grain 								

MODESTY PANEL WORKSURFACE HEIGHT



MODEL NO./DESCRIPTION	LIST PRICE	D	W	H	A	KW	WEIGHT	FEET
KNIFE RIM RETURN MODESTY								
25N5625MPVL Laminate	\$ 263	¾	55⅞	25⅞	—	—	37 lbs.	2.6
25N5025MPVL Laminate	242	¾	49⅞	25⅞	—	—	34 lbs.	2.5
25N4425MPVL Laminate	215	¾	43⅞	25⅞	—	—	31 lbs.	2.5

- For use when creating a return using component knife rim surfaces
- Grain direction runs vertically

PRODUCT SPECIFICATIONS


- Panels shipped with appropriate hardware by specifying modesty type; see page 97 for details
- Modesty and back panels are for use in conjunction with undersurface component worksurfaces to create a finished back or enclosed kneewell

TO ORDER, SPECIFY:

1. Model Number
2. Modesty Type
3. Modesty Grommet
4. Modified Width
5. Veneer Finish/Laminate Color


SAMPLE MODEL NUMBER:

25N7525MPW M G21 X CW
 • See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
			D	W	H	A	KW			
MODESTY PANEL WORKSURFACE HEIGHT 	KNIFE RIM BRIDGE MODESTY									
	25N7525MPW	Wood	\$ 594	¾	74 ¹ / ₁₆	25 ³ / ₈	—	—	47 lbs.	2.8
	25N7525MPL	Laminate	314	¾	74 ¹ / ₁₆	25 ³ / ₈	—	—	47 lbs.	2.8
	25N6925MPW	Wood	\$ 563	¾	69	25 ³ / ₈	—	—	45 lbs.	2.8
	25N6925MPL	Laminate	300	¾	69	25 ³ / ₈	—	—	45 lbs.	2.8
	25N6325MPW	Wood	\$ 529	¾	63	25 ³ / ₈	—	—	42 lbs.	2.7
	25N6325MPL	Laminate	276	¾	63	25 ³ / ₈	—	—	42 lbs.	2.7
	25N5725MPW	Wood	\$ 501	¾	57	25 ³ / ₈	—	—	39 lbs.	2.6
	25N5725MPL	Laminate	263	¾	57	25 ³ / ₈	—	—	39 lbs.	2.6
	25N5125MPW	Wood	\$ 462	¾	51	25 ³ / ₈	—	—	36 lbs.	2.6
	25N5125MPL	Laminate	242	¾	51	25 ³ / ₈	—	—	36 lbs.	2.6
	25N4525MPW	Wood	\$ 447	¾	45	25 ³ / ₈	—	—	33 lbs.	2.5
	25N4525MPL	Laminate	215	¾	45	25 ³ / ₈	—	—	33 lbs.	2.5

- For use when creating a bridge using component knife rim surfaces
- Wood modesty panels have vertical grain
- Laminate modesty panels have horizontal grain

MODESTY PANEL WORKSURFACE HEIGHT



	MODEL NO./DESCRIPTION	LIST PRICE	D	W	H	A	KW	CARTONED WEIGHT	CUBIC FEET	
	KNIFE RIM BRIDGE MODESTY									
	25N5725MPVL	Laminate	\$ 263	¾	58 ³ / ₁₆	25 ³ / ₈	—	—	39 lbs.	2.6
	25N5125MPVL	Laminate	242	¾	52 ¹ / ₄	25 ³ / ₈	—	—	36 lbs.	2.6
	25N4525MPVL	Laminate	215	¾	46 ¹ / ₄	25 ³ / ₈	—	—	33 lbs.	2.5

- For use when creating a bridge using component knife rim surfaces
- Grain direction runs vertically

PRODUCT SPECIFICATIONS

- Panels shipped with appropriate hardware by specifying modesty type; see page 97 for details
- Modesty and back panels are for use in conjunction with undersurface component worksurfaces to create a finished back or enclosed kneewell

TO ORDER, SPECIFY:


1. Model Number
2. Modesty Type
3. Modesty Grommet
4. Modified Width
5. Veneer Finish/Laminate Color

SAMPLE MODEL NUMBER:

25N9620MPL M G21 94.5 MC

- See pages 95-99 for all options available in Epic

MODESTY PANEL BOX/FILE HEIGHT



MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
		D	W	H	A	KW		
25N9620MPW Wood	\$ 616	¾	95%	18%	—	—	45 lbs.	2.8
25N9620MPL Laminate	330	¾	95%	18%	—	—	45 lbs.	2.8
25N9020MPW Wood	\$ 574	¾	89%	18%	—	—	43 lbs.	2.7
25N9020MPL Laminate	308	¾	89%	18%	—	—	43 lbs.	2.7
25N8420MPW Wood	\$ 534	¾	83%	18%	—	—	41 lbs.	2.7
25N8420MPL Laminate	286	¾	83%	18%	—	—	41 lbs.	2.7
25N7820MPW Wood	\$ 497	¾	77%	18%	—	—	39 lbs.	2.6
25N7820MPL Laminate	265	¾	77%	18%	—	—	39 lbs.	2.6
25N7220MPW Wood	\$ 460	¾	71%	18%	—	—	36 lbs.	2.6
25N7220MPL Laminate	246	¾	71%	18%	—	—	36 lbs.	2.6
25N6620MPW Wood	\$ 427	¾	65 ¹ / ₁₆	18%	—	—	34 lbs.	2.5
25N6620MPL Laminate	231	¾	65 ¹ / ₁₆	18%	—	—	34 lbs.	2.5
25N6020MPW Wood	\$ 394	¾	59 ¹ / ₁₆	18%	—	—	32 lbs.	2.5
25N6020MPL Laminate	207	¾	59 ¹ / ₁₆	18%	—	—	32 lbs.	2.5
25N5420MPW Wood	\$ 368	¾	53 ¹ / ₁₆	18%	—	—	30 lbs.	2.4
25N5420MPL Laminate	202	¾	53 ¹ / ₁₆	18%	—	—	30 lbs.	2.4
25N4820MPW Wood	\$ 330	¾	47 ³ / ₄	18%	—	—	28 lbs.	2.4
25N4820MPL Laminate	194	¾	47 ³ / ₄	18%	—	—	28 lbs.	2.4
25N4220MPW Wood	\$ 310	¾	41 ³ / ₄	18%	—	—	25 lbs.	2.3
25N4220MPL Laminate	181	¾	41 ³ / ₄	18%	—	—	25 lbs.	2.3
25N3620MPW Wood	\$ 293	¾	35 ³ / ₄	18%	—	—	23 lbs.	2.3
25N3620MPL Laminate	159	¾	35 ³ / ₄	18%	—	—	23 lbs.	2.3

- Modified widths are available on modesty panels in 1/16" increments; when ordering a modified width, specify the modesty panel 3/16" narrower than the corresponding worksurface
- Do not specify modesty type
- Wood modesty panels have vertical grain
- Laminate modesty panels have horizontal grain

PRODUCT SPECIFICATIONS

- Panels shipped with appropriate hardware by specifying modesty type; see page 97 for details
- Modesty and back panels are for use in conjunction with undersurface component worksurfaces to create a finished back or enclosed kneewell


TO ORDER, SPECIFY:

1. Model Number
2. Modesty Type
3. Modesty Grommet
4. Modified Width
5. Veneer Finish/Laminate Color

SAMPLE MODEL NUMBER:


25N3020MPL M G21 94.5 MC

- See pages 95-99 for all options available in Epic

MODESTY PANEL BOX/FILE HEIGHT (CONTINUED)	MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
				D	W	H	A	KW		
	25N3020MPW	Wood	\$ 258	¾	29¾	18⅞	—	—	21 lbs.	2.2
	25N3020MPL	Laminate	138	¾	29¾	18⅞	—	—	21 lbs.	2.2
	25N2420MPW	Wood	\$ 242	¾	23⅞	18⅞	—	—	19 lbs.	2.1
	25N2420MPL	Laminate	112	¾	23⅞	18⅞	—	—	19 lbs.	2.1
	25N1820MPW	Wood	\$ 223	¾	17⅞	18⅞	—	—	17 lbs.	2.1
	25N1820MPL	Laminate	82	¾	17⅞	18⅞	—	—	17 lbs.	2.1
	25N1520MPW	Wood	\$ 189	¾	14⅞	18⅞	—	—	15 lbs.	2.1
	25N1520MPL	Laminate	62	¾	14⅞	18⅞	—	—	15 lbs.	2.1

- Except for models 1820 and 1520, modified widths are available on modesty panels in 1/16" increments; when ordering a modified width, specify the modesty panel 3/16" narrower than the corresponding worksurface
- Wood modesty panels have vertical grain
- Laminate modesty panels have horizontal grain

**MODESTY PANEL
BOX/FILE HEIGHT**



25N6020MPVL	Laminate	\$ 207	¾	59⅞	18⅞	—	—	32 lbs.	2.5
25N5420MPVL	Laminate	202	¾	53⅞	18⅞	—	—	30 lbs.	2.4
25N4820MPVL	Laminate	194	¾	47⅞	18⅞	—	—	28 lbs.	2.4
25N4220MPVL	Laminate	181	¾	41⅞	18⅞	—	—	25 lbs.	2.3
25N3620MPVL	Laminate	159	¾	35⅞	18⅞	—	—	23 lbs.	2.3
25N3020MPVL	Laminate	138	¾	29¾	18⅞	—	—	21 lbs.	2.2
25N2420MPVL	Laminate	112	¾	23⅞	18⅞	—	—	19 lbs.	2.1
25N1820MPVL	Laminate	82	¾	17⅞	18⅞	—	—	17 lbs.	2.1
25N1520MPVL	Laminate	62	¾	14⅞	18⅞	—	—	15 lbs.	2.1

- Except for models 1820 and 1520, modified widths are available on modesty panels in 1/16" increments; when ordering a modified width, specify the modesty panel 3/16" narrower than the corresponding worksurface
- Grain direction runs vertically

PRODUCT SPECIFICATIONS

- Panels shipped with appropriate hardware by specifying modesty type; see page 97 for details
- Modesty and back panels are for use in conjunction with undersurface component worksurfaces to create a finished back or enclosed kneewell

TO ORDER, SPECIFY:


1. Model Number
2. Modesty Type
3. Modesty Grommet
4. Modified Width
5. Veneer Finish/Laminate Color

SAMPLE MODEL NUMBER:

25N96A25MPL M G21 94.5 MC

- See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED CUBIC	
			D	W	H	A	KW	WEIGHT	FEET
MODESTY PANEL FULL OVERLAY FOR STORAGE CREDENZAS (WORKSURFACE HEIGHT)	25N96A25MPL	\$ 396	¾	95¾	25¾	—	—	65 lbs.	11.8
	25N90A25MPL	375	¾	89¾	25¾	—	—	62 lbs.	11.1
	25N84A25MPL	354	¾	83¾	25¾	—	—	58 lbs.	10.4
	25N78A25MPL	334	¾	77¾	25¾	—	—	51 lbs.	7.2
	25N72A25MPL	314	¾	71¾	25¾	—	—	44 lbs.	3.9
	25N66A25MPL	300	¾	65¾	25¾	—	—	41 lbs.	3.6
	25N60A25MPL	276	¾	59¾	25¾	—	—	38 lbs.	3.3




- Modified widths are available on modesty panels in 1/16" increments; when ordering a modified width, specify the modesty panel 1/16" narrower than the corresponding worksurface
- Wood modesty panels have vertical grain
- Laminate modesty panels have horizontal grain

MODESTY PANEL FULL OVERLAY FOR STORAGE CREDENZAS (WORKSURFACE HEIGHT)

25N60A25MPVL	Laminate	\$ 276	¾	59¾	27¾	—	—	38 lbs.	3.3
--------------	----------	--------	---	-----	-----	---	---	---------	-----

- Modified widths are available on modesty panels in 1/16" increments; when ordering a modified width, specify the modesty panel 1/16" narrower than the corresponding worksurface
- Grain direction runs vertically



PRODUCT SPECIFICATIONS

- Panels shipped with appropriate hardware by specifying modesty type; see page 97 for details
- Modesty and back panels are for use in conjunction with undersurface component worksurfaces to create a finished back or enclosed kneewell

TO ORDER, SPECIFY:

1. Model Number
2. Modesty Type
3. Modesty Grommet
4. Modified Width
5. Veneer Finish/Laminate Color

SAMPLE MODEL NUMBER:


25N96A20MPL M G21 94.5 MC

- See pages 95-99 for all options available in Epic



Shaded model numbers are available on our "To You in 10 Days or Less" Quick Delivery program and will be delivered in 10 days or less.


	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
			D	W	H	A	KW		
MODESTY PANEL FULL OVERLAY FOR STORAGE CRENZAS BOX/FILE HEIGHT	25N96A20MPL Laminate	\$ 330	¾"	95¾"	19½"	—	—	60 lbs.	4.1
	25N90A20MPL Laminate	308	¾"	89¾"	19½"	—	—	57 lbs.	4.0
	25N84A20MPL Laminate	286	¾"	83¾"	19½"	—	—	53 lbs.	3.9
	25N78A20MPL Laminate	265	¾"	77¾"	19½"	—	—	46 lbs.	3.8
	Q25N72A20MPL Laminate	246	¾"	71¾"	19½"	—	—	39 lbs.	3.7
	25N72A20MPL Laminate	246	¾"	71¾"	19½"	—	—	39 lbs.	3.7
	25N66A20MPL Laminate	231	¾"	65½"	19½"	—	—	36 lbs.	3.4
	Q25N60A20MPL Laminate	207	¾"	59½"	19½"	—	—	33 lbs.	3.1
	25N60A20MPL Laminate	207	¾"	59½"	19½"	—	—	33 lbs.	3.1



- Full Overlay Modesty to be used on box/file height storage and when layering surfaces
- Modified widths are available on modesty panels in ¼" increments; when ordering a modified width, specify the modesty panel ¼" narrower than the corresponding worksurface
- Wood modesty panels have vertical grain
- Laminate modesty panels have horizontal grain

MODESTY PANEL FULL OVERLAY FOR STORAGE CRENZAS BOX/FILE HEIGHT

25N60A20MPVL Laminate	\$ 207	¾"	59½"	19½"	—	—	33 lbs.	3.1
-----------------------	--------	----	------	------	---	---	---------	-----



- Full Overlay Modesty to be used on box/file height storage and when layering surfaces
- Modified widths are available on modesty panels in ¼" increments; when ordering a modified width, specify the modesty panel ¼" narrower than the corresponding worksurface
- Grain direction runs vertically

EPIC

PRODUCT SPECIFICATIONS

- End panels, filler panels and support panels shipped with appropriate hardware

TO ORDER, SPECIFY:


1. Model Number
2. Modesty/End Panel Grommet
3. Modified Depth
4. Modified Width
5. Veneer Finish/Laminate Color

SAMPLE MODEL NUMBER:

25N3528EPL GE1L X 425

- See pages 95-99 for all options available in Epic


END PANEL (WORKSURFACE HEIGHT)



25N3528EPW	Wood	\$ 571	35 ¹ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	—	—	35 lbs.	1.9
25N3528EPL	Laminate	344	35 ¹ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	—	—	35 lbs.	1.9
25N2928EPW	Wood	\$ 516	29 ³ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	—	—	30 lbs.	1.3
25N2928EPL	Laminate	294	29 ³ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	—	—	30 lbs.	1.3
25N2328EPW	Wood	\$ 501	22 ¹ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	—	—	25 lbs.	1.1
25N2328EPL	Laminate	269	22 ¹ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	—	—	25 lbs.	1.1
25N1728EPW	Wood	\$ 469	17 ¹ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	—	—	18 lbs.	1.1
25N1728EPL	Laminate	250	17 ¹ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	—	—	18 lbs.	1.1

- End panels are required when pedestals are not used to support the end of a unit or workstation
- End panels are 1" shallower than worksurfaces to accommodate a modesty panel or filler strip
- Modified depth available on 35", 29", and 23" models only
- Modesty panels are recommended when building a shell unit

END PANEL (BOX/FILE HEIGHT)



25N2321EPW	Wood	\$ 484	22 ¹ / ₁₆	1 ³ / ₁₆	21 ⁷ / ₁₆	—	—	25 lbs.	1.1
25N2321EPL	Laminate	250	22 ¹ / ₁₆	1 ³ / ₁₆	21 ⁷ / ₁₆	—	—	25 lbs.	1.1
25N1721EPW	Wood	\$ 452	17 ¹ / ₁₆	1 ³ / ₁₆	21 ⁷ / ₁₆	—	—	15 lbs.	1.0
25N1721EPL	Laminate	235	17 ¹ / ₁₆	1 ³ / ₁₆	21 ⁷ / ₁₆	—	—	15 lbs.	1.0

- End panels are required when pedestals are not used to support the end of a unit or workstation
- End panels are 1" shallower than worksurfaces to accommodate a modesty panel or filler strip
- Modified depth available on 23" models only
- Modesty panels are recommended when building a shell unit

PRODUCT SPECIFICATIONS

- End panels, filler panels and support panels shipped with appropriate hardware



Shaded model numbers are available on our "To You in 10 Days or Less" Quick Delivery program and will be delivered in 10 days or less.

TO ORDER, SPECIFY:

1. Model Number
2. Modesty/End Panel Grommet
3. Modified Depth
4. Modified Width
5. Veneer Finish/Laminate Color


SAMPLE MODEL NUMBER:

25N1228SSW GE1L X 425

- See pages 95-99 for all options available in Epic


	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
			D	W	H	A	KW		
SUPPORT PANEL (WORKSURFACE HEIGHT)	25N1228SSW Wood	\$ 346	11 ⁷ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	—	—	15 lbs.	0.8
	25N1228SSL Laminate	126	11 ⁷ / ₁₆	1 ³ / ₁₆	27 ³ / ₄	—	—	15 lbs.	0.8

- For use as added support
- Specify wood or laminate only




SUPPORT PANEL (BOX/FILE HEIGHT)	25N1221SSW Wood	\$ 331	11 ⁷ / ₁₆	1 ³ / ₁₆	21 ⁷ / ₁₆	—	—	16 lbs.	0.8
	25N1221SSL Laminate	109	11 ⁷ / ₁₆	1 ³ / ₁₆	21 ⁷ / ₁₆	—	—	16 lbs.	0.8

- For use as added support
- Specify wood or laminate only




SUPPORT PANEL U-STYLE	NAC1228UBC Concrete	\$ 414	1 ¹ / ₂	12	28	—	—	12 lbs.	3.1
	NAC1228UBB Cinder	414	1 ¹ / ₂	12	28	—	—	12 lbs.	3.1
	NAC1228UBI Iron	414	1 ¹ / ₂	12	28	—	—	12 lbs.	3.1
	NAC1228UBS Platinum Metallic	414	1 ¹ / ₂	12	28	—	—	12 lbs.	3.1
	NAC1228UBN Satin Nickel Metallic	414	1 ¹ / ₂	12	28	—	—	12 lbs.	3.1
	NAC1228UBH Designer White	414	1 ¹ / ₂	12	28	—	—	12 lbs.	3.1

- For use as added support
- Adjustable glides are standard
- Specify model number only
- Metal mounting plate attached to support panel



UNDERSURFACE SUPPORT RAIL (WORKSURFACE)	QNAC0248SUR	\$ 200	2 ³ / ₄	48	1	—	—	5 lbs.	0.5
	NAC0248SUR	200	2 ³ / ₄	48	1	—	—	5 lbs.	0.5
	QNAC0236SUR	171	2 ³ / ₄	36	1	—	—	3 lbs.	0.3
	NAC0236SUR	171	2 ³ / ₄	36	1	—	—	3 lbs.	0.3

- Specify model number only
- Model recommended for use when the weight on the table has a uniform weight above 125 lbs. or if the span between table legs or support structures is greater than 48" on a 1³/₁₆" worksurface and greater than 60" on a 1¹/₁₆" worksurface
- Specify the 36" model to be used up to 66" worksurfaces
- Specify the 48" model to be used up to 72" worksurfaces
- Specify with worksurfaces when overlapping box/file height storage, sit on box/file height storage and supports worksurface height worksurfaces



PRODUCT SPECIFICATIONS

- End panels, filler panels and support panels shipped with appropriate hardware


TO ORDER, SPECIFY:

1. Model Number
2. Grommet
3. Veneer Finish/Laminate Color

SAMPLE MODEL NUMBER:

25N4228STL GE1R 480

- See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
				D	W	H	A	KW		
T-SUPPORT PANEL (WORKSURFACE HEIGHT)	25N4228STW	Wood	\$ 951	41 ⁷ / ₈	1 ³ / ₈	27 ³ / ₄	—	—	49 lbs.	3.4
	25N4228STL	Laminate	508	41 ⁷ / ₈	1 ³ / ₈	27 ³ / ₄	—	—	49 lbs.	3.4
	25N3628STW	Wood	\$ 902	35 ⁷ / ₈	1 ³ / ₈	27 ³ / ₄	—	—	43 lbs.	2.9
	25N3628STL	Laminate	460	35 ⁷ / ₈	1 ³ / ₈	27 ³ / ₄	—	—	43 lbs.	2.9
	25N3028STW	Wood	\$ 853	29 ¹ / ₈	1 ³ / ₈	27 ³ / ₄	—	—	38 lbs.	2.5
	25N3028STL	Laminate	410	29 ¹ / ₈	1 ³ / ₈	27 ³ / ₄	—	—	38 lbs.	2.5
	25N2428STW	Wood	\$ 832	22 ¹ / ₈	1 ³ / ₈	27 ³ / ₄	—	—	32 lbs.	2.1
	25N2428STL	Laminate	381	22 ¹ / ₈	1 ³ / ₈	27 ³ / ₄	—	—	32 lbs.	2.1
	25N1828STW	Wood	\$ 778	17 ¹ / ₈	1 ³ / ₈	27 ³ / ₄	—	—	28 lbs.	1.4
	25N1828STL	Laminate	356	17 ¹ / ₈	1 ³ / ₈	27 ³ / ₄	—	—	28 lbs.	1.4

- Some assembly required
- Specify with U-surfaces, extended U-surfaces, P-surfaces, extended P-surfaces, and J-surfaces

PRODUCT SPECIFICATIONS


- End panels, filler panels and support panels shipped with appropriate hardware

TO ORDER, SPECIFY:


1. Model Number
2. Grommet
3. Veneer Finish/Laminate Color

SAMPLE MODEL NUMBER:

- 25N3606STL GE1R 480
- See pages 95-99 for all options available in Epic

	MODEL NO./DESCRIPTION	LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET
			D	W	H	A	KW		
 <p>T-SUPPORT PANEL (BOX/FILE HEIGHT) (Not for use with modesty panel)</p>	25N3606STW Wood	\$ 451	35 ⁷ / ₈	1 ³ / ₈	4 ⁷ / ₈	—	—	21 lbs.	2.0
	25N3606STL Laminate	229	35 ⁷ / ₈	1 ³ / ₈	4 ⁷ / ₈	—	—	21 lbs.	2.0
	25N3006STW Wood	\$ 427	29 ¹ / ₂	1 ³ / ₈	4 ⁷ / ₈	—	—	19 lbs.	1.8
	25N3006STL Laminate	205	29 ¹ / ₂	1 ³ / ₈	4 ⁷ / ₈	—	—	19 lbs.	1.8
	25N2406STW Wood	\$ 416	22 ¹ / ₂	1 ³ / ₈	4 ⁷ / ₈	—	—	16 lbs.	1.6
	25N2406STL Laminate	191	22 ¹ / ₂	1 ³ / ₈	4 ⁷ / ₈	—	—	16 lbs.	1.6
	25N1806STW Wood	\$ 389	17 ¹ / ₂	1 ³ / ₈	4 ⁷ / ₈	—	—	12 lbs.	1.1
	25N1806STL Laminate	177	17 ¹ / ₂	1 ³ / ₈	4 ⁷ / ₈	—	—	12 lbs.	1.1

- Some assembly required
- Specify with worksurfaces when overlapping box/file height storage, sits on box/file height storage and supports overlapping worksurfaces
- 36, 30, 24, and 18 models not to be used with modesty panels

 <p>T-SUPPORT PANEL (BOX/FILE HEIGHT) (For use with modesty panel)</p>	25N3506STW Wood	\$ 428	35 ⁷ / ₈	1 ³ / ₈	4 ⁷ / ₈	—	—	21 lbs.	2.0
	25N3506STL Laminate	217	35 ⁷ / ₈	1 ³ / ₈	4 ⁷ / ₈	—	—	21 lbs.	2.0
	25N2906STW Wood	\$ 406	29 ¹ / ₂	1 ³ / ₈	4 ⁷ / ₈	—	—	19 lbs.	1.8
	25N2906STL Laminate	194	29 ¹ / ₂	1 ³ / ₈	4 ⁷ / ₈	—	—	19 lbs.	1.8
	25N2306STW Wood	\$ 395	22 ¹ / ₂	1 ³ / ₈	4 ⁷ / ₈	—	—	16 lbs.	1.6
	25N2306STL Laminate	181	22 ¹ / ₂	1 ³ / ₈	4 ⁷ / ₈	—	—	16 lbs.	1.6
	25N1706STW Wood	\$ 370	17 ¹ / ₂	1 ³ / ₈	4 ⁷ / ₈	—	—	12 lbs.	1.1
	25N1706STL Laminate	168	17 ¹ / ₂	1 ³ / ₈	4 ⁷ / ₈	—	—	12 lbs.	1.1

- Some assembly required
- Specify with worksurfaces when overlapping box/file height storage, sits on box/file height storage and supports overlapping worksurfaces
- 35, 29, 23, and 17 models are 1" shallower than worksurface to accommodate a modesty panel

PRODUCT SPECIFICATIONS


- End panels, filler panels and support panels shipped with appropriate hardware

TO ORDER, SPECIFY:


1. Model Number
2. Grommet
3. Veneer Finish/Laminate Color

SAMPLE MODEL NUMBER:


- 25N3039SLLW GE1R 480
- See pages 95-99 for all options available in Epic

CORNER SUPPORT PRIVACY PANEL	MODEL NO./DESCRIPTION		LIST PRICE	DIMENSIONS					CARTONED WEIGHT	CUBIC FEET	
	LEFT HANDED	RIGHT HANDED		D	W	H	A	KW			
 <p>25N3039SLLW Left shown</p>	25N3039SLLW	25N3039SLRW	Wood	\$ 1189	31 ¹ / ₁₆	31 ¹ / ₄	39 ¹ / ₁₆	—	—	60 lbs.	2.8
	25N3039SLLL	25N3039SLRL	Laminate	680	31 ¹ / ₁₆	31 ¹ / ₄	39 ¹ / ₁₆	—	—	60 lbs.	2.8
	25N2439SLLW	25N2439SLRW	Wood	\$ 1154	25 ¹ / ₁₆	25 ¹ / ₄	39 ¹ / ₁₆	—	—	60 lbs.	2.8
	25N2439SLLL	25N2439SLRL	Laminate	620	25 ¹ / ₁₆	25 ¹ / ₄	39 ¹ / ₁₆	—	—	60 lbs.	2.8
	25N3239SLLW	25N3239SLRW	Wood	\$ 1189	32 ¹ / ₁₆	31 ¹ / ₄	39 ¹ / ₁₆	—	—	60 lbs.	2.8
	25N3239SLLL	25N3239SLRL	Laminate	680	32 ¹ / ₁₆	31 ¹ / ₄	39 ¹ / ₁₆	—	—	60 lbs.	2.8
	25N2639SLLW	25N2639SLRW	Wood	\$ 1154	26 ¹ / ₁₆	25 ¹ / ₄	39 ¹ / ₁₆	—	—	60 lbs.	2.8
	25N2639SLLL	25N2639SLRL	Laminate	620	26 ¹ / ₁₆	25 ¹ / ₄	39 ¹ / ₁₆	—	—	60 lbs.	2.8


- Some assembly required
- 32" and 26" models are to be used with K1 worksurfaces
- 30" and 24" models are to be used with 30" and 24" deep worksurfaces
- Corner supports can be used in place of undersurface support or support panels

FILLER STRIP (WORKSURFACE HEIGHT)	MODEL NO./DESCRIPTION	LIST PRICE	D	W	H	A	KW	CARTONED WEIGHT	CUBIC FEET	
	25N28CPFSW	Wood	\$ 55	3/4	2 ¹ / ₁₆	25 ³ / ₈	—	—	19 lbs.	1.8
	25N28CPFSL	Laminate	40	3/4	2 ¹ / ₁₆	25 ³ / ₈	—	—	19 lbs.	1.8

- When pedestals are positioned against a wall and a modesty panel is not used, specify a filler strip to fill the 1" gap between the work surface and pedestal depths

FILLER STRIP (BOX/FILE HEIGHT)	MODEL NO./DESCRIPTION	LIST PRICE	D	W	H	A	KW	CARTONED WEIGHT	CUBIC FEET	
	25N21CPFSW	Wood	\$ 38	3/4	2 ¹ / ₁₆	18 ⁷ / ₈	—	—	16 lbs.	1.6
	25N21CPFSL	Laminate	26	3/4	2 ¹ / ₁₆	18 ⁷ / ₈	—	—	16 lbs.	1.6

- When pedestals are positioned against a wall and a modesty panel is not used, specify a filler strip to fill the 1" gap between the work surface and pedestal depths

SUPPORT BASE BRACKET	MODEL NO./DESCRIPTION	LIST PRICE	D	W	H	A	KW	CARTONED WEIGHT	CUBIC FEET
	25N04BKT	\$ 26	3/8	4 ¹ / ₁₆	—	—	—	1 lbs.	0.3

- Specify metal paint color 462 Cinder, 501 Platinum Metallic, or 503 Satin Nickel Metallic
- For use with an extension surface and using a full modesty

WORKSURFACE WIRE MANAGER FILLER CAP	MODEL NO./DESCRIPTION	LIST PRICE	D	W	H	A	KW	CARTONED WEIGHT	CUBIC FEET
	NAC01WMFM	\$ 18	1	1	1	—	—	1 lbs.	0.5

- Specify paint color
- Paint options and recommendations are listed on page 96